

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1283267

Luminaire Tested: P3AS09R35B2750DE010 E3DLP1WH_2700K

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1283267
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-19)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R35B2750DE010 E3DLP1WH_2700K
Description: 3in Adjustable Boosted Cyan Tunable White LED luminaire with, R35 optic, 2700K CCT AND, 90CRI , E3DLP1WH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 615.0 lumens
Efficiency: N/A
Efficacy: 46.9 lumens/watt
Spacing Criteria (0/90/45): 0.58 / 0.58 / 0.58
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 13.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1283267

CATALOG NUMBER: P3AS09R35B2750DE010 E3DLP1WH_2700K

Luminous Intensity Polar Plot



CATALOG NUMBER: P3AS09R35B2750DE010 E3DLP1WH_2700K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20					
RC	80					70					50					30					10					0
RW	70	50	30	10		70	50	30	10		50	30	10		50	30	10		50	30	10		0			
RCR																										
0	119	119	119	119		116	116	116	116		111	111	111		106	106	106		102	102	102		100			
1	114	112	109	107		112	109	107	106		105	104	102		102	100	99		98	97	96		95			
2	109	105	101	98		107	103	100	97		100	97	95		97	95	93		94	93	91		90			
3	105	99	95	91		103	98	94	90		95	92	89		93	90	88		91	88	86		85			
4	100	94	89	85		99	93	88	85		91	87	84		89	85	83		87	84	82		80			
5	96	89	84	80		95	88	83	80		86	82	79		85	81	78		83	80	78		76			
6	92	85	80	76		91	84	79	76		83	78	75		81	77	75		80	77	74		73			
7	89	81	76	72		88	80	75	72		79	75	71		78	74	71		77	73	71		70			
8	85	77	72	69		84	77	72	68		76	71	68		75	71	68		74	70	68		66			
9	82	74	69	66		81	74	69	65		73	68	65		72	68	65		71	68	65		64			
10	79	71	66	63		78	71	66	63		70	66	63		69	65	62		69	65	62		61			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	310173
5°	298106
10°	259737
15°	198934
20°	133105
25°	80545
30°	46210
35°	25832
40°	13740
45°	7071
50°	3377
55°	2676
60°	2588
65°	2127
70°	2244
75°	1949
80°	2273
85°	1510

MAXIMUM LUMINANCE 45°-90°:

Luminance: 7071 cd/sqm

TEST NUMBER: P1283267

CATALOG NUMBER: P3AS09R35B2750DE010 E3DLP1WH_2700K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	123.2	20.0
10°-20°	238.8	38.8
20°-30°	156.3	25.4
30°-40°	63.4	10.3
40°-50°	19.0	3.1
50°-60°	6.5	1.0
60°-70°	4.3	0.7
70°-80°	2.5	0.4
80°-90°	0.9	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	518.3	84.3
0°-40°	581.7	94.6
0°-60°	607.2	98.7
0°-90°	615.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	615.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1414	
5°	1354	123
15°	876	239
25°	333	156
35°	96	63
45°	23	19
55°	7	6
65°	4	4
75°	2	3
85°	1	1
90°	0	

TEST NUMBER: P1283267

CATALOG NUMBER: P3AS09R35B2750DE010 E3DLP1WH_2700K

CANDELA DISTRIBUTION (FULL):

0°	
0°	1414.5
1°	1412.2
2°	1405.8
3°	1392.9
4°	1377.7
5°	1354.3
6°	1325.0
7°	1292.3
8°	1255.4
9°	1213.3
10°	1166.5
11°	1114.4
12°	1060.0
13°	999.2
14°	941.3
15°	876.3
17.5°	719.0
20°	570.4
22.5°	438.8
25°	332.9
27.5°	248.0
30°	182.5
32.5°	134.0
35°	96.5
37.5°	68.4
40°	48.0
42.5°	33.3
45°	22.8
47.5°	15.2
50°	9.9
52.5°	7.6
55°	7.0
57.5°	6.4
60°	5.9
62.5°	5.3
65°	4.1
67.5°	3.5
70°	3.5
72.5°	2.9
75°	2.3
77.5°	1.8
80°	1.8
82.5°	1.2
85°	0.6
87.5°	0.6



TEST NUMBER: P1283267

CATALOG NUMBER: P3AS09R35B2750DE010 E3DLP1WH_2700K

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0

(END OF REPORT)