

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1283926

Luminaire Tested: P3AS09R60B2750DE010 E3DL1MW_5000K

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1283926
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-39)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R60B2750DE010 E3DL1MW_5000K
Description: 3in Adjustable Boosted Cyan Tunable White LED luminaire with, R60 optic, 5000K CCT AND, 80CRI , E3DL1MW TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 659.0 lumens
Efficiency: N/A
Efficacy: 50.3 lumens/watt
Spacing Criteria (0/90/45): 0.87 / 0.87 / 0.87
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 13.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1283926

CATALOG NUMBER: P3AS09R60B2750DE010 E3DL1MW_5000K

Luminous Intensity Polar Plot



TEST NUMBER: P1283926

CATALOG NUMBER: P3AS09R60B2750DE010 E3DL1MW_5000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	105	111	108	106	103	104	102	100		100	99	97		97
2	107	102	98	94	105	100	96	93	97	94	91		94	91	89		91
3	101	95	89	85	99	93	88	84	91	86	83		88	85	82		86
4	96	88	82	78	94	87	81	77	85	80	76		83	79	75		81
5	91	82	76	71	89	81	75	71	79	74	70		78	73	70		76
6	86	77	70	66	84	76	70	66	74	69	65		73	68	65		72
7	82	72	66	61	80	71	65	61	70	65	61		69	64	60		67
8	77	68	61	57	76	67	61	57	66	60	57		65	60	56		64
9	74	64	57	53	72	63	57	53	62	57	53		61	56	53		60
10	70	60	54	50	69	60	54	50	59	53	50		58	53	50		57

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	155602
5°	154127
10°	149652
15°	140205
20°	124097
25°	103796
30°	81354
35°	59026
40°	39274
45°	24468
50°	13236
55°	3823
60°	3552
65°	3269
70°	3206
75°	3219
80°	3157
85°	3271

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 24468 cd/sqm

TEST NUMBER: P1283926

CATALOG NUMBER: P3AS09R60B2750DE010 E3DL1MW_5000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	65.9	10.0
10°-20°	171.3	26.0
20°-30°	195.3	29.6
30°-40°	138.5	21.0
40°-50°	62.8	9.5
50°-60°	13.3	2.0
60°-70°	6.4	1.0
70°-80°	4.0	0.6
80°-90°	1.4	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	432.6	65.6
0°-40°	571.1	86.7
0°-60°	647.3	98.2
0°-90°	659.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	659.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	710	
5°	700	66
15°	618	171
25°	429	195
35°	220	139
45°	79	63
55°	10	13
65°	6	6
75°	4	4
85°	1	1
90°	0	

TEST NUMBER: P1283926

CATALOG NUMBER: P3AS09R60B2750DE010 E3DL1MW_5000K

CANDELA DISTRIBUTION (FULL):

0°	
0°	709.6
2.5°	707.1
5°	700.2
7.5°	688.3
10°	672.1
12.5°	648.9
15°	617.6
17.5°	578.1
20°	531.8
22.5°	481.7
25°	429.0
27.5°	375.2
30°	321.3
32.5°	270.0
35°	220.5
37.5°	176.6
40°	137.2
42.5°	104.0
45°	78.9
47.5°	58.9
50°	38.8
52.5°	18.2
55°	10.0
57.5°	8.8
60°	8.1
62.5°	7.5
65°	6.3
67.5°	5.6
70°	5.0
72.5°	4.4
75°	3.8
77.5°	3.1
80°	2.5
82.5°	1.9
85°	1.3
87.5°	0.6
90°	0.0

(END OF REPORT)