

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1283953

Luminaire Tested: P3AS09R60B2750DE010 E3DLD1MW\_3000K

Issue Date: 1/30/2026

**Test Information**

Test Method: LM-79-2019  
Report Number: P1283953  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-38)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: IRiS  
Catalog Number: P3AS09R60B2750DE010 E3DLD1MW\_3000K  
Description: 3in Adjustable Boosted Cyan Tunable White LED luminaire with, R60 optic, 3000K CCT AND, 90CRI , E3DLD1MW TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 475.0 lumens  
Efficiency: N/A  
Efficacy: 36.3 lumens/watt  
Spacing Criteria (0/90/45): 0.94 / 0.94 / 1  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct

Input Watts (W): 13.1  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1283953

CATALOG NUMBER: P3AS09R60B2750DE010 E3DLD1MW\_3000K

### Luminous Intensity Polar Plot





TEST NUMBER: P1283953

CATALOG NUMBER: P3AS09R60B2750DE010 E3DLD1MW\_3000K

### COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

|     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |  |  |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|--|
| RF  | 20  |     |     |     | 20  |     |     |     | 20  |     |     |     | 20  |     |     |     | 20  |     |  |  |
| RC  | 80  |     |     |     | 70  |     |     |     | 50  |     |     |     | 30  |     |     |     | 10  |     |  |  |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50  | 30  | 10  | 50  | 30  | 10  | 50  | 30  | 10  | 0   |  |  |
| RCR |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |  |  |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 | 106 | 106 | 106 | 102 | 102 | 102 | 100 |  |  |
| 1   | 112 | 109 | 106 | 103 | 110 | 107 | 104 | 101 | 102 | 100 | 98  | 99  | 97  | 95  | 95  | 94  | 93  | 91  |  |  |
| 2   | 105 | 99  | 94  | 90  | 103 | 97  | 93  | 89  | 94  | 90  | 87  | 91  | 88  | 85  | 88  | 86  | 84  | 82  |  |  |
| 3   | 99  | 91  | 85  | 80  | 96  | 89  | 84  | 79  | 87  | 82  | 78  | 84  | 80  | 77  | 82  | 78  | 76  | 74  |  |  |
| 4   | 92  | 83  | 77  | 72  | 90  | 82  | 76  | 71  | 80  | 75  | 70  | 78  | 73  | 70  | 76  | 72  | 69  | 67  |  |  |
| 5   | 87  | 77  | 70  | 65  | 85  | 76  | 69  | 65  | 74  | 68  | 64  | 72  | 67  | 63  | 71  | 66  | 63  | 61  |  |  |
| 6   | 82  | 71  | 64  | 59  | 80  | 70  | 64  | 59  | 69  | 63  | 58  | 67  | 62  | 58  | 66  | 61  | 58  | 56  |  |  |
| 7   | 77  | 66  | 59  | 54  | 75  | 65  | 59  | 54  | 64  | 58  | 54  | 63  | 57  | 53  | 61  | 57  | 53  | 51  |  |  |
| 8   | 72  | 61  | 55  | 50  | 71  | 61  | 54  | 50  | 60  | 54  | 49  | 59  | 53  | 49  | 58  | 53  | 49  | 47  |  |  |
| 9   | 68  | 57  | 51  | 46  | 67  | 57  | 50  | 46  | 56  | 50  | 46  | 55  | 49  | 46  | 54  | 49  | 45  | 44  |  |  |
| 10  | 65  | 54  | 47  | 43  | 64  | 53  | 47  | 43  | 52  | 47  | 43  | 52  | 46  | 42  | 51  | 46  | 42  | 41  |  |  |

**AVERAGE LUMINANCE (cd/sqm):**

|     |       |
|-----|-------|
|     | 0°    |
| 0°  | 84313 |
| 5°  | 83381 |
| 10° | 80493 |
| 15° | 76028 |
| 20° | 70099 |
| 25° | 63463 |
| 30° | 56338 |
| 35° | 48158 |
| 40° | 38272 |
| 45° | 27011 |
| 50° | 16136 |
| 55° | 8143  |
| 60° | 7850  |
| 65° | 7160  |
| 70° | 6668  |
| 75° | 6354  |
| 80° | 5809  |
| 85° | 4277  |

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°

Vertical Angle:  $45^\circ$

Luminance: 27011 cd/sqm

TEST NUMBER: P1283953

CATALOG NUMBER: P3AS09R60B2750DE010 E3DLD1MW\_3000K

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 35.6   | 7.5       |
| 10°-20°   | 93.6   | 19.7      |
| 20°-30°   | 120.2  | 25.3      |
| 30°-40°   | 111.4  | 23.5      |
| 40°-50°   | 67.9   | 14.3      |
| 50°-60°   | 22.6   | 4.8       |
| 60°-70°   | 13.8   | 2.9       |
| 70°-80°   | 7.8    | 1.6       |
| 80°-90°   | 2.2    | 0.5       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| <hr/>     |        |           |
| 0°-30°    | 249.4  | 52.5      |
| 0°-40°    | 360.8  | 76.0      |
| 0°-60°    | 451.3  | 95.0      |
| 0°-90°    | 475.0  | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 475.0  | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°  | Flux |
|-----|-----|------|
| 0°  | 384 |      |
| 5°  | 379 | 36   |
| 15° | 335 | 94   |
| 25° | 262 | 120  |
| 35° | 180 | 111  |
| 45° | 87  | 68   |
| 55° | 21  | 23   |
| 65° | 14  | 14   |
| 75° | 8   | 8    |
| 85° | 2   | 2    |
| 90° | 0   |      |

TEST NUMBER: P1283953

CATALOG NUMBER: P3AS09R60B2750DE010 E3DLD1MW\_3000K

**CANDELA DISTRIBUTION (FULL):**

| 0°    |       |
|-------|-------|
| 0°    | 384.5 |
| 2.5°  | 382.8 |
| 5°    | 378.8 |
| 7.5°  | 371.3 |
| 10°   | 361.5 |
| 12.5° | 349.4 |
| 15°   | 334.9 |
| 17.5° | 318.2 |
| 20°   | 300.4 |
| 22.5° | 281.3 |
| 25°   | 262.3 |
| 27.5° | 242.7 |
| 30°   | 222.5 |
| 32.5° | 202.4 |
| 35°   | 179.9 |
| 37.5° | 156.2 |
| 40°   | 133.7 |
| 42.5° | 110.1 |
| 45°   | 87.1  |
| 47.5° | 67.5  |
| 50°   | 47.3  |
| 52.5° | 28.2  |
| 55°   | 21.3  |
| 57.5° | 19.6  |
| 60°   | 17.9  |
| 62.5° | 15.6  |
| 65°   | 13.8  |
| 67.5° | 12.1  |
| 70°   | 10.4  |
| 72.5° | 8.6   |
| 75°   | 7.5   |
| 77.5° | 5.8   |
| 80°   | 4.6   |
| 82.5° | 2.9   |
| 85°   | 1.7   |
| 87.5° | 1.2   |
| 90°   | 0.0   |

(END OF REPORT)