

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1284251

Luminaire Tested: P3AS09R70B2750DE010 E3DLP1WH_5000K

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1284251
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-47)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R70B2750DE010 E3DLP1WH_5000K
Description: 3in Adjustable Boosted Cyan Tunable White LED luminaire with, R70 optic, 5000K CCT AND, 80CRI , E3DLP1WH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 631.0 lumens
Efficiency: N/A
Efficacy: 48.2 lumens/watt
Spacing Criteria (0/90/45): 0.97 / 0.97 / 0.98
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 13.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1284251

CATALOG NUMBER: P3AS09R70B2750DE010 E3DLP1WH_5000K

Luminous Intensity Polar Plot



TEST NUMBER: P1284251

CATALOG NUMBER: P3AS09R70B2750DE010 E3DLP1WH_5000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	107	104	110	107	105	103	103	101	100		100	98	97		96
2	106	101	96	93	104	99	95	92	96	93	90		93	90	88		90
3	100	93	88	83	98	92	87	82	89	85	81		86	83	80		84
4	94	86	80	75	93	85	79	75	83	78	74		81	76	73		79
5	89	80	73	69	87	79	73	68	77	72	68		75	71	67		74
6	84	74	68	63	82	73	67	63	72	66	62		70	65	62		69
7	79	69	62	58	78	68	62	58	67	61	57		66	61	57		65
8	75	65	58	53	74	64	58	53	63	57	53		62	57	53		61
9	71	60	54	50	70	60	54	50	59	53	49		58	53	49		57
10	67	57	50	46	66	56	50	46	55	50	46		55	49	46		54

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	122161
5°	120691
10°	117210
15°	112237
20°	105126
25°	95522
30°	82494
35°	65745
40°	47890
45°	31476
50°	14737
55°	4549
60°	4386
65°	4203
70°	4039
75°	4236
80°	3915
85°	3271

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 31476 cd/sqm

TEST NUMBER: P1284251

CATALOG NUMBER: P3AS09R70B2750DE010 E3DLP1WH_5000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	51.6	8.2
10°-20°	138.4	21.9
20°-30°	179.8	28.5
30°-40°	152.6	24.2
40°-50°	78.7	12.5
50°-60°	15.2	2.4
60°-70°	8.2	1.3
70°-80°	5.0	0.8
80°-90°	1.5	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	369.8	58.6
0°-40°	522.4	82.8
0°-60°	616.3	97.7
0°-90°	631.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	631.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	557	
5°	548	52
15°	494	138
25°	395	180
35°	246	153
45°	102	79
55°	12	15
65°	8	8
75°	5	5
85°	1	1
90°	0	

TEST NUMBER: P1284251

CATALOG NUMBER: P3AS09R70B2750DE010 E3DLP1WH_5000K

CANDELA DISTRIBUTION (FULL):

0°	
0°	557.1
2.5°	555.2
5°	548.3
7.5°	538.3
10°	526.4
12.5°	511.3
15°	494.4
17.5°	473.7
20°	450.5
22.5°	424.2
25°	394.8
27.5°	361.6
30°	325.8
32.5°	286.4
35°	245.6
37.5°	205.5
40°	167.3
42.5°	131.6
45°	101.5
47.5°	74.6
50°	43.2
52.5°	18.8
55°	11.9
57.5°	11.3
60°	10.0
62.5°	9.4
65°	8.1
67.5°	7.5
70°	6.3
72.5°	5.6
75°	5.0
77.5°	3.8
80°	3.1
82.5°	1.9
85°	1.3
87.5°	0.6
90°	0.0

(END OF REPORT)