

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1284418

Luminaire Tested: P3AS13R15B2750DE010 E3PHLD1MW_3000K

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1284418
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2509-551-9)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R15B2750DE010 E3PHLD1MW_3000K
Description: 3in Adjustable Boosted Cyan Tunable White LED luminaire with, R15 optic, 3000K CCT AND, 90CRI , E3PHLD1MW TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 498.0 lumens
Efficiency: N/A
Efficacy: 26.1 lumens/watt
Spacing Criteria (0/90/45): 0.56 / 0.56 / 0.66
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 19.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1284418

CATALOG NUMBER: P3AS13R15B2750DE010 E3PHLD1MW_3000K

Luminous Intensity Polar Plot



TEST NUMBER: P1284418

CATALOG NUMBER: P3AS13R15B2750DE010 E3PHLD1MW_3000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	108	105	102	109	106	103	101	102	100	97		98	96	95		95
2	104	98	93	89	102	97	92	88	93	89	86		90	87	84		87
3	98	90	84	79	96	88	83	78	85	81	77		83	79	75		81
4	92	82	76	70	90	81	75	70	79	73	69		77	72	68		75
5	86	76	69	64	84	75	68	63	73	67	63		71	66	62		70
6	81	71	63	58	79	70	63	58	68	62	58		67	61	57		65
7	77	66	59	54	75	65	58	54	64	58	53		62	57	53		61
8	72	61	55	50	71	61	54	50	60	54	49		59	53	49		58
9	69	58	51	47	68	57	51	46	56	50	46		55	50	46		54
10	65	54	48	44	64	54	48	44	53	47	43		52	47	43		52

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	144923
5°	135857
10°	111399
15°	86539
20°	68326
25°	54439
30°	43703
35°	35683
40°	29398
45°	24716
50°	21253
55°	18389
60°	16271
65°	14165
70°	12630
75°	10167
80°	8334
85°	5535

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 24716 cd/sqm

TEST NUMBER: P1284418

CATALOG NUMBER: P3AS13R15B2750DE010 E3PHLD1MW_3000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	55.1	11.1
10°-20°	106.8	21.4
20°-30°	103.8	20.8
30°-40°	83.9	16.8
40°-50°	62.3	12.5
50°-60°	43.5	8.7
60°-70°	27.3	5.5
70°-80°	12.9	2.6
80°-90°	2.4	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	265.7	53.4
0°-40°	349.6	70.2
0°-60°	455.4	91.4
0°-90°	498.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	498.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	661	
5°	617	55
15°	381	107
25°	225	104
35°	133	84
45°	80	62
55°	48	44
65°	27	27
75°	12	13
85°	2	2
90°	0	



TEST NUMBER: P1284418

CATALOG NUMBER: P3AS13R15B2750DE010 E3PHLD1MW_3000K

CANDELA DISTRIBUTION (FULL):

0°	
0°	660.9
2.5°	650.0
5°	617.2
7.5°	564.8
10°	500.3
12.5°	437.0
15°	381.2
17.5°	334.3
20°	292.8
22.5°	256.7
25°	225.0
27.5°	196.6
30°	172.6
32.5°	151.8
35°	133.3
37.5°	116.9
40°	102.7
42.5°	90.7
45°	79.7
47.5°	71.0
50°	62.3
52.5°	54.6
55°	48.1
57.5°	42.6
60°	37.1
62.5°	31.7
65°	27.3
67.5°	22.9
70°	19.7
72.5°	15.3
75°	12.0
77.5°	8.7
80°	6.6
82.5°	3.3
85°	2.2
87.5°	0.0
90°	0.0

(END OF REPORT)