

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1284648

Luminaire Tested: P3AS13R25B2750DE010 E3DLD1H_3000K

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1284648
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-10)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R25B2750DE010 E3DLD1H_3000K
Description: 3in Adjustable Boosted Cyan Tunable White LED luminaire with, R25 optic, 3000K CCT AND, 90CRI , E3DLD1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 607.0 lumens
Efficiency: N/A
Efficacy: 31.8 lumens/watt
Spacing Criteria (0/90/45): 0.78 / 0.78 / 0.85
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 19.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1284648

CATALOG NUMBER: P3AS13R25B2750DE010 E3DLD1H_3000K

Luminous Intensity Polar Plot



CATALOG NUMBER: P3AS13R25B2750DE010 E3DLD1H_3000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20					
RC	80					70					50					30					10					0
RW	70	50	30	10		70	50	30	10		50	30	10		50	30	10		50	30	10		0			
RCR																										
0	119	119	119	119		116	116	116	116		111	111	111		106	106	106		102	102	102		100			
1	112	109	106	104		110	107	105	102		103	101	99		99	98	96		96	94	93		91			
2	106	100	96	92		104	99	94	91		95	92	89		92	89	87		89	87	85		83			
3	100	92	87	82		98	91	86	82		88	84	80		86	82	79		83	80	78		76			
4	94	85	79	74		92	84	78	74		82	77	73		80	76	72		78	74	71		70			
5	89	79	73	68		87	78	72	68		76	71	67		75	70	66		73	69	66		64			
6	84	74	67	62		82	73	67	62		71	66	62		70	65	61		69	64	61		59			
7	79	69	62	58		78	68	62	58		67	61	57		66	61	57		65	60	57		55			
8	75	65	58	54		74	64	58	53		63	57	53		62	57	53		61	56	53		51			
9	71	61	54	50		70	60	54	50		59	54	50		58	53	50		57	53	49		48			
10	68	57	51	47		67	57	51	47		56	50	47		55	50	46		54	50	46		45			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	144265
5°	140810
10°	130503
15°	116210
20°	99875
25°	84900
30°	69884
35°	54449
40°	39188
45°	24871
50°	14703
55°	10131
60°	9298
65°	8613
70°	7758
75°	7032
80°	6693
85°	5787

MAXIMUM LUMINANCE 45°-90°:

Luminance: 24871 cd/sqm

TEST NUMBER: P1284648

CATALOG NUMBER: P3AS13R25B2750DE010 E3DLD1H_3000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	59.3	9.8
10°-20°	142.1	23.4
20°-30°	160.6	26.5
30°-40°	127.0	20.9
40°-50°	64.2	10.6
50°-60°	25.7	4.2
60°-70°	16.5	2.7
70°-80°	9.1	1.5
80°-90°	2.6	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	362.0	59.6
0°-40°	489.1	80.6
0°-60°	578.9	95.4
0°-90°	607.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	607.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	658	
5°	640	59
15°	512	142
25°	351	161
35°	203	127
45°	80	64
55°	26	26
65°	17	16
75°	8	9
85°	2	3
90°	0	

TEST NUMBER: P1284648

CATALOG NUMBER: P3AS13R25B2750DE010 E3DLD1H_3000K

CANDELA DISTRIBUTION (FULL):

0°	
0°	657.9
1°	657.9
2°	655.6
3°	651.8
4°	646.5
5°	639.7
6°	631.4
7°	621.6
8°	611.0
9°	598.9
10°	586.1
11°	571.7
12°	558.1
13°	542.2
14°	527.1
15°	511.9
17.5°	469.6
20°	428.0
22.5°	388.7
25°	350.9
27.5°	313.8
30°	276.0
32.5°	240.5
35°	203.4
37.5°	169.4
40°	136.9
42.5°	106.6
45°	80.2
47.5°	59.7
50°	43.1
52.5°	32.5
55°	26.5
57.5°	24.2
60°	21.2
62.5°	18.9
65°	16.6
67.5°	14.4
70°	12.1
72.5°	10.6
75°	8.3
77.5°	6.8
80°	5.3
82.5°	3.8
85°	2.3
87.5°	0.8



TEST NUMBER: P1284648

CATALOG NUMBER: P3AS13R25B2750DE010 E3DLD1H_3000K

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0

(END OF REPORT)