

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1284912

Luminaire Tested: P3AS13R35B2750DE010 E3DL1GPH_2700K

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1284912
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-19)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R35B2750DE010 E3DL1GPH_2700K
Description: 3in Adjustable Boosted Cyan Tunable White LED luminaire with, R35 optic, 2700K CCT AND, 90CRI , E3DL1GPH TRIM
Light Source: -
Ballast/Driver: -


Summary

Lumens per Lamp: N/A
Luminaire Lumens: 395.0 lumens
Efficiency: N/A
Efficacy: 20.7 lumens/watt
Spacing Criteria (0/90/45): 0.58 / 0.58 / 0.58
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 19.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1284912
CATALOG NUMBER: P3AS13R35B2750DE010 E3DL1GPH_2700K

Luminous Intensity Polar Plot





TEST NUMBER: P1284912

CATALOG NUMBER: P3AS13R35B2750DE010 E3DL1GPH_2700K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

| | | | | | | | | | | | | | | | | | | | | | |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| RF | 20 | | | | 20 | | | | 20 | | | | 20 | | | | 20 | | | | 20 |
| RC | 80 | | | | 70 | | | | 50 | | | | 30 | | | | 10 | | | | 0 |
| RW | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 0 |
| RCR | | | | | | | | | | | | | | | | | | | | | |
| 0 | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 | 106 | 106 | 106 | 102 | 102 | 102 | 100 | 100 | 100 | 100 |
| 1 | 114 | 112 | 109 | 107 | 112 | 109 | 107 | 106 | 105 | 104 | 102 | 102 | 100 | 99 | 98 | 97 | 96 | 95 | 95 | 95 | 95 |
| 2 | 109 | 105 | 101 | 98 | 107 | 103 | 100 | 97 | 100 | 97 | 95 | 97 | 95 | 93 | 94 | 93 | 91 | 90 | 90 | 90 | 90 |
| 3 | 105 | 99 | 95 | 91 | 103 | 98 | 94 | 90 | 95 | 92 | 89 | 93 | 90 | 88 | 91 | 88 | 86 | 85 | 85 | 85 | 85 |
| 4 | 100 | 94 | 89 | 85 | 99 | 93 | 88 | 85 | 91 | 87 | 84 | 89 | 85 | 83 | 87 | 84 | 82 | 80 | 80 | 80 | 80 |
| 5 | 96 | 89 | 84 | 80 | 95 | 88 | 83 | 80 | 86 | 82 | 79 | 85 | 81 | 78 | 83 | 80 | 78 | 76 | 76 | 76 | 76 |
| 6 | 92 | 85 | 80 | 76 | 91 | 84 | 79 | 76 | 83 | 78 | 75 | 81 | 77 | 75 | 80 | 77 | 74 | 73 | 73 | 73 | 73 |
| 7 | 89 | 81 | 76 | 72 | 88 | 80 | 75 | 72 | 79 | 75 | 71 | 78 | 74 | 71 | 77 | 73 | 71 | 70 | 70 | 70 | 70 |
| 8 | 85 | 77 | 72 | 69 | 84 | 77 | 72 | 68 | 76 | 71 | 68 | 75 | 71 | 68 | 74 | 70 | 68 | 66 | 66 | 66 | 66 |
| 9 | 82 | 74 | 69 | 66 | 81 | 74 | 69 | 65 | 73 | 68 | 65 | 72 | 68 | 65 | 71 | 67 | 65 | 64 | 64 | 64 | 64 |
| 10 | 79 | 71 | 66 | 63 | 78 | 71 | 66 | 63 | 70 | 66 | 63 | 69 | 65 | 62 | 69 | 65 | 62 | 61 | 61 | 61 | 61 |

AVERAGE LUMINANCE (cd/sqm):

| | |
|-----|--------|
| | 0° |
| 0° | 199216 |
| 5° | 191459 |
| 10° | 166819 |
| 15° | 127765 |
| 20° | 85477 |
| 25° | 51729 |
| 30° | 29675 |
| 35° | 16597 |
| 40° | 8817 |
| 45° | 4559 |
| 50° | 2183 |
| 55° | 1720 |
| 60° | 1667 |
| 65° | 1349 |
| 70° | 1475 |
| 75° | 1271 |
| 80° | 1389 |
| 85° | 1006 |

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 4559 cd/sqm



TEST NUMBER: P1284912
 CATALOG NUMBER: P3AS13R35B2750DE010 E3DL1GPH_2700K

ZONAL LUMENS:

| Zone | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10° | 79.1 | 20.0 |
| 10°-20° | 153.4 | 38.8 |
| 20°-30° | 100.4 | 25.4 |
| 30°-40° | 40.7 | 10.3 |
| 40°-50° | 12.2 | 3.1 |
| 50°-60° | 4.2 | 1.1 |
| 60°-70° | 2.8 | 0.7 |
| 70°-80° | 1.6 | 0.4 |
| 80°-90° | 0.6 | 0.1 |
| 90°-100° | 0.0 | 0.0 |
| 100°-110° | 0.0 | 0.0 |
| 110°-120° | 0.0 | 0.0 |
| 120°-130° | 0.0 | 0.0 |
| 130°-140° | 0.0 | 0.0 |
| 140°-150° | 0.0 | 0.0 |
| 150°-160° | 0.0 | 0.0 |
| 160°-170° | 0.0 | 0.0 |
| 170°-180° | 0.0 | 0.0 |
| 0°-30° | 332.9 | 84.3 |
| 0°-40° | 373.6 | 94.6 |
| 0°-60° | 390.0 | 98.7 |
| 0°-90° | 395.0 | 100.0 |
| 90°-120° | 0.0 | 0.0 |
| 90°-150° | 0.0 | 0.0 |
| 90°-180° | 0.0 | 0.0 |
| 0°-180° | 395.0 | 100.0 |

CANDELA DISTRIBUTION:

| | 0° | Flux |
|-----|-----|------|
| 0° | 908 | |
| 5° | 870 | 79 |
| 15° | 563 | 153 |
| 25° | 214 | 100 |
| 35° | 62 | 41 |
| 45° | 15 | 12 |
| 55° | 4 | 4 |
| 65° | 3 | 3 |
| 75° | 2 | 2 |
| 85° | 0 | 1 |
| 90° | 0 | |



TEST NUMBER: P1284912
CATALOG NUMBER: P3AS13R35B2750DE010 E3DL1GPH_2700K

CANDELA DISTRIBUTION (FULL):

| 0° | |
|-------|-------|
| 0° | 908.5 |
| 1° | 907.0 |
| 2° | 902.9 |
| 3° | 894.6 |
| 4° | 884.8 |
| 5° | 869.8 |
| 6° | 851.0 |
| 7° | 830.0 |
| 8° | 806.3 |
| 9° | 779.3 |
| 10° | 749.2 |
| 11° | 715.8 |
| 12° | 680.8 |
| 13° | 641.8 |
| 14° | 604.6 |
| 15° | 562.8 |
| 17.5° | 461.8 |
| 20° | 366.3 |
| 22.5° | 281.8 |
| 25° | 213.8 |
| 27.5° | 159.3 |
| 30° | 117.2 |
| 32.5° | 86.0 |
| 35° | 62.0 |
| 37.5° | 44.0 |
| 40° | 30.8 |
| 42.5° | 21.4 |
| 45° | 14.7 |
| 47.5° | 9.8 |
| 50° | 6.4 |
| 52.5° | 4.9 |
| 55° | 4.5 |
| 57.5° | 4.1 |
| 60° | 3.8 |
| 62.5° | 3.4 |
| 65° | 2.6 |
| 67.5° | 2.3 |
| 70° | 2.3 |
| 72.5° | 1.9 |
| 75° | 1.5 |
| 77.5° | 1.1 |
| 80° | 1.1 |
| 82.5° | 0.8 |
| 85° | 0.4 |
| 87.5° | 0.4 |



TEST NUMBER: P1284912
CATALOG NUMBER: P3AS13R35B2750DE010 E3DL1GPH_2700K

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0

(END OF REPORT)