

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1284953

Luminaire Tested: P3AS13R35B2750DE010 E3DLD1LI_3000K

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1284953
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-18)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R35B2750DE010 E3DLD1LI_3000K
Description: 3in Adjustable Boosted Cyan Tunable White LED luminaire with, R35 optic, 3000K CCT AND, 90CRI , E3DLD1LI TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 612.0 lumens
Efficiency: N/A
Efficacy: 32.0 lumens/watt
Spacing Criteria (0/90/45): 0.8 / 0.8 / 0.87
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 19.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1284953

CATALOG NUMBER: P3AS13R35B2750DE010 E3DLD1LI_3000K

Luminous Intensity Polar Plot



TEST NUMBER: P1284953

CATALOG NUMBER: P3AS13R35B2750DE010 E3DLD1LI_3000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	104	110	107	104	102	103	101	99		99	98	96		96
2	106	100	96	92	104	98	94	91	95	92	89		92	89	87		89
3	100	92	87	82	98	91	86	81	88	84	80		86	82	79		83
4	94	85	79	74	92	84	78	74	82	77	73		80	75	72		78
5	89	79	73	68	87	78	72	67	76	71	67		75	70	66		73
6	84	74	67	62	82	73	67	62	71	66	61		70	65	61		68
7	79	69	62	57	78	68	62	57	67	61	57		65	60	57		64
8	75	64	58	53	74	64	57	53	63	57	53		62	56	53		61
9	71	60	54	50	70	60	54	50	59	53	49		58	53	49		57
10	67	57	51	46	66	56	50	46	56	50	46		55	50	46		54

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	139791
5°	136848
10°	128143
15°	115029
20°	100062
25°	85263
30°	71429
35°	56885
40°	41134
45°	26018
50°	14191
55°	9825
60°	9298
65°	8613
70°	8271
75°	7032
80°	6693
85°	5787

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 26018 cd/sqm

TEST NUMBER: P1284953

CATALOG NUMBER: P3AS13R35B2750DE010 E3DLD1LI_3000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	57.9	9.5
10°-20°	141.0	23.0
20°-30°	161.6	26.4
30°-40°	131.9	21.5
40°-50°	66.5	10.9
50°-60°	24.7	4.0
60°-70°	16.6	2.7
70°-80°	9.2	1.5
80°-90°	2.8	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	360.4	58.9
0°-40°	492.3	80.4
0°-60°	583.5	95.3
0°-90°	612.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	612.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	638	
5°	622	58
15°	507	141
25°	352	162
35°	212	132
45°	84	66
55°	26	25
65°	17	17
75°	8	9
85°	2	3
90°	0	

TEST NUMBER: P1284953

CATALOG NUMBER: P3AS13R35B2750DE010 E3DLD1LI_3000K

CANDELA DISTRIBUTION (FULL):

0°	
0°	637.5
1°	636.8
2°	635.3
3°	632.2
4°	627.7
5°	621.7
6°	614.1
7°	606.5
8°	596.7
9°	586.9
10°	575.5
11°	563.4
12°	550.6
13°	536.2
14°	521.1
15°	506.7
17.5°	468.1
20°	428.8
22.5°	388.7
25°	352.4
27.5°	316.9
30°	282.1
32.5°	247.3
35°	212.5
37.5°	177.7
40°	143.7
42.5°	111.9
45°	83.9
47.5°	60.5
50°	41.6
52.5°	30.3
55°	25.7
57.5°	23.4
60°	21.2
62.5°	18.9
65°	16.6
67.5°	14.4
70°	12.9
72.5°	10.6
75°	8.3
77.5°	6.8
80°	5.3
82.5°	3.8
85°	2.3
87.5°	1.5



TEST NUMBER: P1284953

CATALOG NUMBER: P3AS13R35B2750DE010 E3DLD1LI_3000K

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0

(END OF REPORT)