

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1285322

Luminaire Tested: P3AS13R50B2750DE010 E3D1LI_2700K

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1285322
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-13)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R50B2750DE010 E3D1LI_2700K
Description: 3in Adjustable Boosted Cyan Tunable White LED luminaire with, R50 optic, 2700K CCT AND, 90CRI , E3D1LI TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1066.0 lumens
Efficiency: N/A
Efficacy: 55.8 lumens/watt
Spacing Criteria (0/90/45): 0.82 / 0.82 / 0.77
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 19.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1285322

CATALOG NUMBER: P3AS13R50B2750DE010 E3D1LI_2700K

Luminous Intensity Polar Plot



TEST NUMBER: P1285322

CATALOG NUMBER: P3AS13R50B2750DE010 E3D1LI_2700K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	112	109	107	112	110	108	106	105	104	102		102	101	99		98
2	109	105	101	98	107	103	100	97	100	97	95		97	95	93		94
3	105	99	95	91	103	98	94	90	95	92	89		93	90	88		91
4	100	94	89	85	99	92	88	85	90	87	84		88	85	83		87
5	96	89	84	80	94	88	83	79	86	82	79		84	81	78		83
6	92	84	79	75	91	83	78	75	82	78	74		81	77	74		79
7	88	80	75	71	87	79	74	71	78	74	70		77	73	70		76
8	84	76	71	67	83	76	71	67	75	70	67		74	69	66		73
9	81	73	67	64	80	72	67	64	71	67	63		70	66	63		70
10	78	69	64	61	77	69	64	61	68	64	60		67	63	60		67

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	372514
5°	362601
10°	346019
15°	313259
20°	271017
25°	222303
30°	127716
35°	39672
40°	10649
45°	3721
50°	887
55°	306
60°	175
65°	208
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 3721 cd/sqm

TEST NUMBER: P1285322

CATALOG NUMBER: P3AS13R50B2750DE010 E3D1LI_2700K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	154.3	14.5
10°-20°	382.3	35.9
20°-30°	401.9	37.7
30°-40°	115.0	10.8
40°-50°	11.2	1.1
50°-60°	0.9	0.1
60°-70°	0.3	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	938.5	88.0
0°-40°	1053.5	98.8
0°-60°	1065.7	100.0
0°-90°	1066.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1066.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1699	
5°	1647	154
15°	1380	382
25°	919	402
35°	148	115
45°	12	11
55°	1	1
65°	0	0
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1285322

CATALOG NUMBER: P3AS13R50B2750DE010 E3D1LI_2700K

CANDELA DISTRIBUTION (FULL):

0°	
0°	1698.8
1°	1696.2
2°	1688.7
3°	1677.8
4°	1663.1
5°	1647.3
6°	1630.4
7°	1612.3
8°	1595.4
9°	1575.9
10°	1554.0
11°	1528.9
12°	1499.9
13°	1463.8
14°	1424.7
15°	1379.9
16°	1332.5
17°	1286.6
18°	1239.6
19°	1198.3
20°	1161.4
21°	1126.0
22°	1085.8
23°	1039.5
24°	985.4
25°	918.8
26°	846.6
27°	766.1
28°	686.0
29°	599.5
30°	504.4
31°	415.2
32°	333.2
32.5°	297.5
33°	261.4
34°	200.5
35°	148.2
36°	108.7
37°	80.9
37.5°	70.0
38°	60.6
39°	47.0
40°	37.2
42.5°	21.1
45°	12.0



TEST NUMBER: P1285322

CATALOG NUMBER: P3AS13R50B2750DE010 E3D1LI_2700K

CANDELA DISTRIBUTION (continued):

	0°
47.5°	6.8
50°	2.6
52.5°	1.1
55°	0.8
57.5°	0.8
60°	0.4
62.5°	0.4
65°	0.4
67.5°	0.4
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)