

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1285351

Luminaire Tested: P3AS13R50B2750DE010 E3DL1H_5000K

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1285351
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-31)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R50B2750DE010 E3DL1H_5000K
Description: 3in Adjustable Boosted Cyan Tunable White LED luminaire with, R50 optic, 5000K CCT AND, 80CRI , E3DL1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 924.0 lumens
Efficiency: N/A
Efficacy: 48.4 lumens/watt
Spacing Criteria (0/90/45): 0.77 / 0.77 / 0.75
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 19.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1285351

CATALOG NUMBER: P3AS13R50B2750DE010 E3DL1H_5000K

Luminous Intensity Polar Plot



TEST NUMBER: P1285351

CATALOG NUMBER: P3AS13R50B2750DE010 E3DL1H_5000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	108	106	111	109	106	104	105	103	101		101	99	98		97
2	108	103	99	96	106	102	98	95	98	95	93		95	93	91		93
3	103	97	92	88	101	95	91	87	93	89	86		90	87	84		88
4	98	91	85	81	96	90	85	81	87	83	80		85	82	79		84
5	93	85	80	75	92	84	79	75	83	78	74		81	77	74		79
6	89	80	75	71	88	80	74	70	78	73	70		77	73	69		75
7	85	76	70	66	84	75	70	66	74	69	66		73	69	65		72
8	81	72	66	62	80	71	66	62	70	65	62		69	65	62		68
9	78	68	63	59	76	68	62	59	67	62	59		66	62	58		65
10	74	65	59	56	73	65	59	56	64	59	55		63	58	55		62

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	294187
5°	288267
10°	270002
15°	241704
20°	203414
25°	155235
30°	100902
35°	59829
40°	34579
45°	17335
50°	6448
55°	5008
60°	4693
65°	4255
70°	4231
75°	4151
80°	4167
85°	4026

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 17335 cd/sqm

TEST NUMBER: P1285351

CATALOG NUMBER: P3AS13R50B2750DE010 E3DL1H_5000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	121.8	13.2
10°-20°	294.4	31.9
20°-30°	288.9	31.3
30°-40°	145.5	15.8
40°-50°	46.0	5.0
50°-60°	11.9	1.3
60°-70°	8.4	0.9
70°-80°	5.2	0.6
80°-90°	1.8	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	705.2	76.3
0°-40°	850.7	92.1
0°-60°	908.6	98.3
0°-90°	924.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	924.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1342	
5°	1310	122
15°	1065	294
25°	642	289
35°	224	146
45°	56	46
55°	13	12
65°	8	8
75°	5	5
85°	2	2
90°	0	

TEST NUMBER: P1285351

CATALOG NUMBER: P3AS13R50B2750DE010 E3DL1H_5000K

CANDELA DISTRIBUTION (FULL):

0°	
0°	1341.6
2.5°	1333.4
5°	1309.6
7.5°	1266.8
10°	1212.6
12.5°	1142.8
15°	1064.7
17.5°	974.4
20°	871.7
22.5°	760.8
25°	641.6
27.5°	515.1
30°	398.5
32.5°	299.9
35°	223.5
37.5°	165.1
40°	120.8
42.5°	85.4
45°	55.9
47.5°	32.0
50°	18.9
52.5°	14.0
55°	13.1
57.5°	11.5
60°	10.7
62.5°	9.9
65°	8.2
67.5°	7.4
70°	6.6
72.5°	5.8
75°	4.9
77.5°	4.1
80°	3.3
82.5°	2.5
85°	1.6
87.5°	0.8
90°	0.0

(END OF REPORT)