

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1285362

Luminaire Tested: P3AS13R50B2750DE010 E3DL1WH_2700K

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1285362
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-29)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R50B2750DE010 E3DL1WH_2700K
Description: 3in Adjustable Boosted Cyan Tunable White LED luminaire with, R50 optic, 2700K CCT AND, 90CRI , E3DL1WH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 567.0 lumens
Efficiency: N/A
Efficacy: 29.7 lumens/watt
Spacing Criteria (0/90/45): 0.75 / 0.75 / 0.77
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 19.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1285362

CATALOG NUMBER: P3AS13R50B2750DE010 E3DL1WH_2700K

Luminous Intensity Polar Plot



TEST NUMBER: P1285362

CATALOG NUMBER: P3AS13R50B2750DE010 E3DL1WH_2700K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	107	105	111	108	106	103	104	102	100		100	99	97		97
2	107	102	98	94	105	100	96	93	97	94	91		94	91	89		91
3	101	95	89	85	99	93	88	85	91	87	83		88	85	82		86
4	96	88	82	78	94	87	82	78	85	80	77		83	79	76		81
5	91	83	76	72	90	82	76	72	80	75	71		78	74	70		77
6	87	77	71	67	85	77	71	67	75	70	66		74	69	66		72
7	82	73	67	62	81	72	66	62	71	66	62		70	65	61		68
8	78	69	63	58	77	68	62	58	67	62	58		66	61	58		65
9	75	65	59	55	74	64	59	55	63	58	55		63	58	54		62
10	71	61	56	52	70	61	55	52	60	55	51		59	55	51		59

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	164921
5°	160466
10°	147982
15°	130126
20°	108883
25°	86328
30°	63352
35°	43554
40°	27680
45°	15474
50°	8392
55°	7034
60°	6052
65°	5552
70°	4937
75°	4575
80°	3915
85°	3774

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 15474 cd/sqm

TEST NUMBER: P1285362

CATALOG NUMBER: P3AS13R50B2750DE010 E3DL1WH_2700K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	67.5	11.9
10°-20°	158.8	28.0
20°-30°	162.4	28.6
30°-40°	103.0	18.2
40°-50°	41.0	7.2
50°-60°	16.6	2.9
60°-70°	10.6	1.9
70°-80°	5.5	1.0
80°-90°	1.7	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	388.7	68.6
0°-40°	491.7	86.7
0°-60°	549.3	96.9
0°-90°	567.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	567.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	752	
5°	729	68
15°	573	159
25°	357	162
35°	163	103
45°	50	41
55°	18	17
65°	11	11
75°	5	5
85°	2	2
90°	0	

TEST NUMBER: P1285362

CATALOG NUMBER: P3AS13R50B2750DE010 E3DL1WH_2700K

CANDELA DISTRIBUTION (FULL):

0°	
0°	752.1
2.5°	746.7
5°	729.0
7.5°	701.4
10°	664.6
12.5°	620.8
15°	573.2
17.5°	521.1
20°	466.6
22.5°	412.1
25°	356.8
27.5°	301.6
30°	250.2
32.5°	204.1
35°	162.7
37.5°	127.4
40°	96.7
42.5°	71.4
45°	49.9
47.5°	33.8
50°	24.6
52.5°	20.7
55°	18.4
57.5°	16.1
60°	13.8
62.5°	12.3
65°	10.7
67.5°	9.2
70°	7.7
72.5°	6.1
75°	5.4
77.5°	3.8
80°	3.1
82.5°	2.3
85°	1.5
87.5°	0.8
90°	0.0

(END OF REPORT)