

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1285470

Luminaire Tested: P3AS13R55B2750DE010 E3D1LI_4000K

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1285470
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-14)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R55B2750DE010 E3D1LI_4000K
Description: 3in Adjustable Boosted Cyan Tunable White LED luminaire with, R55 optic, 4000K CCT AND, 80CRI , E3D1LI TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 993.0 lumens
Efficiency: N/A
Efficacy: 52.0 lumens/watt
Spacing Criteria (0/90/45): 0.93 / 0.93 / 0.82
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 19.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1285470

CATALOG NUMBER: P3AS13R55B2750DE010 E3D1LI_4000K

Luminous Intensity Polar Plot





TEST NUMBER: P1285470

CATALOG NUMBER: P3AS13R55B2750DE010 E3D1LI_4000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20				
RC	80					70					50					30					10				
RW	70	50	30	10		70	50	30	10		50	30	10		50	30	10		50	30	10		0		
RCR																									
0	119	119	119	119		116	116	116	116		111	111	111		106	106	106		102	102	102		100		
1	114	111	109	107		112	109	107	105		105	104	102		102	100	99		98	97	96		95		
2	109	105	101	98		107	103	100	97		100	97	95		97	95	93		94	92	91		89		
3	104	98	94	90		102	97	93	90		95	91	88		92	89	87		90	88	86		84		
4	100	93	88	84		98	92	87	84		90	86	83		88	84	82		86	83	81		79		
5	95	88	82	79		94	87	82	78		85	81	78		84	80	77		82	79	76		75		
6	91	83	78	74		90	82	77	74		81	76	73		80	76	73		78	75	72		71		
7	87	79	73	70		86	78	73	69		77	72	69		76	72	69		75	71	68		67		
8	83	75	69	66		82	74	69	65		73	69	65		72	68	65		71	68	65		63		
9	80	71	66	62		79	71	66	62		70	65	62		69	65	62		68	64	61		60		
10	77	68	62	59		76	67	62	59		67	62	59		66	62	59		65	61	58		57		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	287959
5°	277767
10°	287703
15°	283634
20°	262523
25°	212311
30°	127235
35°	43125
40°	11879
45°	5272
50°	1535
55°	306
60°	175
65°	208
70°	256
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 5272 cd/sqm

TEST NUMBER: P1285470

CATALOG NUMBER: P3AS13R55B2750DE010 E3D1LI_4000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	122.1	12.3
10°-20°	347.9	35.0
20°-30°	386.7	38.9
30°-40°	120.4	12.1
40°-50°	14.5	1.5
50°-60°	1.1	0.1
60°-70°	0.4	0.0
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	856.6	86.3
0°-40°	977.0	98.4
0°-60°	992.6	100.0
0°-90°	993.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	993.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1313	
5°	1262	122
15°	1249	348
25°	878	387
35°	161	120
45°	17	14
55°	1	1
65°	0	0
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1285470

CATALOG NUMBER: P3AS13R55B2750DE010 E3D1LI_4000K

CANDELA DISTRIBUTION (FULL):

0°	
0°	1313.2
1°	1308.3
2°	1295.5
3°	1279.6
4°	1265.3
5°	1261.9
6°	1265.7
7°	1273.6
8°	1282.6
9°	1289.8
10°	1292.1
11°	1290.6
12°	1284.5
13°	1275.1
14°	1264.2
15°	1249.4
16°	1232.5
17°	1211.0
18°	1186.8
19°	1157.8
20°	1125.0
21°	1087.6
22°	1043.5
23°	994.8
24°	939.0
25°	877.5
26°	809.9
27°	738.3
28°	661.7
29°	582.8
30°	502.5
31°	421.8
32°	342.9
32.5°	307.8
33°	271.6
34°	210.1
35°	161.1
36°	122.6
37°	90.9
37.5°	77.7
38°	67.5
39°	51.3
40°	41.5
42.5°	26.4
45°	17.0



TEST NUMBER: P1285470

CATALOG NUMBER: P3AS13R55B2750DE010 E3D1LI_4000K

CANDELA DISTRIBUTION (continued):

	0°
47.5°	10.2
50°	4.5
52.5°	1.5
55°	0.8
57.5°	0.4
60°	0.4
62.5°	0.4
65°	0.4
67.5°	0.4
70°	0.4
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)