

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1285668

Luminaire Tested: P3AS13R60B2750DE010 E3DLD1H_3000K

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1285668
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-38)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R60B2750DE010 E3DLD1H_3000K
Description: 3in Adjustable Boosted Cyan Tunable White LED luminaire with, R60 optic, 3000K CCT AND, 90CRI , E3DLD1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 623.0 lumens
Efficiency: N/A
Efficacy: 32.6 lumens/watt
Spacing Criteria (0/90/45): 0.94 / 0.94 / 1
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 19.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1285668

CATALOG NUMBER: P3AS13R60B2750DE010 E3DLD1H_3000K

Luminous Intensity Polar Plot





TEST NUMBER: P1285668

CATALOG NUMBER: P3AS13R60B2750DE010 E3DLD1H_3000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10			
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	112	109	106	103	110	107	104	101	102	100	98	99	97	95	95	94	93	91		
2	105	99	94	90	103	97	93	89	94	90	87	91	88	85	88	86	84	82		
3	99	91	85	80	96	89	84	79	87	82	78	84	80	77	82	78	76	74		
4	92	83	77	72	90	82	76	71	80	75	70	78	73	70	76	72	69	67		
5	87	77	70	65	85	76	69	65	74	68	64	72	67	63	71	66	63	61		
6	82	71	64	59	80	70	64	59	69	63	58	67	62	58	66	61	58	56		
7	77	66	59	54	75	65	59	54	64	58	54	63	57	53	61	57	53	51		
8	72	61	55	50	71	61	54	50	60	54	49	59	53	49	58	53	49	47		
9	68	57	51	46	67	57	50	46	56	50	46	55	49	46	54	49	45	44		
10	65	54	47	43	64	53	47	43	52	47	43	52	46	42	51	46	42	41		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	110583
5°	109355
10°	105565
15°	99728
20°	91918
25°	83231
30°	73910
35°	63149
40°	50208
45°	35415
50°	21151
55°	10705
60°	10262
65°	9391
70°	8719
75°	8303
80°	7577
85°	5787

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 35415 cd/sqm

TEST NUMBER: P1285668

CATALOG NUMBER: P3AS13R60B2750DE010 E3DLD1H_3000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	46.7	7.5
10°-20°	122.8	19.7
20°-30°	157.6	25.3
30°-40°	146.2	23.5
40°-50°	89.0	14.3
50°-60°	29.7	4.8
60°-70°	18.0	2.9
70°-80°	10.2	1.6
80°-90°	2.9	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	327.1	52.5
0°-40°	473.2	76.0
0°-60°	591.9	95.0
0°-90°	623.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	623.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	504	
5°	497	47
15°	439	123
25°	344	158
35°	236	146
45°	114	89
55°	28	30
65°	18	18
75°	10	10
85°	2	3
90°	0	



TEST NUMBER: P1285668

CATALOG NUMBER: P3AS13R60B2750DE010 E3DLD1H_3000K

CANDELA DISTRIBUTION (FULL):

0°	
0°	504.3
2.5°	502.1
5°	496.8
7.5°	486.9
10°	474.1
12.5°	458.2
15°	439.3
17.5°	417.4
20°	393.9
22.5°	369.0
25°	344.0
27.5°	318.3
30°	291.9
32.5°	265.4
35°	235.9
37.5°	204.9
40°	175.4
42.5°	144.4
45°	114.2
47.5°	88.5
50°	62.0
52.5°	37.1
55°	28.0
57.5°	25.7
60°	23.4
62.5°	20.4
65°	18.1
67.5°	15.9
70°	13.6
72.5°	11.3
75°	9.8
77.5°	7.6
80°	6.0
82.5°	3.8
85°	2.3
87.5°	1.5
90°	0.0

(END OF REPORT)