

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1285670

Luminaire Tested: P3AS13R60B2750DE010 E3DLD1H_4000K

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1285670
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-38)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R60B2750DE010 E3DLD1H_4000K
Description: 3in Adjustable Boosted Cyan Tunable White LED luminaire with, R60 optic, 4000K CCT AND, 80CRI , E3DLD1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 634.0 lumens
Efficiency: N/A
Efficacy: 33.2 lumens/watt
Spacing Criteria (0/90/45): 0.94 / 0.94 / 1
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 19.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1285670

CATALOG NUMBER: P3AS13R60B2750DE010 E3DLD1H_4000K

Luminous Intensity Polar Plot



TEST NUMBER: P1285670

CATALOG NUMBER: P3AS13R60B2750DE010 E3DLD1H_4000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10			0
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	112	109	106	103	110	107	104	101	102	100	98		99	97	95		95	94	93	91
2	105	99	94	90	103	97	93	89	94	90	87		91	88	85		88	86	84	82
3	99	91	85	80	96	89	84	79	87	82	78		84	80	77		82	78	76	74
4	92	83	77	72	90	82	76	71	80	75	70		78	73	70		76	72	69	67
5	87	77	70	65	85	76	69	65	74	68	64		72	67	63		71	66	63	61
6	82	71	64	59	80	70	64	59	69	63	58		67	62	58		66	61	58	56
7	77	66	59	54	75	65	59	54	64	58	54		63	57	53		61	57	53	51
8	72	61	55	50	71	61	54	50	60	54	49		59	53	49		58	53	49	47
9	68	57	51	46	67	57	50	46	56	50	46		55	49	46		54	49	45	44
10	65	54	47	43	64	53	47	43	52	47	43		52	46	42		51	46	42	41

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	112535
5°	111270
10°	107435
15°	101499
20°	93551
25°	84707
30°	75201
35°	64273
40°	51096
45°	36035
50°	21526
55°	10896
60°	10482
65°	9599
70°	8912
75°	8472
80°	7829
85°	5787

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 36035 cd/sqm

TEST NUMBER: P1285670

CATALOG NUMBER: P3AS13R60B2750DE010 E3DLD1H_4000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	47.5	7.5
10°-20°	125.0	19.7
20°-30°	160.4	25.3
30°-40°	148.7	23.5
40°-50°	90.6	14.3
50°-60°	30.2	4.8
60°-70°	18.4	2.9
70°-80°	10.4	1.6
80°-90°	2.9	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	332.9	52.5
0°-40°	481.6	76.0
0°-60°	602.4	95.0
0°-90°	634.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	634.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	513	
5°	506	48
15°	447	125
25°	350	160
35°	240	149
45°	116	91
55°	28	30
65°	18	18
75°	10	10
85°	2	3
90°	0	

TEST NUMBER: P1285670

CATALOG NUMBER: P3AS13R60B2750DE010 E3DLD1H_4000K

CANDELA DISTRIBUTION (FULL):

	0°
0°	513.2
2.5°	510.9
5°	505.5
7.5°	495.5
10°	482.5
12.5°	466.3
15°	447.1
17.5°	424.8
20°	400.9
22.5°	375.5
25°	350.1
27.5°	324.0
30°	297.0
32.5°	270.1
35°	240.1
37.5°	208.5
40°	178.5
42.5°	147.0
45°	116.2
47.5°	90.0
50°	63.1
52.5°	37.7
55°	28.5
57.5°	26.2
60°	23.9
62.5°	20.8
65°	18.5
67.5°	16.2
70°	13.9
72.5°	11.5
75°	10.0
77.5°	7.7
80°	6.2
82.5°	3.8
85°	2.3
87.5°	1.5
90°	0.0

(END OF REPORT)