

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1285755

Luminaire Tested: P3AS13R65B2750DE010 E3D1H_4000K

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1285755
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-16)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R65B2750DE010 E3D1H_4000K
Description: 3in Adjustable Boosted Cyan Tunable White LED luminaire with, R65 optic, 4000K CCT AND, 80CRI , E3D1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 918.1 lumens
Efficiency: N/A
Efficacy: 48.1 lumens/watt
Spacing Criteria (0/90/45): 0.92 / 0.92 / 0.88
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 19.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1285755

CATALOG NUMBER: P3AS13R65B2750DE010 E3D1H_4000K

Luminous Intensity Polar Plot



TEST NUMBER: P1285755

CATALOG NUMBER: P3AS13R65B2750DE010 E3D1H_4000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	109	106	111	109	107	105	105	103	102		101	100	99		98
2	108	104	100	96	106	102	98	95	99	96	93		96	93	91		93
3	103	97	92	88	101	95	91	87	93	89	86		90	87	85		88
4	98	91	85	81	96	90	85	81	87	83	80		85	82	79		84
5	93	85	79	75	92	84	79	75	82	78	74		81	77	74		79
6	89	80	74	70	87	79	74	70	78	73	69		76	72	69		75
7	84	75	70	65	83	75	69	65	73	69	65		72	68	65		71
8	80	71	65	61	79	71	65	61	69	64	61		68	64	61		67
9	77	67	61	58	76	67	61	57	66	61	57		65	60	57		64
10	73	64	58	54	72	63	58	54	62	57	54		62	57	54		61

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	245989
5°	228395
10°	220882
15°	212850
20°	196787
25°	179309
30°	138528
35°	80308
40°	31860
45°	13583
50°	3207
55°	421
60°	351
65°	208
70°	256
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 13583 cd/sqm

TEST NUMBER: P1285755

CATALOG NUMBER: P3AS13R65B2750DE010 E3D1H_4000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	97.9	10.7
10°-20°	261.3	28.5
20°-30°	330.7	36.0
30°-40°	188.3	20.5
40°-50°	37.4	4.1
50°-60°	1.9	0.2
60°-70°	0.5	0.1
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	689.8	75.1
0°-40°	878.1	95.6
0°-60°	917.5	99.9
0°-90°	918.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	918.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1122	
5°	1038	98
15°	938	261
25°	741	331
35°	300	188
45°	44	37
55°	1	2
65°	0	1
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1285755

CATALOG NUMBER: P3AS13R65B2750DE010 E3D1H_4000K

CANDELA DISTRIBUTION (FULL):

0°	
0°	1121.8
1°	1113.5
2°	1095.4
3°	1074.2
4°	1053.5
5°	1037.6
6°	1025.9
7°	1016.5
8°	1008.2
9°	999.9
10°	992.0
11°	983.3
12°	974.2
13°	963.3
14°	951.6
15°	937.6
16°	921.0
17°	902.9
18°	883.3
19°	862.6
20°	843.3
21°	823.7
22°	806.0
23°	787.5
24°	766.0
25°	741.1
26°	711.3
27°	675.4
28°	635.0
29°	592.0
30°	547.1
31°	497.7
32°	448.6
32.5°	423.4
33°	398.8
34°	349.0
35°	300.0
36°	254.7
37°	209.8
37.5°	186.8
38°	168.3
39°	136.2
40°	111.3
42.5°	68.7
45°	43.8



TEST NUMBER: P1285755

CATALOG NUMBER: P3AS13R65B2750DE010 E3D1H_4000K

CANDELA DISTRIBUTION (continued):

	0°
47.5°	25.7
50°	9.4
52.5°	1.9
55°	1.1
57.5°	0.8
60°	0.8
62.5°	0.8
65°	0.4
67.5°	0.4
70°	0.4
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)