

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1285898

Luminaire Tested: P3AS13R70B2750DE010 E3D1H_3000K

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1285898
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-17)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R70B2750DE010 E3D1H_3000K
Description: 3in Adjustable Boosted Cyan Tunable White LED luminaire with, R70 optic, 3000K CCT AND, 90CRI , E3D1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 902.0 lumens
Efficiency: N/A
Efficacy: 47.2 lumens/watt
Spacing Criteria (0/90/45): 1.02 / 1.02 / 1.06
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 19.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1285898

CATALOG NUMBER: P3AS13R70B2750DE010 E3D1H_3000K

Luminous Intensity Polar Plot



TEST NUMBER: P1285898

CATALOG NUMBER: P3AS13R70B2750DE010 E3D1H_3000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	105	111	108	106	104	104	102	100		100	99	97		97
2	107	102	98	94	105	100	96	93	97	94	91		94	91	89		91
3	101	94	89	85	99	93	88	84	90	86	83		88	84	81		86
4	95	87	81	77	94	86	81	77	84	79	76		82	78	75		80
5	90	81	75	70	88	80	74	70	78	73	69		77	72	69		75
6	85	75	69	64	83	75	69	64	73	68	64		72	67	63		70
7	80	70	64	59	79	70	63	59	68	63	59		67	62	58		66
8	76	66	59	55	75	65	59	55	64	58	54		63	58	54		62
9	72	61	55	51	71	61	55	51	60	54	50		59	54	50		58
10	68	58	51	47	67	57	51	47	56	51	47		55	50	47		55

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	175381
5°	165375
10°	156822
15°	153985
20°	148436
25°	139919
30°	138933
35°	120997
40°	78261
45°	36996
50°	5185
55°	421
60°	307
65°	363
70°	256
75°	339
80°	505
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 36996 cd/sqm

TEST NUMBER: P1285898

CATALOG NUMBER: P3AS13R70B2750DE010 E3D1H_3000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	70.2	7.8
10°-20°	190.5	21.1
20°-30°	269.5	29.9
30°-40°	270.8	30.0
40°-50°	97.4	10.8
50°-60°	2.6	0.3
60°-70°	0.6	0.1
70°-80°	0.4	0.0
80°-90°	0.1	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	530.1	58.8
0°-40°	801.0	88.8
0°-60°	901.0	99.9
0°-90°	902.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	902.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	800	
5°	751	70
15°	678	190
25°	578	269
35°	452	271
45°	119	97
55°	1	3
65°	1	1
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1285898

CATALOG NUMBER: P3AS13R70B2750DE010 E3D1H_3000K

CANDELA DISTRIBUTION (FULL):

0°	
0°	799.8
1°	797.6
2°	790.6
3°	779.5
4°	765.4
5°	751.3
6°	738.0
7°	727.6
8°	718.3
9°	710.9
10°	704.3
11°	698.7
12°	693.5
13°	688.3
14°	683.5
15°	678.3
16°	672.0
17°	665.4
18°	657.2
19°	647.2
20°	636.1
21°	623.9
22°	611.6
23°	599.8
24°	588.3
25°	578.3
26°	571.3
27°	565.7
28°	561.3
29°	556.1
30°	548.7
31°	537.9
32°	522.7
32.5°	514.2
33°	502.7
34°	480.1
35°	452.0
36°	420.8
37°	385.7
37.5°	369.4
38°	347.1
39°	307.5
40°	273.4
42.5°	189.3
45°	119.3

TEST NUMBER: P1285898

CATALOG NUMBER: P3AS13R70B2750DE010 E3D1H_3000K

CANDELA DISTRIBUTION (continued):

	0°
47.5°	64.1
50°	15.2
52.5°	1.9
55°	1.1
57.5°	1.1
60°	0.7
62.5°	0.7
65°	0.7
67.5°	0.4
70°	0.4
72.5°	0.4
75°	0.4
77.5°	0.4
80°	0.4
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)