

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1286069

Luminaire Tested: P3AS02R259030D2WDE010 E3DLD1LI

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1286069
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-10)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS02R259030D2WDE010 E3DLD1LI
Description: 3in Adjustable Dim to Warm LED luminaire with, R25 optic, 3000K CCT AND, 90CRI ,
E3DLD1LI TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 261.0 lumens
Efficiency: N/A
Efficacy: 36.3 lumens/watt
Spacing Criteria (0/90/45): 0.78 / 0.78 / 0.85
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 7.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1286069

CATALOG NUMBER: P3AS02R259030D2WDE010 E3DLD1LI

Luminous Intensity Polar Plot



TEST NUMBER: P1286069

CATALOG NUMBER: P3AS02R259030D2WDE010 E3DLD1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	104	110	107	105	102	103	101	99		99	98	96		96
2	106	100	96	92	104	99	94	91	95	92	89		92	89	87		89
3	100	92	87	82	98	91	86	82	88	84	80		86	82	79		83
4	94	85	79	74	92	84	78	74	82	77	73		80	76	72		78
5	89	79	73	68	87	78	72	68	76	71	67		75	70	66		73
6	84	74	67	62	82	73	67	62	71	66	62		70	65	61		69
7	79	69	62	58	78	68	62	58	67	61	57		66	61	57		65
8	75	65	58	54	74	64	58	53	63	57	53		62	57	53		61
9	71	61	54	50	70	60	54	50	59	54	50		58	53	50		57
10	68	57	51	47	67	57	51	47	56	50	47		55	50	46		54

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	62035
5°	60555
10°	56111
15°	49966
20°	42937
25°	36510
30°	30055
35°	23423
40°	16860
45°	10699
50°	6311
55°	4358
60°	3991
65°	3736
70°	3334
75°	3050
80°	2904
85°	2516

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 10699 cd/sqm

TEST NUMBER: P1286069

CATALOG NUMBER: P3AS02R259030D2WDE010 E3DLD1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	25.5	9.8
10°-20°	61.1	23.4
20°-30°	69.0	26.5
30°-40°	54.6	20.9
40°-50°	27.6	10.6
50°-60°	11.1	4.2
60°-70°	7.1	2.7
70°-80°	3.9	1.5
80°-90°	1.1	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	155.7	59.6
0°-40°	210.3	80.6
0°-60°	248.9	95.4
0°-90°	261.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	261.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	283	
5°	275	26
15°	220	61
25°	151	69
35°	88	55
45°	34	28
55°	11	11
65°	7	7
75°	4	4
85°	1	1
90°	0	

TEST NUMBER: P1286069

CATALOG NUMBER: P3AS02R259030D2WDE010 E3DLD1LI

CANDELA DISTRIBUTION (FULL):

0°	
0°	282.9
1°	282.9
2°	281.9
3°	280.3
4°	278.0
5°	275.1
6°	271.5
7°	267.3
8°	262.7
9°	257.5
10°	252.0
11°	245.8
12°	240.0
13°	233.1
14°	226.6
15°	220.1
17.5°	201.9
20°	184.0
22.5°	167.1
25°	150.9
27.5°	134.9
30°	118.7
32.5°	103.4
35°	87.5
37.5°	72.8
40°	58.9
42.5°	45.8
45°	34.5
47.5°	25.7
50°	18.5
52.5°	14.0
55°	11.4
57.5°	10.4
60°	9.1
62.5°	8.1
65°	7.2
67.5°	6.2
70°	5.2
72.5°	4.6
75°	3.6
77.5°	2.9
80°	2.3
82.5°	1.6
85°	1.0
87.5°	0.3



TEST NUMBER: P1286069

CATALOG NUMBER: P3AS02R259030D2WDE010 E3DLD1LI

CANDELA DISTRIBUTION (continued):



(END OF REPORT)