

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1286496

Luminaire Tested: P3AS05R409030D2WDE010 E3D1WH

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1286496
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-12)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS05R409030D2WDE010 E3D1WH
Description: 3in Adjustable Dim to Warm LED luminaire with, R40 optic, 3000K CCT AND, 90CRI , E3D1WH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 699.0 lumens
Efficiency: N/A
Efficacy: 63.0 lumens/watt
Spacing Criteria (0/90/45): 0.7 / 0.7 / 0.6
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 11.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1286496

CATALOG NUMBER: P3AS05R409030D2WDE010 E3D1WH

Luminous Intensity Polar Plot



TEST NUMBER: P1286496

CATALOG NUMBER: P3AS05R409030D2WDE010 E3D1WH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10			0
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	115	112	110	109	112	110	109	107	106	105	104		103	102	101		99	98	98	96
2	111	107	104	101	109	105	102	100	102	100	98		99	97	96		96	95	94	92
3	107	102	98	95	105	100	97	94	98	95	93		96	93	91		93	91	90	88
4	103	97	93	90	101	96	92	89	94	91	88		92	89	87		90	88	86	85
5	99	93	89	85	98	92	88	85	91	87	84		89	86	84		88	85	83	82
6	96	89	85	81	95	89	84	81	87	83	81		86	83	80		85	82	80	79
7	93	86	81	78	92	85	81	78	84	80	78		83	80	77		82	79	77	76
8	90	83	78	75	89	82	78	75	81	77	75		80	77	74		79	76	74	73
9	87	80	75	72	86	79	75	72	78	75	72		78	74	72		77	74	71	70
10	84	77	72	70	83	77	72	69	76	72	69		75	72	69		75	71	69	68

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	356287
5°	353730
10°	344460
15°	307698
20°	204021
25°	76432
30°	20459
35°	8004
40°	2863
45°	1364
50°	409
55°	191
60°	88
65°	104
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 45°
Luminance: 1364 cd/sqm

TEST NUMBER: P1286496

CATALOG NUMBER: P3AS05R409030D2WDE010 E3D1WH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	151.6	21.7
10°-20°	359.1	51.4
20°-30°	162.9	23.3
30°-40°	21.1	3.0
40°-50°	3.6	0.5
50°-60°	0.4	0.1
60°-70°	0.1	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	673.7	96.4
0°-40°	694.8	99.4
0°-60°	698.8	100.0
0°-90°	699.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	699.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1625	
5°	1607	152
15°	1355	359
25°	316	163
35°	30	21
45°	4	4
55°	0	0
65°	0	0
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1286496

CATALOG NUMBER: P3AS05R409030D2WDE010 E3D1WH

CANDELA DISTRIBUTION (FULL):

0°	
0°	1624.8
1°	1623.9
2°	1621.4
3°	1617.7
4°	1613.1
5°	1607.0
6°	1599.9
7°	1591.1
8°	1580.3
9°	1565.6
10°	1547.0
11°	1525.2
12°	1496.1
13°	1460.2
14°	1413.2
15°	1355.4
16°	1281.8
17°	1197.8
18°	1097.0
19°	990.6
20°	874.3
21°	758.1
22°	643.6
23°	529.5
24°	417.5
25°	315.9
26°	233.9
27°	171.3
28°	128.7
29°	100.1
30°	80.8
31°	66.8
32°	55.8
32.5°	50.9
33°	46.0
34°	37.4
35°	29.9
36°	23.5
37°	18.6
37.5°	16.6
38°	14.7
39°	12.2
40°	10.0
42.5°	6.6
45°	4.4



TEST NUMBER: P1286496

CATALOG NUMBER: P3AS05R409030D2WDE010 E3D1WH

CANDELA DISTRIBUTION (continued):

	0°
47.5°	2.7
50°	1.2
52.5°	0.5
55°	0.5
57.5°	0.2
60°	0.2
62.5°	0.2
65°	0.2
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)