

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1286643

Luminaire Tested: P3AS05R659030D2WDE010 E3DL1WH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1286643
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-41)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS05R659030D2WDE010 E3DL1WH
Description: 3in Adjustable Dim to Warm LED luminaire with, R65 optic, 3000K CCT AND, 90CRI , E3DL1WH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 346.0 lumens
Efficiency: N/A
Efficacy: 31.2 lumens/watt
Spacing Criteria (0/90/45): 0.79 / 0.79 / 0.83
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 11.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1286643

CATALOG NUMBER: P3AS05R659030D2WDE010 E3DL1WH

Luminous Intensity Polar Plot



TEST NUMBER: P1286643

CATALOG NUMBER: P3AS05R659030D2WDE010 E3DL1WH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	107	105	110	108	105	103	104	102	100		100	98	97		96
2	107	101	97	93	104	100	96	92	96	93	90		93	91	88		90
3	101	94	88	84	99	92	87	83	90	85	82		87	84	81		85
4	95	87	81	76	93	86	80	76	84	79	75		82	78	74		80
5	90	81	75	70	88	80	74	70	78	73	69		77	72	69		75
6	85	76	69	65	84	75	69	65	73	68	64		72	67	64		71
7	81	71	65	60	79	70	64	60	69	63	60		68	63	59		67
8	77	67	60	56	75	66	60	56	65	59	56		64	59	55		63
9	73	63	57	52	72	62	56	52	61	56	52		60	55	52		59
10	69	59	53	49	68	59	53	49	58	53	49		57	52	49		56

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	87953
5°	85758
10°	79869
15°	71578
20°	61815
25°	51414
30°	40538
35°	30035
40°	20696
45°	12839
50°	6993
55°	4396
60°	3728
65°	3373
70°	2885
75°	2542
80°	2526
85°	2516

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 12839 cd/sqm

TEST NUMBER: P1286643

CATALOG NUMBER: P3AS05R659030D2WDE010 E3DL1WH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	36.2	10.5
10°-20°	87.6	25.3
20°-30°	96.9	28.0
30°-40°	70.4	20.3
40°-50°	33.0	9.5
50°-60°	11.1	3.2
60°-70°	6.4	1.9
70°-80°	3.4	1.0
80°-90°	1.1	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	220.7	63.8
0°-40°	291.1	84.1
0°-60°	335.2	96.9
0°-90°	346.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	346.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	401	
5°	390	36
15°	315	88
25°	212	97
35°	112	70
45°	41	33
55°	12	11
65°	6	6
75°	3	3
85°	1	1
90°	0	

TEST NUMBER: P1286643

CATALOG NUMBER: P3AS05R659030D2WDE010 E3DL1WH

CANDELA DISTRIBUTION (FULL):

0°	
0°	401.1
2.5°	398.6
5°	389.6
7.5°	376.1
10°	358.7
12.5°	338.2
15°	315.3
17.5°	290.3
20°	264.9
22.5°	238.4
25°	212.5
27.5°	186.1
30°	160.1
32.5°	135.2
35°	112.2
37.5°	91.3
40°	72.3
42.5°	55.4
45°	41.4
47.5°	29.9
50°	20.5
52.5°	14.0
55°	11.5
57.5°	10.0
60°	8.5
62.5°	7.5
65°	6.5
67.5°	5.5
70°	4.5
72.5°	4.0
75°	3.0
77.5°	2.5
80°	2.0
82.5°	1.5
85°	1.0
87.5°	0.5
90°	0.0

(END OF REPORT)