

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1286900

Luminaire Tested: P3AS09R509030D2WDE010 E3DL1MW

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1286900
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-31)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R509030D2WDE010 E3DL1MW
Description: 3in Adjustable Dim to Warm LED luminaire with, R50 optic, 3000K CCT AND, 90CRI , E3DL1M
TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 753.0 lumens
Efficiency: N/A
Efficacy: 51.2 lumens/watt
Spacing Criteria (0/90/45): 0.77 / 0.77 / 0.75
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 14.7
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1286900

CATALOG NUMBER: P3AS09R509030D2WDE010 E3DL1MW

Luminous Intensity Polar Plot



TEST NUMBER: P1286900

CATALOG NUMBER: P3AS09R509030D2WDE010 E3DL1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	108	106	111	109	106	104	105	103	101		101	99	98		97
2	108	103	99	96	106	102	98	95	98	95	93		95	93	91		93
3	103	97	92	88	101	95	91	87	93	89	86		90	87	84		88
4	98	91	85	81	96	90	85	81	87	83	80		85	82	79		84
5	93	85	80	75	92	84	79	75	83	78	74		81	77	74		79
6	89	80	75	71	88	80	74	70	78	73	70		77	73	69		75
7	85	76	70	66	84	75	70	66	74	69	66		73	69	65		72
8	81	72	66	62	80	71	66	62	70	65	62		69	65	62		68
9	78	68	63	59	76	68	62	59	67	62	59		66	62	58		65
10	74	65	59	56	73	65	59	56	64	59	55		63	58	55		62

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	239740
5°	234910
10°	220036
15°	196982
20°	165751
25°	126515
30°	82215
35°	48747
40°	28167
45°	14110
50°	5254
55°	4091
60°	3815
65°	3476
70°	3462
75°	3389
80°	3410
85°	3271

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 14110 cd/sqm

TEST NUMBER: P1286900

CATALOG NUMBER: P3AS09R509030D2WDE010 E3DL1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	99.3	13.2
10°-20°	240.0	31.9
20°-30°	235.4	31.3
30°-40°	118.6	15.8
40°-50°	37.5	5.0
50°-60°	9.7	1.3
60°-70°	6.9	0.9
70°-80°	4.2	0.6
80°-90°	1.5	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	574.6	76.3
0°-40°	693.3	92.1
0°-60°	740.4	98.3
0°-90°	753.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	753.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1093	
5°	1067	99
15°	868	240
25°	523	235
35°	182	119
45°	46	37
55°	11	10
65°	7	7
75°	4	4
85°	1	1
90°	0	

TEST NUMBER: P1286900

CATALOG NUMBER: P3AS09R509030D2WDE010 E3DL1MW

CANDELA DISTRIBUTION (FULL):

0°	
0°	1093.3
2.5°	1086.6
5°	1067.2
7.5°	1032.4
10°	988.2
12.5°	931.3
15°	867.7
17.5°	794.0
20°	710.3
22.5°	620.0
25°	522.9
27.5°	419.8
30°	324.7
32.5°	244.4
35°	182.1
37.5°	134.6
40°	98.4
42.5°	69.6
45°	45.5
47.5°	26.1
50°	15.4
52.5°	11.4
55°	10.7
57.5°	9.4
60°	8.7
62.5°	8.0
65°	6.7
67.5°	6.0
70°	5.4
72.5°	4.7
75°	4.0
77.5°	3.3
80°	2.7
82.5°	2.0
85°	1.3
87.5°	0.7
90°	0.0

(END OF REPORT)