

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1286904

Luminaire Tested: P3AS09R509030D2WDE010 E3DLD1H

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1286904
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-30)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R509030D2WDE010 E3DLD1H
Description: 3in Adjustable Dim to Warm LED luminaire with, R50 optic, 3000K CCT AND, 90CRI , E3DLD1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 586.0 lumens
Efficiency: N/A
Efficacy: 39.9 lumens/watt
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.93
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 14.7
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1286904

CATALOG NUMBER: P3AS09R509030D2WDE010 E3DLD1H

Luminous Intensity Polar Plot



TEST NUMBER: P1286904

CATALOG NUMBER: P3AS09R509030D2WDE010 E3DLD1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	103	110	107	104	102	103	101	99		99	97	96		95
2	106	100	95	91	103	98	94	90	95	91	88		92	89	86		89
3	99	92	86	81	97	90	85	81	88	83	79		85	81	78		83
4	93	85	78	73	91	83	77	73	81	76	72		79	75	71		77
5	88	78	72	67	86	77	71	66	75	70	66		74	69	65		72
6	83	73	66	61	81	72	65	61	70	65	60		69	64	60		67
7	78	68	61	56	77	67	61	56	66	60	56		64	59	55		63
8	74	63	57	52	73	63	56	52	61	56	52		60	55	51		59
9	70	59	53	48	69	59	52	48	58	52	48		57	52	48		56
10	66	56	49	45	65	55	49	45	54	49	45		54	48	45		53

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	119091
5°	117323
10°	112133
15°	103860
20°	93341
25°	82045
30°	69783
35°	56563
40°	42508
45°	27383
50°	12997
55°	10246
60°	9692
65°	9028
70°	8142
75°	7371
80°	6819
85°	6793

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 27383 cd/sqm

TEST NUMBER: P1286904

CATALOG NUMBER: P3AS09R509030D2WDE010 E3DLD1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	50.0	8.5
10°-20°	127.5	21.8
20°-30°	155.0	26.4
30°-40°	131.4	22.4
40°-50°	68.3	11.7
50°-60°	24.6	4.2
60°-70°	17.0	2.9
70°-80°	9.3	1.6
80°-90°	2.9	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	332.5	56.7
0°-40°	463.9	79.2
0°-60°	556.8	95.0
0°-90°	586.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	586.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	543	
5°	533	50
15°	458	128
25°	339	155
35°	211	131
45°	88	68
55°	27	25
65°	17	17
75°	9	9
85°	3	3
90°	0	

TEST NUMBER: P1286904

CATALOG NUMBER: P3AS09R509030D2WDE010 E3DLD1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	543.1
2.5°	541.1
5°	533.0
7.5°	521.0
10°	503.6
12.5°	481.5
15°	457.5
17.5°	430.0
20°	400.0
22.5°	369.2
25°	339.1
27.5°	307.7
30°	275.6
32.5°	243.4
35°	211.3
37.5°	179.9
40°	148.5
42.5°	118.4
45°	88.3
47.5°	58.9
50°	38.1
52.5°	29.4
55°	26.8
57.5°	24.1
60°	22.1
62.5°	19.4
65°	17.4
67.5°	14.7
70°	12.7
72.5°	10.7
75°	8.7
77.5°	6.7
80°	5.4
82.5°	4.0
85°	2.7
87.5°	1.3
90°	0.0

(END OF REPORT)