

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1287136

Luminaire Tested: P3AS13R309030D2WDE010 E3DLD1LI

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1287136
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-14)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRIS
Catalog Number: P3AS13R309030D2WDE010 E3DLD1LI
Description: 3in Adjustable Dim to Warm LED luminaire with, R30 optic, 3000K CCT AND, 90CRI ,
E3DLD1LI TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 876.9 lumens
Efficiency: N/A
Efficacy: 43.6 lumens/watt
Spacing Criteria (0/90/45): 0.78 / 0.78 / 0.85
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 20.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1287136

CATALOG NUMBER: P3AS13R309030D2WDE010 E3DLD1LI

Luminous Intensity Polar Plot



TEST NUMBER: P1287136

CATALOG NUMBER: P3AS13R309030D2WDE010 E3DLD1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	104	110	107	105	102	103	101	99		99	98	96		96
2	106	100	96	92	104	99	94	91	95	92	89		92	89	87		89
3	100	92	87	82	98	91	86	82	88	84	80		86	82	79		84
4	94	85	79	74	92	84	79	74	82	77	73		80	76	72		78
5	89	79	73	68	87	78	72	68	76	71	67		75	70	66		73
6	84	74	67	62	82	73	67	62	71	66	62		70	65	61		69
7	79	69	62	58	78	68	62	58	67	61	57		66	61	57		65
8	75	65	58	54	74	64	58	53	63	57	53		62	57	53		61
9	71	61	54	50	70	60	54	50	59	54	50		58	53	50		57
10	68	57	51	47	67	57	51	47	56	50	47		55	50	46		54

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	207198
5°	202531
10°	188351
15°	167583
20°	144143
25°	122112
30°	101357
35°	79505
40°	56992
45°	37368
50°	21287
55°	13992
60°	13201
65°	12297
70°	11028
75°	9997
80°	9471
85°	8051

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 37368 cd/sqm

TEST NUMBER: P1287136

CATALOG NUMBER: P3AS13R309030D2WDE010 E3DLD1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	85.4	9.7
10°-20°	205.2	23.4
20°-30°	231.3	26.4
30°-40°	184.7	21.1
40°-50°	94.9	10.8
50°-60°	35.7	4.1
60°-70°	23.4	2.7
70°-80°	12.6	1.4
80°-90°	3.7	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	521.9	59.5
0°-40°	706.6	80.6
0°-60°	837.3	95.5
0°-90°	876.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	876.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	945	
5°	920	85
15°	738	205
25°	505	231
35°	297	185
45°	120	95
55°	37	36
65°	24	23
75°	12	13
85°	3	4
90°	0	

TEST NUMBER: P1287136

CATALOG NUMBER: P3AS13R309030D2WDE010 E3DLD1LI

CANDELA DISTRIBUTION (FULL):

0°	
0°	944.9
1°	944.9
2°	941.6
3°	936.3
4°	928.7
5°	920.1
6°	909.4
7°	895.4
8°	880.3
9°	863.1
10°	845.9
11°	826.5
12°	806.0
13°	784.5
14°	761.9
15°	738.2
17.5°	678.0
20°	617.7
22.5°	559.6
25°	504.7
27.5°	450.9
30°	400.3
32.5°	348.7
35°	297.0
37.5°	246.4
40°	199.1
42.5°	157.1
45°	120.5
47.5°	89.3
50°	62.4
52.5°	44.1
55°	36.6
57.5°	33.4
60°	30.1
62.5°	26.9
65°	23.7
67.5°	20.4
70°	17.2
72.5°	14.0
75°	11.8
77.5°	9.7
80°	7.5
82.5°	5.4
85°	3.2
87.5°	1.1



TEST NUMBER: P1287136

CATALOG NUMBER: P3AS13R309030D2WDE010 E3DLD1LI

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0

(END OF REPORT)