

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1287201

Luminaire Tested: P3AS13R409030D2WDE010 E3DLP1H

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1287201
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-21)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R409030D2WDE010 E3DLP1H
Description: 3in Adjustable Dim to Warm LED luminaire with, R40 optic, 3000K CCT AND, 90CRI , E3DLP1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 791.0 lumens
Efficiency: N/A
Efficacy: 39.4 lumens/watt
Spacing Criteria (0/90/45): 0.73 / 0.73 / 0.74
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 20.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1287201

CATALOG NUMBER: P3AS13R409030D2WDE010 E3DLP1H

Luminous Intensity Polar Plot



TEST NUMBER: P1287201

CATALOG NUMBER: P3AS13R409030D2WDE010 E3DLP1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	105	111	108	106	104	104	102	100		100	99	97		97
2	107	102	98	95	105	101	97	93	97	94	91		94	92	89		92
3	102	95	90	86	100	94	89	85	91	87	84		89	85	83		86
4	97	89	83	79	95	88	83	79	86	81	78		84	80	77		82
5	92	83	77	73	90	82	77	73	81	76	72		79	75	71		77
6	87	78	72	68	86	78	72	68	76	71	67		75	70	67		73
7	83	74	68	64	82	73	68	63	72	67	63		71	66	63		70
8	79	70	64	60	78	69	64	60	68	63	59		67	63	59		66
9	76	66	60	56	75	66	60	56	65	60	56		64	59	56		63
10	72	63	57	53	71	62	57	53	62	57	53		61	56	53		60

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	246296
5°	241316
10°	224690
15°	195824
20°	157817
25°	118289
30°	83177
35°	54475
40°	32976
45°	19692
50°	11769
55°	9481
60°	8508
65°	7264
70°	6924
75°	5507
80°	5430
85°	5535

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 19692 cd/sqm

TEST NUMBER: P1287201

CATALOG NUMBER: P3AS13R409030D2WDE010 E3DLP1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	101.8	12.9
10°-20°	237.6	30.0
20°-30°	223.9	28.3
30°-40°	129.5	16.4
40°-50°	51.6	6.5
50°-60°	22.8	2.9
60°-70°	14.1	1.8
70°-80°	7.4	0.9
80°-90°	2.4	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	563.3	71.2
0°-40°	692.7	87.6
0°-60°	767.2	97.0
0°-90°	791.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	791.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1123	
5°	1096	102
15°	863	238
25°	489	224
35°	204	129
45°	64	52
55°	25	23
65°	14	14
75°	6	7
85°	2	2
90°	0	

TEST NUMBER: P1287201

CATALOG NUMBER: P3AS13R409030D2WDE010 E3DLP1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	1123.2
2.5°	1116.8
5°	1096.3
7.5°	1058.6
10°	1009.1
12.5°	942.3
15°	862.6
17.5°	773.2
20°	676.3
22.5°	579.4
25°	488.9
27.5°	404.9
30°	328.5
32.5°	261.7
35°	203.5
37.5°	154.0
40°	115.2
42.5°	86.2
45°	63.5
47.5°	46.3
50°	34.5
52.5°	28.0
55°	24.8
57.5°	22.6
60°	19.4
62.5°	16.2
65°	14.0
67.5°	11.8
70°	10.8
72.5°	8.6
75°	6.5
77.5°	5.4
80°	4.3
82.5°	3.2
85°	2.2
87.5°	1.1
90°	0.0

(END OF REPORT)