

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1287567

Luminaire Tested: P3AS17R459030D2WDE010 E3DLD1MW

Issue Date: 1/30/2026

**Test Information**

Test Method: LM-79-2019  
Report Number: P1287567  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-26)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: IRiS  
Catalog Number: P3AS17R459030D2WDE010 E3DLD1MW  
Description: 3in Adjustable Dim to Warm LED luminaire with, R45 optic, 3000K CCT AND, 90CRI ,  
E3DLD1MW TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 1250.0 lumens  
Efficiency: N/A  
Efficacy: 45.8 lumens/watt  
Spacing Criteria (0/90/45): 0.84 / 0.84 / 0.92  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct

Input Watts (W): 27.3  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1287567

CATALOG NUMBER: P3AS17R459030D2WDE010 E3DLD1MW

### Luminous Intensity Polar Plot



TEST NUMBER: P1287567

CATALOG NUMBER: P3AS17R459030D2WDE010 E3DLD1MW

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|-----|-----|-----|--|-----|
| RF  | 20  |     |     |     | 20  |     |     |     | 20  |     |     |  | 20  |     |     |  | 20  |
| RC  | 80  |     |     |     | 70  |     |     |     | 50  |     |     |  | 30  |     |     |  | 10  |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50  | 30  | 10  |  | 50  | 30  | 10  |  | 50  |
| RCR |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 |  | 106 | 106 | 106 |  | 102 |
| 1   | 112 | 109 | 106 | 104 | 110 | 107 | 104 | 102 | 103 | 101 | 99  |  | 99  | 97  | 96  |  | 96  |
| 2   | 106 | 100 | 95  | 91  | 103 | 98  | 94  | 90  | 95  | 91  | 88  |  | 92  | 89  | 86  |  | 89  |
| 3   | 99  | 92  | 86  | 82  | 97  | 90  | 85  | 81  | 88  | 83  | 80  |  | 85  | 81  | 78  |  | 83  |
| 4   | 94  | 85  | 78  | 74  | 92  | 84  | 78  | 73  | 81  | 76  | 72  |  | 79  | 75  | 71  |  | 77  |
| 5   | 88  | 79  | 72  | 67  | 86  | 78  | 71  | 67  | 76  | 70  | 66  |  | 74  | 69  | 65  |  | 72  |
| 6   | 83  | 73  | 66  | 61  | 81  | 72  | 66  | 61  | 71  | 65  | 61  |  | 69  | 64  | 60  |  | 68  |
| 7   | 78  | 68  | 61  | 57  | 77  | 67  | 61  | 56  | 66  | 60  | 56  |  | 65  | 60  | 56  |  | 64  |
| 8   | 74  | 64  | 57  | 52  | 73  | 63  | 57  | 52  | 62  | 56  | 52  |  | 61  | 56  | 52  |  | 60  |
| 9   | 70  | 60  | 53  | 49  | 69  | 59  | 53  | 49  | 58  | 52  | 48  |  | 57  | 52  | 48  |  | 56  |
| 10  | 67  | 56  | 50  | 45  | 66  | 56  | 49  | 45  | 55  | 49  | 45  |  | 54  | 49  | 45  |  | 53  |

**AVERAGE LUMINANCE (cd/sqm):**

|     |        |
|-----|--------|
|     | 0°     |
| 0°  | 265023 |
| 5°  | 260334 |
| 10° | 246333 |
| 15° | 224678 |
| 20° | 198677 |
| 25° | 172534 |
| 30° | 148099 |
| 35° | 123406 |
| 40° | 91944  |
| 45° | 56285  |
| 50° | 26029  |
| 55° | 20377  |
| 60° | 19604  |
| 65° | 17953  |
| 70° | 16605  |
| 75° | 15843  |
| 80° | 14522  |
| 85° | 10819  |

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 56285 cd/sqm

TEST NUMBER: P1287567

CATALOG NUMBER: P3AS17R459030D2WDE010 E3DLD1MW

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 110.5  | 8.8       |
| 10°-20°   | 275.5  | 22.0      |
| 20°-30°   | 327.4  | 26.2      |
| 30°-40°   | 284.5  | 22.8      |
| 40°-50°   | 142.7  | 11.4      |
| 50°-60°   | 49.5   | 4.0       |
| 60°-70°   | 34.7   | 2.8       |
| 70°-80°   | 19.4   | 1.5       |
| 80°-90°   | 5.9    | 0.5       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| <hr/>     |        |           |
| 0°-30°    | 713.4  | 57.1      |
| 0°-40°    | 997.9  | 79.8      |
| 0°-60°    | 1190.0 | 95.2      |
| 0°-90°    | 1250.0 | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 1250.0 | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°   | Flux |
|-----|------|------|
| 0°  | 1209 |      |
| 5°  | 1183 | 110  |
| 15° | 990  | 276  |
| 25° | 713  | 327  |
| 35° | 461  | 284  |
| 45° | 182  | 143  |
| 55° | 53   | 50   |
| 65° | 35   | 35   |
| 75° | 19   | 19   |
| 85° | 4    | 6    |
| 90° | 0    |      |

TEST NUMBER: P1287567

CATALOG NUMBER: P3AS17R459030D2WDE010 E3DLD1MW

**CANDELA DISTRIBUTION (FULL):**

| 0°    |        |
|-------|--------|
| 0°    | 1208.6 |
| 2.5°  | 1202.9 |
| 5°    | 1182.7 |
| 7.5°  | 1151.0 |
| 10°   | 1106.3 |
| 12.5° | 1051.6 |
| 15°   | 989.7  |
| 17.5° | 920.5  |
| 20°   | 851.4  |
| 22.5° | 780.8  |
| 25°   | 713.1  |
| 27.5° | 648.2  |
| 30°   | 584.9  |
| 32.5° | 524.4  |
| 35°   | 461.0  |
| 37.5° | 393.3  |
| 40°   | 321.2  |
| 42.5° | 250.7  |
| 45°   | 181.5  |
| 47.5° | 119.6  |
| 50°   | 76.3   |
| 52.5° | 59.1   |
| 55°   | 53.3   |
| 57.5° | 49.0   |
| 60°   | 44.7   |
| 62.5° | 40.3   |
| 65°   | 34.6   |
| 67.5° | 30.3   |
| 70°   | 25.9   |
| 72.5° | 21.6   |
| 75°   | 18.7   |
| 77.5° | 14.4   |
| 80°   | 11.5   |
| 82.5° | 8.6    |
| 85°   | 4.3    |
| 87.5° | 2.9    |
| 90°   | 0.0    |

(END OF REPORT)