

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1287655

Luminaire Tested: P3AS17R609030D2WDE010 E3DLD1WH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1287655
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-38)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS17R609030D2WDE010 E3DLD1WH
Description: 3in Adjustable Dim to Warm LED luminaire with, R60 optic, 3000K CCT AND, 90CRI ,
E3DLD1WH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1187.0 lumens
Efficiency: N/A
Efficacy: 43.5 lumens/watt
Spacing Criteria (0/90/45): 0.94 / 0.94 / 1
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 27.3
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1287655

CATALOG NUMBER: P3AS17R609030D2WDE010 E3DLD1WH

Luminous Intensity Polar Plot



TEST NUMBER: P1287655

CATALOG NUMBER: P3AS17R609030D2WDE010 E3DLD1WH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	103	110	107	104	101	102	100	98		99	97	95		95
2	105	99	94	90	103	97	93	89	94	90	87		91	88	85		88
3	99	91	85	80	96	89	84	79	87	82	78		84	80	77		82
4	92	83	77	72	90	82	76	71	80	75	70		78	73	70		76
5	87	77	70	65	85	76	69	65	74	68	64		72	67	63		71
6	82	71	64	59	80	70	64	59	69	63	58		67	62	58		66
7	77	66	59	54	75	65	59	54	64	58	54		63	57	53		61
8	72	61	55	50	71	61	54	50	60	54	49		59	53	49		58
9	68	57	51	46	67	57	50	46	56	50	46		55	49	46		54
10	65	54	47	43	64	53	47	43	52	47	43		52	46	42		51

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	210707
5°	208342
10°	201132
15°	190012
20°	175155
25°	158598
30°	140806
35°	120328
40°	95665
45°	67449
50°	40289
55°	20377
60°	19604
65°	17953
70°	16605
75°	15843
80°	14522
85°	10819

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 67449 cd/sqm

TEST NUMBER: P1287655

CATALOG NUMBER: P3AS17R609030D2WDE010 E3DLD1WH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	88.9	7.5
10°-20°	233.9	19.7
20°-30°	300.4	25.3
30°-40°	278.5	23.5
40°-50°	169.5	14.3
50°-60°	56.5	4.8
60°-70°	34.4	2.9
70°-80°	19.4	1.6
80°-90°	5.5	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	623.2	52.5
0°-40°	901.7	76.0
0°-60°	1127.8	95.0
0°-90°	1187.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1187.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	961	
5°	946	89
15°	837	234
25°	656	300
35°	450	278
45°	218	170
55°	53	57
65°	35	34
75°	19	19
85°	4	5
90°	0	

TEST NUMBER: P1287655

CATALOG NUMBER: P3AS17R609030D2WDE010 E3DLD1WH

CANDELA DISTRIBUTION (FULL):

0°	
0°	960.9
2.5°	956.6
5°	946.5
7.5°	927.8
10°	903.3
12.5°	873.0
15°	837.0
17.5°	795.2
20°	750.6
22.5°	703.0
25°	655.5
27.5°	606.5
30°	556.1
32.5°	505.7
35°	449.5
37.5°	390.4
40°	334.2
42.5°	275.2
45°	217.5
47.5°	168.6
50°	118.1
52.5°	70.6
55°	53.3
57.5°	49.0
60°	44.7
62.5°	38.9
65°	34.6
67.5°	30.3
70°	25.9
72.5°	21.6
75°	18.7
77.5°	14.4
80°	11.5
82.5°	7.2
85°	4.3
87.5°	2.9
90°	0.0

(END OF REPORT)