

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1287767

Luminaire Tested: P3AS05R15W2N902750DE010 E3D1WMH_2700K

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1287767
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-7)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS05R15W2N902750DE010 E3D1WMH_2700K
Description: 3in Adjustable Tunable White LED luminaire with, R15 optic, 2700K CCT AND, 90CRI ,
E3D1WMH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 464.0 lumens
Efficiency: N/A
Efficacy: 78.6 lumens/watt
Spacing Criteria (0/90/45): 0.3 / 0.3 / 0.29
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 5.9
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1287767

CATALOG NUMBER: P3AS05R15W2N902750DE010 E3D1WMH_2700K

Luminous Intensity Polar Plot



TEST NUMBER: P1287767

CATALOG NUMBER: P3AS05R15W2N902750DE010 E3D1WMH_2700K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10				0
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10		0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102		100
1	116	114	112	111	113	112	110	109	108	107	105		104	103	102		101	100	99		98
2	112	109	107	105	110	108	105	103	105	103	101		102	100	99		99	98	97		96
3	110	106	102	100	108	104	101	99	102	100	98		100	98	96		98	96	95		94
4	107	102	99	96	105	101	98	96	99	97	95		98	96	94		96	94	93		92
5	105	100	96	94	103	99	96	93	97	94	92		96	93	92		94	93	91		90
6	102	97	94	91	101	96	93	91	95	92	90		94	92	90		93	91	89		88
7	100	95	91	89	99	94	91	89	93	90	88		92	90	88		91	89	88		87
8	98	93	89	87	97	92	89	87	91	89	87		91	88	86		90	88	86		85
9	96	91	88	85	96	91	87	85	90	87	85		89	87	85		88	86	85		84
10	95	89	86	84	94	89	86	84	88	85	83		88	85	83		87	85	83		82

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	883570
5°	720491
10°	352855
15°	107992
20°	45737
25°	20687
30°	8052
35°	3721
40°	1145
45°	434
50°	171
55°	76
60°	88
65°	104
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 434 cd/sqm

TEST NUMBER: P1287767

CATALOG NUMBER: P3AS05R15W2N902750DE010 E3D1WMH_2700K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	254.8	54.9
10°-20°	156.3	33.7
20°-30°	42.0	9.1
30°-40°	9.2	2.0
40°-50°	1.3	0.3
50°-60°	0.3	0.1
60°-70°	0.1	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	453.1	97.6
0°-40°	462.4	99.6
0°-60°	463.9	100.0
0°-90°	464.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	464.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	4029	
5°	3273	255
15°	476	156
25°	86	42
35°	14	9
45°	1	1
55°	0	0
65°	0	0
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1287767

CATALOG NUMBER: P3AS05R15W2N902750DE010 E3D1WMH_2700K

CANDELA DISTRIBUTION (FULL):

0°	
0°	4029.4
1°	4004.3
2°	3923.5
3°	3778.0
4°	3559.0
5°	3273.2
6°	2950.0
7°	2590.0
8°	2259.3
9°	1908.6
10°	1584.7
11°	1264.1
12°	972.6
13°	748.1
14°	592.2
15°	475.7
17.5°	294.9
20°	196.0
22.5°	132.0
25°	85.5
27.5°	50.7
30°	31.8
32.5°	21.5
35°	13.9
37.5°	7.7
40°	4.0
42.5°	2.3
45°	1.4
47.5°	0.9
50°	0.5
52.5°	0.4
55°	0.2
57.5°	0.2
60°	0.2
62.5°	0.2
65°	0.2
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0



TEST NUMBER: P1287767

CATALOG NUMBER: P3AS05R15W2N902750DE010 E3D1WMH_2700K

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0

(END OF REPORT)