

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1288763

Luminaire Tested: P3AS05R30W2N902750DE010 E3DL1GPH_3000K

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1288763
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-15)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS05R30W2N902750DE010 E3DL1GPH_3000K
Description: 3in Adjustable Tunable White LED luminaire with, R30 optic, 3000K CCT AND, 90CRI ,
E3DL1GPH TRIM
Light Source: -
Ballast/Driver: -


Summary

Lumens per Lamp: N/A
Luminaire Lumens: 205.0 lumens
Efficiency: N/A
Efficacy: 34.7 lumens/watt
Spacing Criteria (0/90/45): 0.54 / 0.54 / 0.54
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 5.9
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1288763
CATALOG NUMBER: P3AS05R30W2N902750DE010 E3DL1GPH_3000K

Luminous Intensity Polar Plot





TEST NUMBER: P1288763

CATALOG NUMBER: P3AS05R30W2N902750DE010 E3DL1GPH_3000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

| | | | | | | | | | | | | | | | | | | | | | |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| RF | 20 | | | | 20 | | | | 20 | | | | 20 | | | | 20 | | | | |
| RC | 80 | | | | 70 | | | | 50 | | | | 30 | | | | 10 | | | 0 | |
| RW | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 0 |
| RCR | | | | | | | | | | | | | | | | | | | | | |
| 0 | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 | 106 | 106 | 106 | 102 | 102 | 102 | 100 | 100 | 100 | 100 |
| 1 | 114 | 112 | 110 | 108 | 112 | 110 | 108 | 106 | 106 | 104 | 103 | 102 | 101 | 100 | 99 | 98 | 97 | 95 | 95 | 95 | 95 |
| 2 | 110 | 105 | 102 | 99 | 107 | 104 | 101 | 98 | 101 | 98 | 96 | 98 | 96 | 94 | 95 | 93 | 92 | 90 | 90 | 90 | 90 |
| 3 | 105 | 100 | 96 | 92 | 103 | 98 | 95 | 91 | 96 | 93 | 90 | 94 | 91 | 89 | 91 | 89 | 87 | 86 | 86 | 86 | 86 |
| 4 | 101 | 95 | 90 | 86 | 99 | 94 | 89 | 86 | 92 | 88 | 85 | 90 | 87 | 84 | 88 | 85 | 83 | 82 | 82 | 82 | 82 |
| 5 | 97 | 90 | 85 | 82 | 96 | 89 | 85 | 81 | 88 | 84 | 81 | 86 | 83 | 80 | 85 | 82 | 79 | 78 | 78 | 78 | 78 |
| 6 | 94 | 86 | 81 | 78 | 92 | 85 | 81 | 77 | 84 | 80 | 77 | 83 | 79 | 76 | 81 | 78 | 76 | 75 | 75 | 75 | 75 |
| 7 | 90 | 82 | 77 | 74 | 89 | 82 | 77 | 74 | 81 | 76 | 73 | 80 | 76 | 73 | 78 | 75 | 73 | 71 | 71 | 71 | 71 |
| 8 | 87 | 79 | 74 | 71 | 86 | 79 | 74 | 71 | 78 | 73 | 70 | 77 | 73 | 70 | 76 | 72 | 70 | 69 | 69 | 69 | 69 |
| 9 | 84 | 76 | 71 | 68 | 83 | 75 | 71 | 68 | 75 | 70 | 67 | 74 | 70 | 67 | 73 | 70 | 67 | 66 | 66 | 66 | 66 |
| 10 | 81 | 73 | 68 | 65 | 80 | 73 | 68 | 65 | 72 | 68 | 65 | 71 | 67 | 65 | 71 | 67 | 65 | 63 | 63 | 63 | 63 |

AVERAGE LUMINANCE (cd/sqm):

| | |
|-----|--------|
| | 0° |
| 0° | 119618 |
| 5° | 113867 |
| 10° | 95768 |
| 15° | 69058 |
| 20° | 42844 |
| 25° | 24364 |
| 30° | 13521 |
| 35° | 7362 |
| 40° | 3893 |
| 45° | 2109 |
| 50° | 1126 |
| 55° | 726 |
| 60° | 658 |
| 65° | 726 |
| 70° | 641 |
| 75° | 508 |
| 80° | 505 |
| 85° | 503 |

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 2109 cd/sqm



TEST NUMBER: P1288763

CATALOG NUMBER: P3AS05R30W2N902750DE010 E3DL1GPH_3000K

ZONAL LUMENS:

| Zone | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10° | 46.6 | 22.7 |
| 10°-20° | 82.8 | 40.4 |
| 20°-30° | 47.8 | 23.3 |
| 30°-40° | 18.2 | 8.9 |
| 40°-50° | 5.6 | 2.7 |
| 50°-60° | 1.8 | 0.9 |
| 60°-70° | 1.3 | 0.6 |
| 70°-80° | 0.7 | 0.3 |
| 80°-90° | 0.2 | 0.1 |
| 90°-100° | 0.0 | 0.0 |
| 100°-110° | 0.0 | 0.0 |
| 110°-120° | 0.0 | 0.0 |
| 120°-130° | 0.0 | 0.0 |
| 130°-140° | 0.0 | 0.0 |
| 140°-150° | 0.0 | 0.0 |
| 150°-160° | 0.0 | 0.0 |
| 160°-170° | 0.0 | 0.0 |
| 170°-180° | 0.0 | 0.0 |
| 0°-30° | 177.2 | 86.4 |
| 0°-40° | 195.4 | 95.3 |
| 0°-60° | 202.8 | 98.9 |
| 0°-90° | 205.0 | 100.0 |
| 90°-120° | 0.0 | 0.0 |
| 90°-150° | 0.0 | 0.0 |
| 90°-180° | 0.0 | 0.0 |
| 0°-180° | 205.0 | 100.0 |

CANDELA DISTRIBUTION:

| | 0° | Flux |
|-----|-----|------|
| 0° | 546 | |
| 5° | 517 | 47 |
| 15° | 304 | 83 |
| 25° | 101 | 48 |
| 35° | 28 | 18 |
| 45° | 7 | 6 |
| 55° | 2 | 2 |
| 65° | 1 | 1 |
| 75° | 1 | 1 |
| 85° | 0 | 0 |
| 90° | 0 | |



TEST NUMBER: P1288763
CATALOG NUMBER: P3AS05R30W2N902750DE010 E3DL1GPH_3000K

CANDELA DISTRIBUTION (FULL):

| 0° | |
|-------|-------|
| 0° | 545.5 |
| 1° | 545.1 |
| 2° | 541.8 |
| 3° | 535.7 |
| 4° | 527.9 |
| 5° | 517.3 |
| 6° | 503.7 |
| 7° | 488.6 |
| 8° | 471.7 |
| 9° | 451.6 |
| 10° | 430.1 |
| 11° | 406.9 |
| 12° | 382.3 |
| 13° | 356.5 |
| 14° | 330.4 |
| 15° | 304.2 |
| 17.5° | 239.9 |
| 20° | 183.6 |
| 22.5° | 136.1 |
| 25° | 100.7 |
| 27.5° | 73.2 |
| 30° | 53.4 |
| 32.5° | 38.5 |
| 35° | 27.5 |
| 37.5° | 19.2 |
| 40° | 13.6 |
| 42.5° | 9.5 |
| 45° | 6.8 |
| 47.5° | 4.6 |
| 50° | 3.3 |
| 52.5° | 2.3 |
| 55° | 1.9 |
| 57.5° | 1.7 |
| 60° | 1.5 |
| 62.5° | 1.4 |
| 65° | 1.4 |
| 67.5° | 1.2 |
| 70° | 1.0 |
| 72.5° | 0.8 |
| 75° | 0.6 |
| 77.5° | 0.6 |
| 80° | 0.4 |
| 82.5° | 0.4 |
| 85° | 0.2 |
| 87.5° | 0.0 |



TEST NUMBER: P1288763
CATALOG NUMBER: P3AS05R30W2N902750DE010 E3DL1GPH_3000K

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0

(END OF REPORT)