

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1288822

Luminaire Tested: P3AS05R30W2N902750DE010 E3DLP1GPH_2700K

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1288822
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-13)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS05R30W2N902750DE010 E3DLP1GPH_2700K
Description: 3in Adjustable Tunable White LED luminaire with, R30 optic, 2700K CCT AND, 90CRI ,
E3DLP1GPH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 113.0 lumens
Efficiency: N/A
Efficacy: 19.2 lumens/watt
Spacing Criteria (0/90/45): 0.66 / 0.66 / 0.7
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 5.9
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1288822

CATALOG NUMBER: P3AS05R30W2N902750DE010 E3DLP1GPH_2700K

Luminous Intensity Polar Plot



TEST NUMBER: P1288822

CATALOG NUMBER: P3AS05R30W2N902750DE010 E3DLP1GPH_2700K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20
RC	80					70					50					30					10
RW	70	50	30	10		70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																					
0	119	119	119	119		116	116	116	116		111	111	111		106	106	106		102	102	102
1	113	110	108	105		111	108	106	104		104	102	100		100	99	97		97	96	95
2	107	102	98	95		105	101	97	94		97	94	92		94	92	90		92	90	88
3	102	95	90	86		100	94	89	85		91	87	84		89	86	83		87	84	81
4	97	89	83	79		95	88	83	79		86	81	78		84	80	77		82	79	76
5	92	84	78	73		90	83	77	73		81	76	72		79	75	72		78	74	71
6	88	79	73	68		86	78	72	68		76	71	68		75	71	67		74	70	67
7	83	74	68	64		82	74	68	64		72	67	63		71	66	63		70	66	63
8	80	70	64	60		78	70	64	60		68	63	60		67	63	60		67	62	59
9	76	67	61	57		75	66	60	57		65	60	56		64	60	56		63	59	56
10	73	63	58	54		72	63	57	54		62	57	53		61	57	53		60	56	53

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	38615
5°	37420
10°	33711
15°	27878
20°	21585
25°	16186
30°	11749
35°	7843
40°	4809
45°	2822
50°	1740
55°	1415
60°	1228
65°	986
70°	898
75°	932
80°	631
85°	1006

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 45°
Luminance: 2822 cd/sqm

TEST NUMBER: P1288822

CATALOG NUMBER: P3AS05R30W2N902750DE010 E3DLP1GPH_2700K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	15.6	13.8
10°-20°	33.8	29.9
20°-30°	30.8	27.2
30°-40°	18.6	16.5
40°-50°	7.5	6.6
50°-60°	3.3	2.9
60°-70°	2.0	1.8
70°-80°	1.1	1.0
80°-90°	0.3	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	80.2	71.0
0°-40°	98.8	87.4
0°-60°	109.6	97.0
0°-90°	113.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	113.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	176	
5°	170	16
15°	123	34
25°	67	31
35°	29	19
45°	9	7
55°	4	3
65°	2	2
75°	1	1
85°	0	0
90°	0	

TEST NUMBER: P1288822

CATALOG NUMBER: P3AS05R30W2N902750DE010 E3DLP1GPH_2700K

CANDELA DISTRIBUTION (FULL):

0°	
0°	176.1
1°	175.9
2°	175.2
3°	174.0
4°	172.2
5°	170.0
6°	167.2
7°	164.2
8°	160.3
9°	155.9
10°	151.4
11°	146.1
12°	140.5
13°	134.9
14°	128.8
15°	122.8
17.5°	107.2
20°	92.5
22.5°	78.8
25°	66.9
27.5°	56.1
30°	46.4
32.5°	37.5
35°	29.3
37.5°	22.4
40°	16.8
42.5°	12.3
45°	9.1
47.5°	6.8
50°	5.1
52.5°	4.0
55°	3.7
57.5°	3.2
60°	2.8
62.5°	2.3
65°	1.9
67.5°	1.8
70°	1.4
72.5°	1.2
75°	1.1
77.5°	0.9
80°	0.5
82.5°	0.4
85°	0.4
87.5°	0.2



TEST NUMBER: P1288822

CATALOG NUMBER: P3AS05R30W2N902750DE010 E3DLP1GPH_2700K

CANDELA DISTRIBUTION (continued):



(END OF REPORT)