

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1289743

Luminaire Tested: P3AS05R45W2N902750DE010 E3DL1WH_3500K

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1289743
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-25)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS05R45W2N902750DE010 E3DL1WH_3500K
Description: 3in Adjustable Tunable White LED luminaire with, R45 optic, 3500K CCT AND, 90CRI ,
E3DL1WH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 289.9 lumens
Efficiency: N/A
Efficacy: 49.1 lumens/watt
Spacing Criteria (0/90/45): 0.73 / 0.73 / 0.76
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 5.9
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1289743

CATALOG NUMBER: P3AS05R45W2N902750DE010 E3DL1WH_3500K

Luminous Intensity Polar Plot



TEST NUMBER: P1289743

CATALOG NUMBER: P3AS05R45W2N902750DE010 E3DL1WH_3500K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10				0
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10		0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102		100
1	113	110	107	105	111	108	106	103	104	102	100		100	99	97		97	96	94		93
2	107	102	98	94	105	100	96	93	97	94	91		94	91	89		91	89	87		86
3	102	95	90	85	100	93	89	85	91	87	83		88	85	82		86	83	81		79
4	96	88	83	78	94	87	82	78	85	81	77		83	79	76		81	78	75		74
5	91	83	77	72	90	82	76	72	80	75	71		78	74	71		77	73	70		69
6	87	78	72	67	85	77	71	67	75	70	66		74	69	66		73	69	66		64
7	83	73	67	63	81	72	67	63	71	66	62		70	65	62		69	65	62		60
8	79	69	63	59	77	68	63	59	67	62	58		66	62	58		65	61	58		56
9	75	65	59	55	74	65	59	55	64	59	55		63	58	55		62	58	55		53
10	72	62	56	52	71	61	56	52	61	55	52		60	55	52		59	55	52		50

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	86375
5°	84415
10°	77865
15°	67719
20°	55632
25°	43285
30°	31954
35°	22486
40°	14026
45°	7598
50°	4128
55°	3517
60°	3158
65°	2698
70°	2308
75°	2372
80°	2020
85°	2013

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 45°
Luminance: 7598 cd/sqm

TEST NUMBER: P1289743

CATALOG NUMBER: P3AS05R45W2N902750DE010 E3DL1WH_3500K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	35.5	12.2
10°-20°	82.5	28.4
20°-30°	81.9	28.2
30°-40°	52.7	18.2
40°-50°	20.3	7.0
50°-60°	8.2	2.8
60°-70°	5.2	1.8
70°-80°	2.8	1.0
80°-90°	0.9	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	199.8	68.9
0°-40°	252.5	87.1
0°-60°	281.1	96.9
0°-90°	289.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	289.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	394	
5°	384	36
15°	298	82
25°	179	82
35°	84	53
45°	24	20
55°	9	8
65°	5	5
75°	3	3
85°	1	1
90°	0	



TEST NUMBER: P1289743

CATALOG NUMBER: P3AS05R45W2N902750DE010 E3DL1WH_3500K

CANDELA DISTRIBUTION (FULL):

0°	
0°	393.9
2.5°	391.9
5°	383.5
7.5°	369.0
10°	349.7
12.5°	325.6
15°	298.3
17.5°	268.5
20°	238.4
22.5°	207.8
25°	178.9
27.5°	151.5
30°	126.2
32.5°	104.1
35°	84.0
37.5°	65.9
40°	49.0
42.5°	35.4
45°	24.5
47.5°	16.5
50°	12.1
52.5°	10.0
55°	9.2
57.5°	8.0
60°	7.2
62.5°	6.0
65°	5.2
67.5°	4.4
70°	3.6
72.5°	3.2
75°	2.8
77.5°	2.0
80°	1.6
82.5°	1.2
85°	0.8
87.5°	0.4
90°	0.0

(END OF REPORT)