

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1291944

Luminaire Tested: P3AS09R20W2N902750DE010 E3DLD1GPH_2700K

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1291944
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-6)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R20W2N902750DE010 E3DLD1GPH_2700K
Description: 3in Adjustable Tunable White LED luminaire with, R20 optic, 2700K CCT AND, 90CRI ,
E3DLD1GPH TRIM
Light Source: -
Ballast/Driver: -


Summary

Lumens per Lamp: N/A
Luminaire Lumens: 204.0 lumens
Efficiency: N/A
Efficacy: 22.7 lumens/watt
Spacing Criteria (0/90/45): 0.76 / 0.76 / 0.83
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 9
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1291944
CATALOG NUMBER: P3AS09R20W2N902750DE010 E3DLD1GPH_2700K

Luminous Intensity Polar Plot





TEST NUMBER: P1291944

CATALOG NUMBER: P3AS09R20W2N902750DE010 E3DLD1GPH_2700K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	20.6	10.1
10°-20°	48.8	23.9
20°-30°	54.1	26.5
30°-40°	41.3	20.2
40°-50°	21.1	10.4
50°-60°	8.7	4.2
60°-70°	5.4	2.6
70°-80°	3.0	1.5
80°-90°	0.9	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	123.5	60.6
0°-40°	164.8	80.8
0°-60°	194.6	95.4
0°-90°	204.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	204.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	230	
5°	223	21
15°	175	49
25°	118	54
35°	66	41
45°	27	21
55°	9	9
65°	5	5
75°	3	3
85°	1	1
90°	0	



TEST NUMBER: P1291944
CATALOG NUMBER: P3AS09R20W2N902750DE010 E3DLD1GPH_2700K

CANDELA DISTRIBUTION (FULL):

0°	
0°	230.1
1°	230.4
2°	229.3
3°	228.0
4°	226.0
5°	223.1
6°	219.7
7°	216.1
8°	212.2
9°	207.6
10°	202.9
12.5°	189.4
15°	175.2
17.5°	160.7
20°	146.2
22.5°	131.6
25°	118.4
27.5°	105.2
30°	91.5
32.5°	78.5
35°	65.8
37.5°	54.7
40°	43.8
42.5°	34.5
45°	26.7
47.5°	20.2
50°	15.0
52.5°	11.1
55°	8.8
57.5°	8.0
60°	7.0
62.5°	6.2
65°	5.4
67.5°	4.7
70°	4.1
72.5°	3.4
75°	2.9
77.5°	2.3
80°	1.8
82.5°	1.3
85°	0.8
87.5°	0.3
90°	0.0

(END OF REPORT)