

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1292859

Luminaire Tested: P3AS09R35W2N902750DE010 E3CB1MMS_2700K

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1292859
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-20)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R35W2N902750DE010 E3CB1MMS_2700K
Description: 3in Adjustable Tunable White LED luminaire with, R35 optic, 2700K CCT AND, 90CRI ,
E3CB1MMS TRIM
Light Source: -
Ballast/Driver: -


Summary

Lumens per Lamp: N/A
Luminaire Lumens: 671.0 lumens
Efficiency: N/A
Efficacy: 74.6 lumens/watt
Spacing Criteria (0/90/45): 0.58 / 0.58 / 0.52
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 9
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1292859
CATALOG NUMBER: P3AS09R35W2N902750DE010 E3CB1MMS_2700K

Luminous Intensity Polar Plot





TEST NUMBER: P1292859

CATALOG NUMBER: P3AS09R35W2N902750DE010 E3CB1MMS_2700K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

| | | | | | | | | | | | | | | | | | | | | | |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| RF | 20 | | | | 20 | | | | 20 | | | | 20 | | | | 20 | | | | |
| RC | 80 | | | | 70 | | | | 50 | | | | 30 | | | | 10 | | | 0 | |
| RW | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 0 |
| RCR | | | | | | | | | | | | | | | | | | | | | |
| 0 | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 | 106 | 106 | 106 | 102 | 102 | 102 | 102 | 102 | 102 | 100 |
| 1 | 115 | 113 | 111 | 109 | 112 | 110 | 109 | 107 | 106 | 105 | 104 | 103 | 102 | 101 | 99 | 99 | 98 | 98 | 98 | 98 | 96 |
| 2 | 111 | 107 | 104 | 101 | 109 | 105 | 103 | 100 | 102 | 100 | 98 | 99 | 98 | 96 | 97 | 95 | 94 | 94 | 94 | 94 | 93 |
| 3 | 107 | 102 | 98 | 95 | 105 | 101 | 97 | 95 | 98 | 96 | 93 | 96 | 94 | 92 | 94 | 92 | 90 | 94 | 92 | 90 | 89 |
| 4 | 104 | 98 | 94 | 91 | 102 | 97 | 93 | 90 | 95 | 92 | 89 | 93 | 90 | 88 | 91 | 89 | 87 | 91 | 89 | 87 | 86 |
| 5 | 100 | 94 | 90 | 87 | 99 | 93 | 89 | 86 | 92 | 88 | 86 | 90 | 87 | 85 | 89 | 86 | 84 | 89 | 86 | 84 | 83 |
| 6 | 97 | 91 | 86 | 83 | 96 | 90 | 86 | 83 | 89 | 85 | 82 | 87 | 84 | 82 | 86 | 83 | 81 | 86 | 83 | 81 | 80 |
| 7 | 94 | 87 | 83 | 80 | 93 | 87 | 83 | 80 | 86 | 82 | 79 | 85 | 81 | 79 | 84 | 81 | 79 | 84 | 81 | 79 | 77 |
| 8 | 91 | 84 | 80 | 77 | 90 | 84 | 80 | 77 | 83 | 79 | 77 | 82 | 79 | 76 | 81 | 78 | 76 | 81 | 78 | 76 | 75 |
| 9 | 89 | 82 | 77 | 74 | 88 | 81 | 77 | 74 | 80 | 77 | 74 | 80 | 76 | 74 | 79 | 76 | 74 | 79 | 76 | 74 | 73 |
| 10 | 86 | 79 | 75 | 72 | 85 | 79 | 75 | 72 | 78 | 74 | 72 | 77 | 74 | 72 | 77 | 74 | 71 | 77 | 74 | 71 | 70 |

AVERAGE LUMINANCE (cd/sqm):

| | |
|-----|--------|
| | 0° |
| 0° | 437531 |
| 5° | 428614 |
| 10° | 398746 |
| 15° | 292351 |
| 20° | 149696 |
| 25° | 53955 |
| 30° | 21016 |
| 35° | 7362 |
| 40° | 3034 |
| 45° | 806 |
| 50° | 716 |
| 55° | 803 |
| 60° | 702 |
| 65° | 571 |
| 70° | 705 |
| 75° | 932 |
| 80° | 631 |
| 85° | 0 |

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 75°
 Luminance: 932 cd/sqm



TEST NUMBER: P1292859

CATALOG NUMBER: P3AS09R35W2N902750DE010 E3CB1MMS_2700K

ZONAL LUMENS:

| Zone | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10° | 181.5 | 27.1 |
| 10°-20° | 340.6 | 50.8 |
| 20°-30° | 120.6 | 18.0 |
| 30°-40° | 21.1 | 3.1 |
| 40°-50° | 3.1 | 0.5 |
| 50°-60° | 1.7 | 0.3 |
| 60°-70° | 1.3 | 0.2 |
| 70°-80° | 0.9 | 0.1 |
| 80°-90° | 0.2 | 0.0 |
| 90°-100° | 0.0 | 0.0 |
| 100°-110° | 0.0 | 0.0 |
| 110°-120° | 0.0 | 0.0 |
| 120°-130° | 0.0 | 0.0 |
| 130°-140° | 0.0 | 0.0 |
| 140°-150° | 0.0 | 0.0 |
| 150°-160° | 0.0 | 0.0 |
| 160°-170° | 0.0 | 0.0 |
| 170°-180° | 0.0 | 0.0 |
| 0°-30° | 642.7 | 95.8 |
| 0°-40° | 663.8 | 98.9 |
| 0°-60° | 668.6 | 99.6 |
| 0°-90° | 671.0 | 100.0 |
| 90°-120° | 0.0 | 0.0 |
| 90°-150° | 0.0 | 0.0 |
| 90°-180° | 0.0 | 0.0 |
| 0°-180° | 671.0 | 100.0 |

CANDELA DISTRIBUTION:

| | 0° | Flux |
|-----|------|------|
| 0° | 1995 | |
| 5° | 1947 | 182 |
| 15° | 1288 | 341 |
| 25° | 223 | 121 |
| 35° | 28 | 21 |
| 45° | 3 | 3 |
| 55° | 2 | 2 |
| 65° | 1 | 1 |
| 75° | 1 | 1 |
| 85° | 0 | 0 |
| 90° | 0 | |



TEST NUMBER: P1292859
CATALOG NUMBER: P3AS09R35W2N902750DE010 E3CB1MMS_2700K

CANDELA DISTRIBUTION (FULL):

| 0° | |
|-------|--------|
| 0° | 1995.3 |
| 1° | 1994.8 |
| 2° | 1988.5 |
| 3° | 1976.3 |
| 4° | 1965.2 |
| 5° | 1947.2 |
| 6° | 1928.7 |
| 7° | 1908.1 |
| 8° | 1882.8 |
| 9° | 1843.1 |
| 10° | 1790.8 |
| 11° | 1718.4 |
| 12° | 1631.2 |
| 13° | 1527.7 |
| 14° | 1413.5 |
| 15° | 1287.8 |
| 17.5° | 959.1 |
| 20° | 641.5 |
| 22.5° | 386.8 |
| 25° | 223.0 |
| 27.5° | 133.2 |
| 30° | 83.0 |
| 32.5° | 48.1 |
| 35° | 27.5 |
| 37.5° | 17.4 |
| 40° | 10.6 |
| 42.5° | 5.3 |
| 45° | 2.6 |
| 47.5° | 2.1 |
| 50° | 2.1 |
| 52.5° | 2.1 |
| 55° | 2.1 |
| 57.5° | 1.6 |
| 60° | 1.6 |
| 62.5° | 1.6 |
| 65° | 1.1 |
| 67.5° | 1.1 |
| 70° | 1.1 |
| 72.5° | 1.1 |
| 75° | 1.1 |
| 77.5° | 0.5 |
| 80° | 0.5 |
| 82.5° | 0.5 |
| 85° | 0.0 |
| 87.5° | 0.0 |



TEST NUMBER: P1292859
CATALOG NUMBER: P3AS09R35W2N902750DE010 E3CB1MMS_2700K

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0

(END OF REPORT)