

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1293072

Luminaire Tested: P3AS09R35W2N902765DE010 E3DLD1GPH_2700K

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1293072
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-18)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS09R35W2N902765DE010 E3DLD1GPH_2700K
Description: 3in Adjustable Tunable White LED luminaire with, R35 optic, 2700K CCT AND, 90CRI ,
E3DLD1GPH TRIM
Light Source: -
Ballast/Driver: -


Summary

Lumens per Lamp: N/A
Luminaire Lumens: 210.0 lumens
Efficiency: N/A
Efficacy: 23.3 lumens/watt
Spacing Criteria (0/90/45): 0.8 / 0.8 / 0.87
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 9
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1293072
CATALOG NUMBER: P3AS09R35W2N902765DE010 E3DLD1GPH_2700K

Luminous Intensity Polar Plot





TEST NUMBER: P1293072

CATALOG NUMBER: P3AS09R35W2N902765DE010 E3DLD1GPH_2700K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	19.9	9.5
10°-20°	48.4	23.0
20°-30°	55.4	26.4
30°-40°	45.3	21.6
40°-50°	22.8	10.9
50°-60°	8.5	4.0
60°-70°	5.7	2.7
70°-80°	3.1	1.5
80°-90°	1.0	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	123.7	58.9
0°-40°	168.9	80.4
0°-60°	200.2	95.3
0°-90°	210.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	210.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	219	
5°	213	20
15°	174	48
25°	121	55
35°	73	45
45°	29	23
55°	9	8
65°	6	6
75°	3	3
85°	1	1
90°	0	



TEST NUMBER: P1293072
CATALOG NUMBER: P3AS09R35W2N902765DE010 E3DLD1GPH_2700K

CANDELA DISTRIBUTION (FULL):

0°	
0°	218.8
1°	218.5
2°	218.0
3°	216.9
4°	215.4
5°	213.3
6°	210.7
7°	208.1
8°	204.7
9°	201.4
10°	197.5
11°	193.3
12°	188.9
13°	184.0
14°	178.8
15°	173.9
17.5°	160.6
20°	147.1
22.5°	133.4
25°	120.9
27.5°	108.7
30°	96.8
32.5°	84.9
35°	72.9
37.5°	61.0
40°	49.3
42.5°	38.4
45°	28.8
47.5°	20.8
50°	14.3
52.5°	10.4
55°	8.8
57.5°	8.0
60°	7.3
62.5°	6.5
65°	5.7
67.5°	4.9
70°	4.4
72.5°	3.6
75°	2.9
77.5°	2.3
80°	1.8
82.5°	1.3
85°	0.8
87.5°	0.5



TEST NUMBER: P1293072
CATALOG NUMBER: P3AS09R35W2N902765DE010 E3DLD1GPH_2700K

CANDELA DISTRIBUTION (continued):



(END OF REPORT)