

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1293985

Luminaire Tested: P3AS09R50W2N902765DE010 E3DL1MW\_2700K

Issue Date: 1/30/2026

**Test Information**


Test Method: LM-79-2019  
Report Number: P1293985  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-31)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: IRiS  
Catalog Number: P3AS09R50W2N902765DE010 E3DL1MW\_2700K  
Description: 3in Adjustable Tunable White LED luminaire with, R50 optic, 2700K CCT AND, 90CRI ,  
E3DL1MW TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 595.0 lumens  
Efficiency: N/A  
Efficacy: 66.1 lumens/watt  
Spacing Criteria (0/90/45): 0.77 / 0.77 / 0.75  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct  
  
Input Watts (W): 9  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1293985  
CATALOG NUMBER: P3AS09R50W2N902765DE010 E3DL1MW\_2700K

### Luminous Intensity Polar Plot







TEST NUMBER: P1293985

CATALOG NUMBER: P3AS09R50W2N902765DE010 E3DL1MW\_2700K

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	78.5	13.2
10°-20°	189.6	31.9
20°-30°	186.0	31.3
30°-40°	93.7	15.7
40°-50°	29.6	5.0
50°-60°	7.7	1.3
60°-70°	5.4	0.9
70°-80°	3.3	0.6
80°-90°	1.2	0.2
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	454.1	76.3
0°-40°	547.8	92.1
0°-60°	585.1	98.3
0°-90°	595.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	595.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	864	
5°	843	78
15°	686	190
25°	413	186
35°	144	94
45°	36	30
55°	8	8
65°	5	5
75°	3	3
85°	1	1
90°	0	



TEST NUMBER: P1293985  
CATALOG NUMBER: P3AS09R50W2N902765DE010 E3DL1MW\_2700K

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	863.9
2.5°	858.6
5°	843.3
7.5°	815.8
10°	780.8
12.5°	735.9
15°	685.6
17.5°	627.4
20°	561.3
22.5°	489.9
25°	413.2
27.5°	331.7
30°	256.6
32.5°	193.1
35°	143.9
37.5°	106.3
40°	77.8
42.5°	55.0
45°	36.0
47.5°	20.6
50°	12.2
52.5°	9.0
55°	8.5
57.5°	7.4
60°	6.9
62.5°	6.3
65°	5.3
67.5°	4.8
70°	4.2
72.5°	3.7
75°	3.2
77.5°	2.6
80°	2.1
82.5°	1.6
85°	1.1
87.5°	0.5
90°	0.0

(END OF REPORT)