

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1294006

Luminaire Tested: P3AS09R50W2N902765DE010 E3DLD1GPH\_4000K

Issue Date: 1/30/2026

**Test Information**


Test Method: LM-79-2019  
Report Number: P1294006  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-30)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: IRiS  
Catalog Number: P3AS09R50W2N902765DE010 E3DLD1GPH\_4000K  
Description: 3in Adjustable Tunable White LED luminaire with, R50 optic, 4000K CCT AND, 90CRI ,  
E3DLD1GPH TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 254.0 lumens  
Efficiency: N/A  
Efficacy: 28.2 lumens/watt  
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.93  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct  
  
Input Watts (W): 9  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1294006  
CATALOG NUMBER: P3AS09R50W2N902765DE010 E3DLD1GPH\_4000K

### Luminous Intensity Polar Plot





TEST NUMBER: P1294006

CATALOG NUMBER: P3AS09R50W2N902765DE010 E3DLD1GPH\_4000K

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| RF  | 20  |     |     |     | 20  |     |     |     | 20  |     |     |     | 20  |     |     |     | 20  |     |
| RC  | 80  |     |     |     | 70  |     |     |     | 50  |     |     |     | 30  |     |     |     | 10  | 0   |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50  | 30  | 10  | 50  | 30  | 10  | 50  | 30  | 10  | 0   |
| RCR |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 | 106 | 106 | 106 | 102 | 102 | 102 | 100 |
| 1   | 112 | 109 | 106 | 103 | 110 | 107 | 104 | 102 | 103 | 101 | 99  | 99  | 97  | 96  | 95  | 94  | 93  | 91  |
| 2   | 106 | 100 | 95  | 91  | 103 | 98  | 94  | 90  | 95  | 91  | 88  | 92  | 89  | 86  | 89  | 86  | 84  | 83  |
| 3   | 99  | 92  | 86  | 81  | 97  | 90  | 85  | 81  | 88  | 83  | 79  | 85  | 81  | 78  | 83  | 80  | 77  | 75  |
| 4   | 93  | 85  | 78  | 73  | 91  | 83  | 77  | 73  | 81  | 76  | 72  | 79  | 75  | 71  | 77  | 73  | 70  | 69  |
| 5   | 88  | 78  | 72  | 67  | 86  | 77  | 71  | 66  | 75  | 70  | 66  | 74  | 69  | 65  | 72  | 68  | 64  | 63  |
| 6   | 83  | 73  | 66  | 61  | 81  | 72  | 65  | 61  | 70  | 65  | 60  | 69  | 64  | 60  | 67  | 63  | 59  | 58  |
| 7   | 78  | 68  | 61  | 56  | 77  | 67  | 61  | 56  | 66  | 60  | 56  | 64  | 59  | 55  | 63  | 59  | 55  | 53  |
| 8   | 74  | 63  | 57  | 52  | 73  | 63  | 56  | 52  | 61  | 56  | 52  | 60  | 55  | 51  | 59  | 55  | 51  | 50  |
| 9   | 70  | 59  | 53  | 48  | 69  | 59  | 52  | 48  | 58  | 52  | 48  | 57  | 52  | 48  | 56  | 51  | 48  | 46  |
| 10  | 66  | 56  | 49  | 45  | 65  | 55  | 49  | 45  | 54  | 49  | 45  | 54  | 48  | 45  | 53  | 48  | 45  | 43  |

**AVERAGE LUMINANCE (cd/sqm):**

|     |       |
|-----|-------|
|     | 0°    |
| 0°  | 51619 |
| 5°  | 50847 |
| 10° | 48607 |
| 15° | 45017 |
| 20° | 40464 |
| 25° | 35567 |
| 30° | 30232 |
| 35° | 24521 |
| 40° | 18435 |
| 45° | 11877 |
| 50° | 5629  |
| 55° | 4435  |
| 60° | 4210  |
| 65° | 3891  |
| 70° | 3526  |
| 75° | 3219  |
| 80° | 2904  |
| 85° | 3019  |

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 45°  
 Luminance: 11877 cd/sqm



TEST NUMBER: P1294006

CATALOG NUMBER: P3AS09R50W2N902765DE010 E3DLD1GPH\_4000K

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 21.7   | 8.5       |
| 10°-20°   | 55.3   | 21.8      |
| 20°-30°   | 67.2   | 26.4      |
| 30°-40°   | 57.0   | 22.4      |
| 40°-50°   | 29.6   | 11.7      |
| 50°-60°   | 10.7   | 4.2       |
| 60°-70°   | 7.4    | 2.9       |
| 70°-80°   | 4.0    | 1.6       |
| 80°-90°   | 1.3    | 0.5       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| 0°-30°    | 144.1  | 56.7      |
| 0°-40°    | 201.1  | 79.2      |
| 0°-60°    | 241.4  | 95.0      |
| 0°-90°    | 254.0  | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 254.0  | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°  | Flux |
|-----|-----|------|
| 0°  | 235 |      |
| 5°  | 231 | 22   |
| 15° | 198 | 55   |
| 25° | 147 | 67   |
| 35° | 92  | 57   |
| 45° | 38  | 30   |
| 55° | 12  | 11   |
| 65° | 8   | 7    |
| 75° | 4   | 4    |
| 85° | 1   | 1    |
| 90° | 0   |      |



TEST NUMBER: P1294006  
CATALOG NUMBER: P3AS09R50W2N902765DE010 E3DLD1GPH\_4000K

**CANDELA DISTRIBUTION (FULL):**

|       | 0°    |
|-------|-------|
| 0°    | 235.4 |
| 2.5°  | 234.5 |
| 5°    | 231.0 |
| 7.5°  | 225.8 |
| 10°   | 218.3 |
| 12.5° | 208.7 |
| 15°   | 198.3 |
| 17.5° | 186.4 |
| 20°   | 173.4 |
| 22.5° | 160.0 |
| 25°   | 147.0 |
| 27.5° | 133.4 |
| 30°   | 119.4 |
| 32.5° | 105.5 |
| 35°   | 91.6  |
| 37.5° | 78.0  |
| 40°   | 64.4  |
| 42.5° | 51.3  |
| 45°   | 38.3  |
| 47.5° | 25.5  |
| 50°   | 16.5  |
| 52.5° | 12.8  |
| 55°   | 11.6  |
| 57.5° | 10.4  |
| 60°   | 9.6   |
| 62.5° | 8.4   |
| 65°   | 7.5   |
| 67.5° | 6.4   |
| 70°   | 5.5   |
| 72.5° | 4.6   |
| 75°   | 3.8   |
| 77.5° | 2.9   |
| 80°   | 2.3   |
| 82.5° | 1.7   |
| 85°   | 1.2   |
| 87.5° | 0.6   |
| 90°   | 0.0   |

(END OF REPORT)