

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1294244

Luminaire Tested: P3AS09R55W2N902765DE010 E3CD1MMS\_2700K

Issue Date: 1/30/2026

**Test Information**


Test Method: LM-79-2019  
Report Number: P1294244  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-36)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: IRiS  
Catalog Number: P3AS09R55W2N902765DE010 E3CD1MMS\_2700K  
Description: 3in Adjustable Tunable White LED luminaire with, R55 optic, 2700K CCT AND, 90CRI ,  
E3CD1MMS TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 703.0 lumens  
Efficiency: N/A  
Efficacy: 78.1 lumens/watt  
Spacing Criteria (0/90/45): 0.94 / 0.94 / 0.82  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct  
  
Input Watts (W): 9  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1294244  
CATALOG NUMBER: P3AS09R55W2N902765DE010 E3CD1MMS\_2700K

### Luminous Intensity Polar Plot







TEST NUMBER: P1294244

CATALOG NUMBER: P3AS09R55W2N902765DE010 E3CD1MMS\_2700K

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	84.8	12.1
10°-20°	242.6	34.5
20°-30°	270.4	38.5
30°-40°	88.5	12.6
40°-50°	11.7	1.7
50°-60°	2.5	0.4
60°-70°	1.5	0.2
70°-80°	0.9	0.1
80°-90°	0.2	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	597.9	85.0
0°-40°	686.3	97.6
0°-60°	700.5	99.6
0°-90°	703.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	703.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	889	
5°	878	85
15°	873	243
25°	614	270
35°	117	88
45°	14	12
55°	2	2
65°	2	1
75°	1	1
85°	0	0
90°	0	



TEST NUMBER: P1294244  
CATALOG NUMBER: P3AS09R55W2N902765DE010 E3CD1MMS\_2700K

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	889.2
2.5°	882.8
5°	877.6
7.5°	890.2
10°	902.4
12.5°	896.1
15°	872.8
17.5°	835.8
20°	783.0
22.5°	710.1
25°	614.5
27.5°	492.9
30°	356.6
32.5°	218.7
35°	116.8
37.5°	59.2
40°	31.2
42.5°	20.1
45°	13.7
47.5°	9.5
50°	5.3
52.5°	3.2
55°	2.1
57.5°	2.1
60°	2.1
62.5°	1.6
65°	1.6
67.5°	1.1
70°	1.1
72.5°	1.1
75°	1.1
77.5°	0.5
80°	0.5
82.5°	0.5
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)