

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1295455

Luminaire Tested: P3AS13R15W2N902750DE010 E3PH1MW_4000K

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1295455
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2509-551-1)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R15W2N902750DE010 E3PH1MW_4000K
Description: 3in Adjustable Tunable White LED luminaire with, R15 optic, 4000K CCT AND, 90CRI ,
E3PH1MW TRIM
Light Source: -
Ballast/Driver: -


Summary

Lumens per Lamp: N/A
Luminaire Lumens: 663.0 lumens
Efficiency: N/A
Efficacy: 53.9 lumens/watt
Spacing Criteria (0/90/45): 0.31 / 0.31 / 0.29
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 12.3
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1295455
CATALOG NUMBER: P3AS13R15W2N902750DE010 E3PH1MW_4000K

Luminous Intensity Polar Plot





TEST NUMBER: P1295455

CATALOG NUMBER: P3AS13R15W2N902750DE010 E3PH1MW_4000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

| | | | | | | | | | | | | | | | | | | |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| RF | 20 | | | | 20 | | | | 20 | | | | 20 | | | | 20 | |
| RC | 80 | | | | 70 | | | | 50 | | | | 30 | | | | 10 | 0 |
| RW | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 0 |
| RCR | | | | | | | | | | | | | | | | | | |
| 0 | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 | 106 | 106 | 106 | 102 | 102 | 102 | 100 |
| 1 | 116 | 114 | 113 | 111 | 114 | 112 | 111 | 110 | 108 | 107 | 106 | 105 | 104 | 103 | 101 | 101 | 100 | 99 |
| 2 | 113 | 110 | 108 | 106 | 111 | 109 | 107 | 105 | 106 | 104 | 103 | 103 | 102 | 100 | 100 | 99 | 98 | 97 |
| 3 | 111 | 107 | 104 | 102 | 109 | 106 | 103 | 101 | 104 | 101 | 100 | 101 | 100 | 98 | 99 | 98 | 97 | 96 |
| 4 | 109 | 104 | 101 | 99 | 107 | 103 | 101 | 99 | 102 | 99 | 98 | 100 | 98 | 97 | 98 | 97 | 95 | 94 |
| 5 | 107 | 102 | 99 | 97 | 105 | 101 | 99 | 96 | 100 | 98 | 96 | 99 | 96 | 95 | 97 | 96 | 94 | 93 |
| 6 | 105 | 100 | 97 | 95 | 104 | 100 | 97 | 95 | 98 | 96 | 94 | 97 | 95 | 93 | 96 | 94 | 93 | 92 |
| 7 | 103 | 98 | 95 | 93 | 102 | 98 | 95 | 93 | 97 | 94 | 93 | 96 | 94 | 92 | 95 | 93 | 92 | 91 |
| 8 | 101 | 97 | 94 | 92 | 101 | 96 | 94 | 92 | 96 | 93 | 91 | 95 | 93 | 91 | 94 | 92 | 91 | 90 |
| 9 | 100 | 95 | 92 | 90 | 99 | 95 | 92 | 90 | 94 | 92 | 90 | 94 | 91 | 90 | 93 | 91 | 90 | 89 |
| 10 | 99 | 94 | 91 | 89 | 98 | 94 | 91 | 89 | 93 | 91 | 89 | 93 | 90 | 89 | 92 | 90 | 89 | 88 |

AVERAGE LUMINANCE (cd/sqm):

| | |
|-----|---------|
| | 0° |
| 0° | 1397892 |
| 5° | 1212015 |
| 10° | 589301 |
| 15° | 125721 |
| 20° | 26416 |
| 25° | 7863 |
| 30° | 1696 |
| 35° | 294 |
| 40° | 0 |
| 45° | 0 |
| 50° | 0 |
| 55° | 0 |
| 60° | 0 |
| 65° | 0 |
| 70° | 0 |
| 75° | 0 |
| 80° | 0 |
| 85° | 0 |

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 0 cd/sqm



TEST NUMBER: P1295455
 CATALOG NUMBER: P3AS13R15W2N902750DE010 E3PH1MW_4000K

ZONAL LUMENS:

| Zone | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10° | 430.1 | 64.9 |
| 10°-20° | 213.9 | 32.3 |
| 20°-30° | 17.8 | 2.7 |
| 30°-40° | 1.2 | 0.2 |
| 40°-50° | 0.0 | 0.0 |
| 50°-60° | 0.0 | 0.0 |
| 60°-70° | 0.0 | 0.0 |
| 70°-80° | 0.0 | 0.0 |
| 80°-90° | 0.0 | 0.0 |
| 90°-100° | 0.0 | 0.0 |
| 100°-110° | 0.0 | 0.0 |
| 110°-120° | 0.0 | 0.0 |
| 120°-130° | 0.0 | 0.0 |
| 130°-140° | 0.0 | 0.0 |
| 140°-150° | 0.0 | 0.0 |
| 150°-160° | 0.0 | 0.0 |
| 160°-170° | 0.0 | 0.0 |
| 170°-180° | 0.0 | 0.0 |
| 0°-30° | 661.8 | 99.8 |
| 0°-40° | 663.0 | 100.0 |
| 0°-60° | 663.0 | 100.0 |
| 0°-90° | 663.0 | 100.0 |
| 90°-120° | 0.0 | 0.0 |
| 90°-150° | 0.0 | 0.0 |
| 90°-180° | 0.0 | 0.0 |
| 0°-180° | 663.0 | 100.0 |

CANDELA DISTRIBUTION:

| | 0° | Flux |
|-----|------|------|
| 0° | 6375 | |
| 5° | 5506 | 430 |
| 15° | 554 | 214 |
| 25° | 32 | 18 |
| 35° | 1 | 1 |
| 45° | 0 | 0 |
| 55° | 0 | 0 |
| 65° | 0 | 0 |
| 75° | 0 | 0 |
| 85° | 0 | 0 |
| 90° | 0 | |



TEST NUMBER: P1295455
CATALOG NUMBER: P3AS13R15W2N902750DE010 E3PH1MW_4000K

CANDELA DISTRIBUTION (FULL):

| | 0° |
|-------|--------|
| 0° | 6374.9 |
| 2.5° | 6151.8 |
| 5° | 5506.2 |
| 7.5° | 4215.9 |
| 10° | 2646.6 |
| 12.5° | 1273.4 |
| 15° | 553.8 |
| 17.5° | 282.5 |
| 20° | 113.2 |
| 22.5° | 56.0 |
| 25° | 32.5 |
| 27.5° | 16.8 |
| 30° | 6.7 |
| 32.5° | 2.2 |
| 35° | 1.1 |
| 37.5° | 1.1 |
| 40° | 0.0 |
| 42.5° | 0.0 |
| 45° | 0.0 |
| 47.5° | 0.0 |
| 50° | 0.0 |
| 52.5° | 0.0 |
| 55° | 0.0 |
| 57.5° | 0.0 |
| 60° | 0.0 |
| 62.5° | 0.0 |
| 65° | 0.0 |
| 67.5° | 0.0 |
| 70° | 0.0 |
| 72.5° | 0.0 |
| 75° | 0.0 |
| 77.5° | 0.0 |
| 80° | 0.0 |
| 82.5° | 0.0 |
| 85° | 0.0 |
| 87.5° | 0.0 |
| 90° | 0.0 |

(END OF REPORT)