

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1296561

Luminaire Tested: P3AS13R30W2N902765DE010 E3DLD1GPH_3500K

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1296561
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-14)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS13R30W2N902765DE010 E3DLD1GPH_3500K
Description: 3in Adjustable Tunable White LED luminaire with, R30 optic, 3500K CCT AND, 90CRI ,
E3DLD1GPH TRIM
Light Source: -
Ballast/Driver: -


Summary

Lumens per Lamp: N/A
Luminaire Lumens: 310.0 lumens
Efficiency: N/A
Efficacy: 25.2 lumens/watt
Spacing Criteria (0/90/45): 0.78 / 0.78 / 0.85
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 12.3
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1296561
CATALOG NUMBER: P3AS13R30W2N902765DE010 E3DLD1GPH_3500K

Luminous Intensity Polar Plot





TEST NUMBER: P1296561

CATALOG NUMBER: P3AS13R30W2N902765DE010 E3DLD1GPH_3500K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	30.2	9.7
10°-20°	72.6	23.4
20°-30°	81.8	26.4
30°-40°	65.3	21.1
40°-50°	33.6	10.8
50°-60°	12.6	4.1
60°-70°	8.3	2.7
70°-80°	4.5	1.4
80°-90°	1.3	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	184.5	59.5
0°-40°	249.8	80.6
0°-60°	296.0	95.5
0°-90°	310.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	310.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	334	
5°	325	30
15°	261	73
25°	178	82
35°	105	65
45°	43	34
55°	13	13
65°	8	8
75°	4	4
85°	1	1
90°	0	



TEST NUMBER: P1296561
CATALOG NUMBER: P3AS13R30W2N902765DE010 E3DLD1GPH_3500K

CANDELA DISTRIBUTION (FULL):

0°	
0°	334.0
1°	334.0
2°	332.9
3°	330.9
4°	328.3
5°	325.2
6°	321.4
7°	316.5
8°	311.2
9°	305.1
10°	299.0
11°	292.1
12°	284.9
13°	277.3
14°	269.3
15°	261.0
17.5°	239.7
20°	218.4
22.5°	197.8
25°	178.4
27.5°	159.4
30°	141.5
32.5°	123.2
35°	105.0
37.5°	87.1
40°	70.4
42.5°	55.5
45°	42.6
47.5°	31.6
50°	22.1
52.5°	15.6
55°	12.9
57.5°	11.8
60°	10.7
62.5°	9.5
65°	8.4
67.5°	7.2
70°	6.1
72.5°	4.9
75°	4.2
77.5°	3.4
80°	2.7
82.5°	1.9
85°	1.1
87.5°	0.4



TEST NUMBER: P1296561
CATALOG NUMBER: P3AS13R30W2N902765DE010 E3DLD1GPH_3500K

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0

(END OF REPORT)