

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1297640

Luminaire Tested: P3AS13R50W2N902750DE010 E3DLD1GPH\_5000K

Issue Date: 1/30/2026

**Test Information**


Test Method: LM-79-2019  
Report Number: P1297640  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-30)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: IRiS  
Catalog Number: P3AS13R50W2N902750DE010 E3DLD1GPH\_5000K  
Description: 3in Adjustable Tunable White LED luminaire with, R50 optic, 5000K CCT AND, 90CRI ,  
E3DLD1GPH TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 331.0 lumens  
Efficiency: N/A  
Efficacy: 26.9 lumens/watt  
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.93  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct  
  
Input Watts (W): 12.3  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1297640  
CATALOG NUMBER: P3AS13R50W2N902750DE010 E3DLD1GPH\_5000K

### Luminous Intensity Polar Plot







TEST NUMBER: P1297640

CATALOG NUMBER: P3AS13R50W2N902750DE010 E3DLD1GPH\_5000K

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	28.2	8.5
10°-20°	72.0	21.8
20°-30°	87.5	26.4
30°-40°	74.2	22.4
40°-50°	38.6	11.7
50°-60°	13.9	4.2
60°-70°	9.6	2.9
70°-80°	5.2	1.6
80°-90°	1.7	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	187.8	56.7
0°-40°	262.0	79.2
0°-60°	314.5	95.0
0°-90°	331.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	331.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	307	
5°	301	28
15°	258	72
25°	192	88
35°	119	74
45°	50	39
55°	15	14
65°	10	10
75°	5	5
85°	2	2
90°	0	



TEST NUMBER: P1297640  
CATALOG NUMBER: P3AS13R50W2N902750DE010 E3DLD1GPH\_5000K

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	306.8
2.5°	305.6
5°	301.1
7.5°	294.3
10°	284.5
12.5°	272.0
15°	258.4
17.5°	242.9
20°	225.9
22.5°	208.5
25°	191.5
27.5°	173.8
30°	155.6
32.5°	137.5
35°	119.4
37.5°	101.6
40°	83.9
42.5°	66.9
45°	49.9
47.5°	33.2
50°	21.5
52.5°	16.6
55°	15.1
57.5°	13.6
60°	12.5
62.5°	11.0
65°	9.8
67.5°	8.3
70°	7.2
72.5°	6.0
75°	4.9
77.5°	3.8
80°	3.0
82.5°	2.3
85°	1.5
87.5°	0.8
90°	0.0

(END OF REPORT)