

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1300496

Luminaire Tested: P3AS17R35W2N902750DE010 E3DL1MW\_3500K

Issue Date: 1/30/2026

**Test Information**


Test Method: LM-79-2019  
Report Number: P1300496  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-19)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: IRiS  
Catalog Number: P3AS17R35W2N902750DE010 E3DL1MW\_3500K  
Description: 3in Adjustable Tunable White LED luminaire with, R35 optic, 3500K CCT AND, 90CRI ,  
E3DL1MW TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 1274.0 lumens  
Efficiency: N/A  
Efficacy: 65.7 lumens/watt  
Spacing Criteria (0/90/45): 0.58 / 0.58 / 0.58  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct  
  
Input Watts (W): 19.4  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1300496  
CATALOG NUMBER: P3AS17R35W2N902750DE010 E3DL1MW\_3500K

### Luminous Intensity Polar Plot





TEST NUMBER: P1300496

CATALOG NUMBER: P3AS17R35W2N902750DE010 E3DL1MW\_3500K

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	102	102	102	100
1	114	112	109	107	112	109	107	106	105	104	102	102	100	99	98	97	96	96	96	96	95
2	109	105	101	98	107	103	100	97	100	97	95	97	95	93	94	93	91	91	91	91	90
3	105	99	95	91	103	98	94	90	95	92	89	93	90	88	91	88	86	86	86	86	85
4	100	94	89	85	99	93	88	85	91	87	84	89	85	83	87	84	82	82	82	82	80
5	96	89	84	80	95	88	83	80	86	82	79	85	81	78	83	80	78	78	78	78	76
6	92	85	80	76	91	84	79	76	83	78	75	81	77	75	80	77	74	74	74	74	73
7	89	81	76	72	88	80	75	72	79	75	71	78	74	71	77	73	71	71	71	71	70
8	85	77	72	69	84	77	72	68	76	71	68	75	71	68	74	70	68	68	68	68	67
9	82	74	69	66	81	74	69	65	73	68	65	72	68	65	71	68	65	65	65	65	64
10	79	71	66	63	78	71	66	63	70	66	63	69	65	62	69	65	62	62	62	62	61

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	642558
5°	617520
10°	538044
15°	412125
20°	275731
25°	166824
30°	95736
35°	53538
40°	28453
45°	14668
50°	7027
55°	5543
60°	5307
65°	4410
70°	4680
75°	4067
80°	4546
85°	3019

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 45°  
 Luminance: 14668 cd/sqm



TEST NUMBER: P1300496

CATALOG NUMBER: P3AS17R35W2N902750DE010 E3DL1MW\_3500K

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	255.3	20.0
10°-20°	494.7	38.8
20°-30°	323.8	25.4
30°-40°	131.4	10.3
40°-50°	39.4	3.1
50°-60°	13.4	1.1
60°-70°	9.0	0.7
70°-80°	5.3	0.4
80°-90°	1.8	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1073.8	84.3
0°-40°	1205.1	94.6
0°-60°	1257.9	98.7
0°-90°	1274.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1274.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	2930	
5°	2805	255
15°	1815	495
25°	690	324
35°	200	131
45°	47	39
55°	14	13
65°	8	9
75°	5	5
85°	1	2
90°	0	



TEST NUMBER: P1300496

CATALOG NUMBER: P3AS17R35W2N902750DE010 E3DL1MW\_3500K

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	2930.3
1°	2925.4
2°	2912.1
3°	2885.4
4°	2853.9
5°	2805.4
6°	2744.9
7°	2677.0
8°	2600.6
9°	2513.4
10°	2416.4
11°	2308.6
12°	2195.9
13°	2069.8
14°	1949.9
15°	1815.4
17.5°	1489.4
20°	1181.6
22.5°	908.9
25°	689.5
27.5°	513.8
30°	378.1
32.5°	277.5
35°	200.0
37.5°	141.8
40°	99.4
42.5°	69.1
45°	47.3
47.5°	31.5
50°	20.6
52.5°	15.8
55°	14.5
57.5°	13.3
60°	12.1
62.5°	10.9
65°	8.5
67.5°	7.3
70°	7.3
72.5°	6.1
75°	4.8
77.5°	3.6
80°	3.6
82.5°	2.4
85°	1.2
87.5°	1.2



TEST NUMBER: P1300496  
CATALOG NUMBER: P3AS17R35W2N902750DE010 E3DL1MW\_3500K

CANDELA DISTRIBUTION (continued):

0°  
90° | 0.0

(END OF REPORT)