

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1300728

Luminaire Tested: P3AS17R35W2N902765DE010 E3DLP1WMH\_2700K

Issue Date: 1/30/2026

**Test Information**


Test Method: LM-79-2019  
Report Number: P1300728  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-17)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: IRiS  
Catalog Number: P3AS17R35W2N902765DE010 E3DLP1WMH\_2700K  
Description: 3in Adjustable Tunable White LED luminaire with, R35 optic, 2700K CCT AND, 90CRI ,  
E3DLP1WMH TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 702.0 lumens  
Efficiency: N/A  
Efficacy: 36.2 lumens/watt  
Spacing Criteria (0/90/45): 0.69 / 0.69 / 0.72  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct  
  
Input Watts (W): 19.4  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1300728  
CATALOG NUMBER: P3AS17R35W2N902765DE010 E3DLP1WMH\_2700K

### Luminous Intensity Polar Plot







TEST NUMBER: P1300728

CATALOG NUMBER: P3AS17R35W2N902765DE010 E3DLP1WMH\_2700K

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	92.4	13.2
10°-20°	207.4	29.5
20°-30°	194.0	27.6
30°-40°	118.8	16.9
40°-50°	46.8	6.7
50°-60°	20.6	2.9
60°-70°	12.8	1.8
70°-80°	6.8	1.0
80°-90°	2.4	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	493.8	70.3
0°-40°	612.6	87.3
0°-60°	680.0	96.9
0°-90°	702.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	702.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	1029	
5°	1000	92
15°	752	207
25°	423	194
35°	188	119
45°	57	47
55°	23	21
65°	13	13
75°	6	7
85°	2	2
90°	0	



TEST NUMBER: P1300728

CATALOG NUMBER: P3AS17R35W2N902765DE010 E3DLP1WMH\_2700K

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	1029.0
1°	1030.1
2°	1026.8
3°	1020.4
4°	1010.6
5°	999.8
6°	985.8
7°	969.6
8°	950.1
9°	928.5
10°	903.6
11°	877.7
12°	849.6
13°	819.3
14°	785.8
15°	752.3
17.5°	665.8
20°	579.4
22.5°	496.1
25°	422.6
27.5°	354.5
30°	294.0
32.5°	237.8
35°	188.1
37.5°	143.8
40°	108.1
42.5°	77.8
45°	57.3
47.5°	41.1
50°	31.3
52.5°	25.9
55°	22.7
57.5°	19.5
60°	17.3
62.5°	15.1
65°	13.0
67.5°	10.8
70°	8.6
72.5°	7.6
75°	6.5
77.5°	5.4
80°	4.3
82.5°	3.2
85°	2.2
87.5°	1.1



TEST NUMBER: P1300728

CATALOG NUMBER: P3AS17R35W2N902765DE010 E3DLP1WMH\_2700K

CANDELA DISTRIBUTION (continued):

0°  
90° | 0.0

(END OF REPORT)