

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1301557

Luminaire Tested: P3AS17R50W2N902765DE010 E3DL1GPH_2700K

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1301557
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-31)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3AS17R50W2N902765DE010 E3DL1GPH_2700K
Description: 3in Adjustable Tunable White LED luminaire with, R50 optic, 2700K CCT AND, 90CRI ,
E3DL1GPH TRIM
Light Source: -
Ballast/Driver: -


Summary

Lumens per Lamp: N/A
Luminaire Lumens: 597.0 lumens
Efficiency: N/A
Efficacy: 30.8 lumens/watt
Spacing Criteria (0/90/45): 0.77 / 0.77 / 0.75
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 19.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1301557
CATALOG NUMBER: P3AS17R50W2N902765DE010 E3DL1GPH_2700K

Luminous Intensity Polar Plot





TEST NUMBER: P1301557
 CATALOG NUMBER: P3AS17R50W2N902765DE010 E3DL1GPH_2700K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

| | | | | | | | | | | | | | | | | | | | | | |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| RF | 20 | | | | 20 | | | | 20 | | | | 20 | | | | 20 | | | | |
| RC | 80 | | | | 70 | | | | 50 | | | | 30 | | | | 10 | | | 0 | |
| RW | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 0 |
| RCR | | | | | | | | | | | | | | | | | | | | | |
| 0 | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 | 106 | 106 | 106 | 102 | 102 | 102 | 100 | 100 | 100 | 100 |
| 1 | 114 | 111 | 108 | 106 | 111 | 109 | 106 | 104 | 105 | 103 | 101 | 101 | 99 | 98 | 97 | 96 | 95 | 94 | 94 | 94 | 94 |
| 2 | 108 | 103 | 99 | 96 | 106 | 102 | 98 | 95 | 98 | 95 | 93 | 95 | 93 | 91 | 93 | 91 | 89 | 87 | 87 | 87 | 87 |
| 3 | 103 | 97 | 92 | 88 | 101 | 95 | 91 | 87 | 93 | 89 | 86 | 90 | 87 | 84 | 88 | 85 | 83 | 82 | 82 | 82 | 82 |
| 4 | 98 | 91 | 85 | 81 | 96 | 90 | 85 | 81 | 87 | 83 | 80 | 85 | 82 | 79 | 84 | 80 | 78 | 76 | 76 | 76 | 76 |
| 5 | 93 | 85 | 80 | 75 | 92 | 84 | 79 | 75 | 83 | 78 | 74 | 81 | 77 | 74 | 79 | 76 | 73 | 72 | 72 | 72 | 72 |
| 6 | 89 | 80 | 75 | 71 | 88 | 80 | 74 | 70 | 78 | 73 | 70 | 77 | 73 | 69 | 75 | 72 | 69 | 67 | 67 | 67 | 67 |
| 7 | 85 | 76 | 70 | 66 | 84 | 75 | 70 | 66 | 74 | 69 | 66 | 73 | 69 | 65 | 72 | 68 | 65 | 64 | 64 | 64 | 64 |
| 8 | 81 | 72 | 66 | 62 | 80 | 71 | 66 | 62 | 70 | 65 | 62 | 69 | 65 | 62 | 68 | 64 | 61 | 60 | 60 | 60 | 60 |
| 9 | 78 | 68 | 63 | 59 | 76 | 68 | 62 | 59 | 67 | 62 | 59 | 66 | 62 | 58 | 65 | 61 | 58 | 57 | 57 | 57 | 57 |
| 10 | 74 | 65 | 59 | 56 | 73 | 65 | 59 | 56 | 64 | 59 | 55 | 63 | 58 | 55 | 62 | 58 | 55 | 54 | 54 | 54 | 54 |

AVERAGE LUMINANCE (cd/sqm):

| | |
|-----|--------|
| | 0° |
| 0° | 190072 |
| 5° | 186242 |
| 10° | 174457 |
| 15° | 156164 |
| 20° | 131425 |
| 25° | 100312 |
| 30° | 65175 |
| 35° | 38655 |
| 40° | 22328 |
| 45° | 11195 |
| 50° | 4162 |
| 55° | 3250 |
| 60° | 3026 |
| 65° | 2750 |
| 70° | 2693 |
| 75° | 2711 |
| 80° | 2652 |
| 85° | 2768 |

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 11195 cd/sqm



TEST NUMBER: P1301557

CATALOG NUMBER: P3AS17R50W2N902765DE010 E3DL1GPH_2700K

ZONAL LUMENS:

| Zone | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10° | 78.7 | 13.2 |
| 10°-20° | 190.2 | 31.9 |
| 20°-30° | 186.6 | 31.3 |
| 30°-40° | 94.0 | 15.7 |
| 40°-50° | 29.7 | 5.0 |
| 50°-60° | 7.7 | 1.3 |
| 60°-70° | 5.5 | 0.9 |
| 70°-80° | 3.4 | 0.6 |
| 80°-90° | 1.2 | 0.2 |
| 90°-100° | 0.0 | 0.0 |
| 100°-110° | 0.0 | 0.0 |
| 110°-120° | 0.0 | 0.0 |
| 120°-130° | 0.0 | 0.0 |
| 130°-140° | 0.0 | 0.0 |
| 140°-150° | 0.0 | 0.0 |
| 150°-160° | 0.0 | 0.0 |
| 160°-170° | 0.0 | 0.0 |
| 170°-180° | 0.0 | 0.0 |
| 0°-30° | 455.6 | 76.3 |
| 0°-40° | 549.6 | 92.1 |
| 0°-60° | 587.0 | 98.3 |
| 0°-90° | 597.0 | 100.0 |
| 90°-120° | 0.0 | 0.0 |
| 90°-150° | 0.0 | 0.0 |
| 90°-180° | 0.0 | 0.0 |
| 0°-180° | 597.0 | 100.0 |

CANDELA DISTRIBUTION:

| | 0° | Flux |
|-----|-----|------|
| 0° | 867 | |
| 5° | 846 | 79 |
| 15° | 688 | 190 |
| 25° | 415 | 187 |
| 35° | 144 | 94 |
| 45° | 36 | 30 |
| 55° | 8 | 8 |
| 65° | 5 | 5 |
| 75° | 3 | 3 |
| 85° | 1 | 1 |
| 90° | 0 | |



TEST NUMBER: P1301557
CATALOG NUMBER: P3AS17R50W2N902765DE010 E3DL1GPH_2700K

CANDELA DISTRIBUTION (FULL):

| | 0° |
|-------|-------|
| 0° | 866.8 |
| 2.5° | 861.5 |
| 5° | 846.1 |
| 7.5° | 818.5 |
| 10° | 783.5 |
| 12.5° | 738.4 |
| 15° | 687.9 |
| 17.5° | 629.5 |
| 20° | 563.2 |
| 22.5° | 491.5 |
| 25° | 414.6 |
| 27.5° | 332.8 |
| 30° | 257.4 |
| 32.5° | 193.7 |
| 35° | 144.4 |
| 37.5° | 106.7 |
| 40° | 78.0 |
| 42.5° | 55.2 |
| 45° | 36.1 |
| 47.5° | 20.7 |
| 50° | 12.2 |
| 52.5° | 9.0 |
| 55° | 8.5 |
| 57.5° | 7.4 |
| 60° | 6.9 |
| 62.5° | 6.4 |
| 65° | 5.3 |
| 67.5° | 4.8 |
| 70° | 4.2 |
| 72.5° | 3.7 |
| 75° | 3.2 |
| 77.5° | 2.7 |
| 80° | 2.1 |
| 82.5° | 1.6 |
| 85° | 1.1 |
| 87.5° | 0.5 |
| 90° | 0.0 |

(END OF REPORT)