

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1302234

Luminaire Tested: P3AS17R60W2N902765DE010 E3DLD1GPH\_4000K

Issue Date: 1/30/2026

**Test Information**


Test Method: LM-79-2019  
Report Number: P1302234  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-38)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: IRiS  
Catalog Number: P3AS17R60W2N902765DE010 E3DLD1GPH\_4000K  
Description: 3in Adjustable Tunable White LED luminaire with, R60 optic, 4000K CCT AND, 90CRI ,  
E3DLD1GPH TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 490.0 lumens  
Efficiency: N/A  
Efficacy: 25.3 lumens/watt  
Spacing Criteria (0/90/45): 0.94 / 0.94 / 1  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct  
  
Input Watts (W): 19.4  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1302234  
CATALOG NUMBER: P3AS17R60W2N902765DE010 E3DLD1GPH\_4000K

### Luminous Intensity Polar Plot





TEST NUMBER: P1302234

CATALOG NUMBER: P3AS17R60W2N902765DE010 E3DLD1GPH\_4000K

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	112	109	106	103	110	107	104	101	102	100	98	99	97	95	95	94	93	91
2	105	99	94	90	103	97	93	89	94	90	87	91	88	85	88	86	84	82
3	99	91	85	80	96	89	84	79	87	82	78	84	80	77	82	78	76	74
4	92	83	77	72	90	82	76	71	80	75	70	78	73	70	76	72	69	67
5	87	77	70	65	85	76	69	65	74	68	64	72	67	63	71	66	63	61
6	82	71	64	59	80	70	64	59	69	63	58	67	62	58	66	61	58	56
7	77	66	59	54	75	65	59	54	64	58	54	63	57	53	61	57	53	51
8	72	61	55	50	71	61	54	50	60	54	49	59	53	49	58	53	49	47
9	68	57	51	46	67	57	50	46	56	50	46	55	49	46	54	49	45	44
10	65	54	47	43	64	53	47	43	52	47	43	52	46	42	51	46	42	41

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	86989
5°	86000
10°	83031
15°	78434
20°	72293
25°	65472
30°	58136
35°	49657
40°	39503
45°	27848
50°	16648
55°	8411
60°	8070
65°	7420
70°	6860
75°	6524
80°	6061
85°	4529

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 45°  
 Luminance: 27848 cd/sqm



TEST NUMBER: P1302234

CATALOG NUMBER: P3AS17R60W2N902765DE010 E3DLD1GPH\_4000K

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	36.7	7.5
10°-20°	96.6	19.7
20°-30°	124.0	25.3
30°-40°	115.0	23.5
40°-50°	70.0	14.3
50°-60°	23.3	4.8
60°-70°	14.2	2.9
70°-80°	8.0	1.6
80°-90°	2.3	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	257.3	52.5
0°-40°	372.2	76.0
0°-60°	465.5	95.0
0°-90°	490.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	490.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	397	
5°	391	37
15°	346	97
25°	271	124
35°	186	115
45°	90	70
55°	22	23
65°	14	14
75°	8	8
85°	2	2
90°	0	



TEST NUMBER: P1302234  
CATALOG NUMBER: P3AS17R60W2N902765DE010 E3DLD1GPH\_4000K

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	396.7
2.5°	394.9
5°	390.7
7.5°	383.0
10°	372.9
12.5°	360.4
15°	345.5
17.5°	328.3
20°	309.8
22.5°	290.2
25°	270.6
27.5°	250.4
30°	229.6
32.5°	208.7
35°	185.5
37.5°	161.2
40°	138.0
42.5°	113.6
45°	89.8
47.5°	69.6
50°	48.8
52.5°	29.1
55°	22.0
57.5°	20.2
60°	18.4
62.5°	16.1
65°	14.3
67.5°	12.5
70°	10.7
72.5°	8.9
75°	7.7
77.5°	5.9
80°	4.8
82.5°	3.0
85°	1.8
87.5°	1.2
90°	0.0

(END OF REPORT)