

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1246890

Luminaire Tested: P3A13R309024DE010 E3DL1H

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1246890
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-15)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A13R309024DE010 E3DL1H
Description: 3in Adjustable LED luminaire with, R30 optic, 2400K CCT AND, 90CRI , E3DL1H TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 908.0 lumens
Efficiency: N/A
Efficacy: 62.2 lumens/watt
Spacing Criteria (0/90/45): 0.54 / 0.54 / 0.54
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 14.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1246890

CATALOG NUMBER: P3A13R309024DE010 E3DL1H

Luminous Intensity Polar Plot



TEST NUMBER: P1246890

CATALOG NUMBER: P3A13R309024DE010 E3DL1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	112	110	108	112	110	108	106	106	104	103		102	101	100		99
2	110	105	102	99	107	104	101	98	101	98	96		98	96	94		95
3	105	100	96	92	103	98	95	91	96	93	90		94	91	89		91
4	101	95	90	87	99	94	89	86	92	88	85		90	87	84		88
5	97	90	85	82	96	89	85	81	88	84	81		86	83	80		85
6	94	86	81	78	92	85	81	77	84	80	77		83	79	76		81
7	90	82	77	74	89	82	77	74	81	76	73		80	76	73		79
8	87	79	74	71	86	79	74	71	78	73	70		77	73	70		76
9	84	76	71	68	83	75	71	68	75	70	67		74	70	67		73
10	81	73	68	65	80	73	68	65	72	68	65		71	67	65		71

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	529848
5°	504313
10°	424196
15°	305904
20°	189763
25°	107909
30°	59933
35°	32605
40°	17175
45°	9303
50°	4981
55°	3288
60°	3026
65°	3113
70°	2757
75°	2203
80°	2147
85°	2264

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 9303 cd/sqm

TEST NUMBER: P1246890

CATALOG NUMBER: P3A13R309024DE010 E3DL1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	206.3	22.7
10°-20°	366.7	40.4
20°-30°	211.9	23.3
30°-40°	80.4	8.9
40°-50°	24.7	2.7
50°-60°	8.3	0.9
60°-70°	5.6	0.6
70°-80°	3.1	0.3
80°-90°	0.9	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	784.9	86.4
0°-40°	865.4	95.3
0°-60°	898.4	98.9
0°-90°	908.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	908.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2416	
5°	2291	206
15°	1348	367
25°	446	212
35°	122	80
45°	30	25
55°	9	8
65°	6	6
75°	3	3
85°	1	1
90°	0	

TEST NUMBER: P1246890

CATALOG NUMBER: P3A13R309024DE010 E3DL1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	2416.3
1°	2414.6
2°	2400.0
3°	2372.5
4°	2338.2
5°	2291.1
6°	2231.0
7°	2164.1
8°	2089.5
9°	2000.3
10°	1905.1
11°	1802.1
12°	1693.2
13°	1579.1
14°	1463.3
15°	1347.5
17.5°	1062.8
20°	813.2
22.5°	603.0
25°	446.0
27.5°	324.2
30°	236.7
32.5°	170.7
35°	121.8
37.5°	84.9
40°	60.0
42.5°	42.0
45°	30.0
47.5°	20.6
50°	14.6
52.5°	10.3
55°	8.6
57.5°	7.7
60°	6.9
62.5°	6.0
65°	6.0
67.5°	5.1
70°	4.3
72.5°	3.4
75°	2.6
77.5°	2.6
80°	1.7
82.5°	1.7
85°	0.9
87.5°	0.0



TEST NUMBER: P1246890

CATALOG NUMBER: P3A13R309024DE010 E3DL1H

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0

(END OF REPORT)