

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1246906

Luminaire Tested: P3A13R309024DE010 E3DLP1WMH

Issue Date: 1/30/2026

**Test Information**

Test Method: LM-79-2019  
Report Number: P1246906  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-13)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: IRiS  
Catalog Number: P3A13R309024DE010 E3DLP1WMH  
Description: 3in Adjustable LED luminaire with, R30 optic, 2400K CCT AND, 90CRI , E3DLP1WMH TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 553.0 lumens  
Efficiency: N/A  
Efficacy: 37.9 lumens/watt  
Spacing Criteria (0/90/45): 0.66 / 0.66 / 0.7  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct

Input Watts (W): 14.6  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1246906

CATALOG NUMBER: P3A13R309024DE010 E3DLP1WMH

### Luminous Intensity Polar Plot



TEST NUMBER: P1246906

CATALOG NUMBER: P3A13R309024DE010 E3DLP1WMH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|-----|-----|-----|--|-----|
| RF  | 20  |     |     |     | 20  |     |     |     | 20  |     |     |  | 20  |     |     |  | 20  |
| RC  | 80  |     |     |     | 70  |     |     |     | 50  |     |     |  | 30  |     |     |  | 10  |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50  | 30  | 10  |  | 50  | 30  | 10  |  | 50  |
| RCR |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 |  | 106 | 106 | 106 |  | 102 |
| 1   | 113 | 110 | 108 | 105 | 111 | 108 | 106 | 104 | 104 | 102 | 100 |  | 100 | 99  | 97  |  | 97  |
| 2   | 107 | 102 | 98  | 95  | 105 | 101 | 97  | 94  | 97  | 94  | 92  |  | 94  | 92  | 90  |  | 92  |
| 3   | 102 | 95  | 90  | 86  | 100 | 94  | 89  | 85  | 91  | 87  | 84  |  | 89  | 86  | 83  |  | 87  |
| 4   | 97  | 89  | 84  | 79  | 95  | 88  | 83  | 79  | 86  | 81  | 78  |  | 84  | 80  | 77  |  | 82  |
| 5   | 92  | 84  | 78  | 73  | 90  | 83  | 77  | 73  | 81  | 76  | 72  |  | 79  | 75  | 72  |  | 78  |
| 6   | 88  | 79  | 73  | 68  | 86  | 78  | 72  | 68  | 76  | 71  | 68  |  | 75  | 71  | 67  |  | 74  |
| 7   | 83  | 74  | 68  | 64  | 82  | 74  | 68  | 64  | 72  | 67  | 63  |  | 71  | 67  | 63  |  | 70  |
| 8   | 80  | 70  | 64  | 60  | 78  | 70  | 64  | 60  | 69  | 63  | 60  |  | 67  | 63  | 60  |  | 67  |
| 9   | 76  | 67  | 61  | 57  | 75  | 66  | 60  | 57  | 65  | 60  | 56  |  | 64  | 60  | 56  |  | 63  |
| 10  | 73  | 63  | 58  | 54  | 72  | 63  | 57  | 54  | 62  | 57  | 54  |  | 61  | 57  | 53  |  | 61  |

**AVERAGE LUMINANCE (cd/sqm):**

|     |        |
|-----|--------|
|     | 0°     |
| 0°  | 188976 |
| 5°  | 183094 |
| 10° | 164971 |
| 15° | 136459 |
| 20° | 105663 |
| 25° | 79263  |
| 30° | 57528  |
| 35° | 38334  |
| 40° | 23558  |
| 45° | 13831  |
| 50° | 8494   |
| 55° | 6881   |
| 60° | 6008   |
| 65° | 4877   |
| 70° | 4424   |
| 75° | 4321   |
| 80° | 3283   |
| 85° | 4277   |

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 13831 cd/sqm

TEST NUMBER: P1246906

CATALOG NUMBER: P3A13R309024DE010 E3DLP1WMH

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 76.5   | 13.8      |
| 10°-20°   | 165.6  | 29.9      |
| 20°-30°   | 150.6  | 27.2      |
| 30°-40°   | 91.1   | 16.5      |
| 40°-50°   | 36.5   | 6.6       |
| 50°-60°   | 16.2   | 2.9       |
| 60°-70°   | 9.7    | 1.8       |
| 70°-80°   | 5.3    | 1.0       |
| 80°-90°   | 1.5    | 0.3       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| 0°-30°    | 392.7  | 71.0      |
| 0°-40°    | 483.8  | 87.5      |
| 0°-60°    | 536.4  | 97.0      |
| 0°-90°    | 553.0  | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 553.0  | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°  | Flux |
|-----|-----|------|
| 0°  | 862 |      |
| 5°  | 832 | 77   |
| 15° | 601 | 166  |
| 25° | 328 | 151  |
| 35° | 143 | 91   |
| 45° | 45  | 37   |
| 55° | 18  | 16   |
| 65° | 9   | 10   |
| 75° | 5   | 5    |
| 85° | 2   | 2    |
| 90° | 0   |      |

TEST NUMBER: P1246906

CATALOG NUMBER: P3A13R309024DE010 E3DLP1WMH

**CANDELA DISTRIBUTION (FULL):**

| 0°    |       |
|-------|-------|
| 0°    | 861.8 |
| 1°    | 860.9 |
| 2°    | 857.5 |
| 3°    | 851.5 |
| 4°    | 842.9 |
| 5°    | 831.8 |
| 6°    | 818.0 |
| 7°    | 803.5 |
| 8°    | 784.6 |
| 9°    | 763.2 |
| 10°   | 740.9 |
| 11°   | 715.1 |
| 12°   | 687.7 |
| 13°   | 660.3 |
| 14°   | 630.3 |
| 15°   | 601.1 |
| 17.5° | 524.8 |
| 20°   | 452.8 |
| 22.5° | 385.9 |
| 25°   | 327.6 |
| 27.5° | 274.4 |
| 30°   | 227.2 |
| 32.5° | 183.5 |
| 35°   | 143.2 |
| 37.5° | 109.8 |
| 40°   | 82.3  |
| 42.5° | 60.0  |
| 45°   | 44.6  |
| 47.5° | 33.4  |
| 50°   | 24.9  |
| 52.5° | 19.7  |
| 55°   | 18.0  |
| 57.5° | 15.4  |
| 60°   | 13.7  |
| 62.5° | 11.1  |
| 65°   | 9.4   |
| 67.5° | 8.6   |
| 70°   | 6.9   |
| 72.5° | 6.0   |
| 75°   | 5.1   |
| 77.5° | 4.3   |
| 80°   | 2.6   |
| 82.5° | 1.7   |
| 85°   | 1.7   |
| 87.5° | 0.9   |



TEST NUMBER: P1246906

CATALOG NUMBER: P3A13R309024DE010 E3DLP1WMH

CANDELA DISTRIBUTION (continued):

0°  
90° | 0.0

(END OF REPORT)