

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1246962

Luminaire Tested: P3A13R409024DE010 E3DLP1H

Issue Date: 1/30/2026

**Test Information**

Test Method: LM-79-2019  
Report Number: P1246962  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-21)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: IRiS  
Catalog Number: P3A13R409024DE010 E3DLP1H  
Description: 3in Adjustable LED luminaire with, R40 optic, 2400K CCT AND, 90CRI , E3DLP1H TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 630.0 lumens  
Efficiency: N/A  
Efficacy: 43.1 lumens/watt  
Spacing Criteria (0/90/45): 0.73 / 0.73 / 0.74  
Luminous Opening: Circular (Dia: 0.25' x H: 0')  
CIE Type: Direct

Input Watts (W): 14.6  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1246962

CATALOG NUMBER: P3A13R409024DE010 E3DLP1H

### Luminous Intensity Polar Plot





TEST NUMBER: P1246962

CATALOG NUMBER: P3A13R409024DE010 E3DLP1H

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|-----|-----|-----|--|-----|
| RF  | 20  |     |     |     | 20  |     |     |     | 20  |     |     |  | 20  |     |     |  | 20  |
| RC  | 80  |     |     |     | 70  |     |     |     | 50  |     |     |  | 30  |     |     |  | 10  |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50  | 30  | 10  |  | 50  | 30  | 10  |  | 50  |
| RCR |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 |  | 106 | 106 | 106 |  | 102 |
| 1   | 113 | 110 | 108 | 105 | 111 | 108 | 106 | 104 | 104 | 102 | 100 |  | 100 | 99  | 97  |  | 97  |
| 2   | 107 | 102 | 98  | 95  | 105 | 101 | 97  | 93  | 97  | 94  | 91  |  | 94  | 92  | 89  |  | 92  |
| 3   | 102 | 95  | 90  | 86  | 100 | 94  | 89  | 85  | 91  | 87  | 84  |  | 89  | 85  | 83  |  | 86  |
| 4   | 97  | 89  | 83  | 79  | 95  | 88  | 83  | 79  | 86  | 81  | 78  |  | 84  | 80  | 77  |  | 82  |
| 5   | 92  | 83  | 77  | 73  | 90  | 82  | 77  | 73  | 81  | 76  | 72  |  | 79  | 75  | 71  |  | 77  |
| 6   | 87  | 78  | 72  | 68  | 86  | 78  | 72  | 68  | 76  | 71  | 67  |  | 75  | 70  | 67  |  | 73  |
| 7   | 83  | 74  | 68  | 64  | 82  | 73  | 68  | 64  | 72  | 67  | 63  |  | 71  | 66  | 63  |  | 70  |
| 8   | 79  | 70  | 64  | 60  | 78  | 69  | 64  | 60  | 68  | 63  | 59  |  | 67  | 63  | 59  |  | 66  |
| 9   | 76  | 66  | 60  | 56  | 75  | 66  | 60  | 56  | 65  | 60  | 56  |  | 64  | 59  | 56  |  | 63  |
| 10  | 72  | 63  | 57  | 53  | 71  | 62  | 57  | 53  | 62  | 57  | 53  |  | 61  | 56  | 53  |  | 60  |

**AVERAGE LUMINANCE (cd/sqm):**

|     |        |
|-----|--------|
|     | 0°     |
| 0°  | 196168 |
| 5°  | 192207 |
| 10° | 178955 |
| 15° | 155960 |
| 20° | 125684 |
| 25° | 94215  |
| 30° | 66238  |
| 35° | 43393  |
| 40° | 26278  |
| 45° | 15692  |
| 50° | 9347   |
| 55° | 7531   |
| 60° | 6754   |
| 65° | 5811   |
| 70° | 5514   |
| 75° | 4321   |
| 80° | 4293   |
| 85° | 4277   |

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 15692 cd/sqm

TEST NUMBER: P1246962

CATALOG NUMBER: P3A13R409024DE010 E3DLP1H

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 81.1   | 12.9      |
| 10°-20°   | 189.2  | 30.0      |
| 20°-30°   | 178.3  | 28.3      |
| 30°-40°   | 103.1  | 16.4      |
| 40°-50°   | 41.1   | 6.5       |
| 50°-60°   | 18.2   | 2.9       |
| 60°-70°   | 11.2   | 1.8       |
| 70°-80°   | 5.9    | 0.9       |
| 80°-90°   | 1.9    | 0.3       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| <hr/>     |        |           |
| 0°-30°    | 448.6  | 71.2      |
| 0°-40°    | 551.7  | 87.6      |
| 0°-60°    | 611.0  | 97.0      |
| 0°-90°    | 630.0  | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 630.0  | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°  | Flux |
|-----|-----|------|
| 0°  | 895 |      |
| 5°  | 873 | 81   |
| 15° | 687 | 189  |
| 25° | 389 | 178  |
| 35° | 162 | 103  |
| 45° | 51  | 41   |
| 55° | 20  | 18   |
| 65° | 11  | 11   |
| 75° | 5   | 6    |
| 85° | 2   | 2    |
| 90° | 0   |      |

TEST NUMBER: P1246962

CATALOG NUMBER: P3A13R409024DE010 E3DLP1H

**CANDELA DISTRIBUTION (FULL):**

| 0°    |       |
|-------|-------|
| 0°    | 894.6 |
| 2.5°  | 889.4 |
| 5°    | 873.2 |
| 7.5°  | 843.1 |
| 10°   | 803.7 |
| 12.5° | 750.5 |
| 15°   | 687.0 |
| 17.5° | 615.8 |
| 20°   | 538.6 |
| 22.5° | 461.4 |
| 25°   | 389.4 |
| 27.5° | 322.5 |
| 30°   | 261.6 |
| 32.5° | 208.4 |
| 35°   | 162.1 |
| 37.5° | 122.7 |
| 40°   | 91.8  |
| 42.5° | 68.6  |
| 45°   | 50.6  |
| 47.5° | 36.9  |
| 50°   | 27.4  |
| 52.5° | 22.3  |
| 55°   | 19.7  |
| 57.5° | 18.0  |
| 60°   | 15.4  |
| 62.5° | 12.9  |
| 65°   | 11.2  |
| 67.5° | 9.4   |
| 70°   | 8.6   |
| 72.5° | 6.9   |
| 75°   | 5.1   |
| 77.5° | 4.3   |
| 80°   | 3.4   |
| 82.5° | 2.6   |
| 85°   | 1.7   |
| 87.5° | 0.9   |
| 90°   | 0.0   |

(END OF REPORT)