

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1247482

Luminaire Tested: P3A17R659024DE010 E3DLP1LI

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1247482
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-41)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A17R659024DE010 E3DLP1LI
Description: 3in Adjustable LED luminaire with, R65 optic, 2400K CCT AND, 90CRI , E3DLP1LI TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 787.0 lumens
Efficiency: N/A
Efficacy: 37.1 lumens/watt
Spacing Criteria (0/90/45): 0.79 / 0.79 / 0.83
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 21.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1247482

CATALOG NUMBER: P3A17R659024DE010 E3DLP1LI

Luminous Intensity Polar Plot



TEST NUMBER: P1247482

CATALOG NUMBER: P3A17R659024DE010 E3DLP1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	107	105	110	108	105	103	104	102	100		100	98	97		96
2	107	101	97	93	104	100	96	92	96	93	90		93	91	88		90
3	101	94	88	84	99	92	87	83	90	85	82		87	84	81		85
4	95	87	81	76	93	86	80	76	84	79	75		82	78	74		80
5	90	81	75	70	88	80	74	70	78	73	69		77	72	69		75
6	85	76	69	65	84	75	69	65	73	68	64		72	67	64		71
7	81	71	65	60	79	70	64	60	69	64	60		68	63	59		67
8	77	67	60	56	75	66	60	56	65	59	56		64	59	55		63
9	73	63	57	52	72	62	56	52	61	56	52		60	55	52		59
10	69	59	53	49	68	59	53	49	58	53	49		57	52	49		56

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	200050
5°	195069
10°	181649
15°	162793
20°	140596
25°	116958
30°	92217
35°	68342
40°	47088
45°	29212
50°	15863
55°	9978
60°	8464
65°	7679
70°	6540
75°	5761
80°	5683
85°	5787

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 29212 cd/sqm

TEST NUMBER: P1247482

CATALOG NUMBER: P3A17R659024DE010 E3DLP1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	82.3	10.5
10°-20°	199.3	25.3
20°-30°	220.4	28.0
30°-40°	160.1	20.3
40°-50°	75.0	9.5
50°-60°	25.3	3.2
60°-70°	14.6	1.9
70°-80°	7.6	1.0
80°-90°	2.5	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	502.0	63.8
0°-40°	662.1	84.1
0°-60°	762.3	96.9
0°-90°	787.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	787.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	912	
5°	886	82
15°	717	199
25°	483	220
35°	255	160
45°	94	75
55°	26	25
65°	15	15
75°	7	8
85°	2	2
90°	0	

TEST NUMBER: P1247482

CATALOG NUMBER: P3A17R659024DE010 E3DLP1LI

CANDELA DISTRIBUTION (FULL):

0°	
0°	912.3
2.5°	906.6
5°	886.2
7.5°	855.5
10°	815.8
12.5°	769.3
15°	717.1
17.5°	660.4
20°	602.5
22.5°	542.4
25°	483.4
27.5°	423.2
30°	364.2
32.5°	307.5
35°	255.3
37.5°	207.6
40°	164.5
42.5°	125.9
45°	94.2
47.5°	68.1
50°	46.5
52.5°	31.8
55°	26.1
57.5°	22.7
60°	19.3
62.5°	17.0
65°	14.8
67.5°	12.5
70°	10.2
72.5°	9.1
75°	6.8
77.5°	5.7
80°	4.5
82.5°	3.4
85°	2.3
87.5°	1.1
90°	0.0

(END OF REPORT)