

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1245586

Luminaire Tested: P3A02R129024DE010 E3PHLD1MW

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1245586
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2509-551-9)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A02R129024DE010 E3PHLD1MW
Description: 3in Adjustable LED luminaire with, R12 optic, 2400K CCT AND, 90CRI , E3PHLD1MW TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 159.0 lumens
Efficiency: N/A
Efficacy: 43.0 lumens/watt
Spacing Criteria (0/90/45): 0.56 / 0.56 / 0.66
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 3.7
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1245586

CATALOG NUMBER: P3A02R129024DE010 E3PHLD1MW

Luminous Intensity Polar Plot



TEST NUMBER: P1245586

CATALOG NUMBER: P3A02R129024DE010 E3PHLD1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	108	105	102	109	106	103	101	102	100	97		98	96	95		95
2	104	98	93	89	102	97	92	88	93	89	86		90	87	84		87
3	98	90	84	79	96	88	83	78	85	81	77		83	79	75		81
4	92	82	76	70	90	81	75	70	79	73	69		77	72	68		75
5	86	76	69	64	84	75	68	63	73	67	63		71	66	62		70
6	81	71	63	58	79	70	63	58	68	62	58		67	61	57		65
7	77	66	59	54	75	65	58	54	64	58	53		62	57	53		61
8	72	61	55	50	71	61	54	50	60	54	49		59	53	49		58
9	69	58	51	47	68	57	51	46	56	50	46		55	50	46		54
10	65	54	48	44	64	54	48	44	53	47	43		52	47	43		52

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	46268
5°	43385
10°	35559
15°	27628
20°	21819
25°	17372
30°	13952
35°	11404
40°	9389
45°	7908
50°	6789
55°	5849
60°	5219
65°	4514
70°	4039
75°	3219
80°	2652
85°	1761

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 45°
Luminance: 7908 cd/sqm

TEST NUMBER: P1245586

CATALOG NUMBER: P3A02R129024DE010 E3PHLD1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	17.6	11.1
10°-20°	34.1	21.4
20°-30°	33.1	20.8
30°-40°	26.8	16.9
40°-50°	19.9	12.5
50°-60°	13.9	8.7
60°-70°	8.7	5.5
70°-80°	4.1	2.6
80°-90°	0.7	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	84.8	53.4
0°-40°	111.6	70.2
0°-60°	145.4	91.5
0°-90°	159.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	159.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	211	
5°	197	18
15°	122	34
25°	72	33
35°	43	27
45°	26	20
55°	15	14
65°	9	9
75°	4	4
85°	1	1
90°	0	

TEST NUMBER: P1245586

CATALOG NUMBER: P3A02R129024DE010 E3PHLD1MW

CANDELA DISTRIBUTION (FULL):

	0°
0°	211.0
2.5°	207.5
5°	197.1
7.5°	180.3
10°	159.7
12.5°	139.5
15°	121.7
17.5°	106.7
20°	93.5
22.5°	82.0
25°	71.8
27.5°	62.8
30°	55.1
32.5°	48.5
35°	42.6
37.5°	37.3
40°	32.8
42.5°	28.9
45°	25.5
47.5°	22.7
50°	19.9
52.5°	17.4
55°	15.3
57.5°	13.6
60°	11.9
62.5°	10.1
65°	8.7
67.5°	7.3
70°	6.3
72.5°	4.9
75°	3.8
77.5°	2.8
80°	2.1
82.5°	1.0
85°	0.7
87.5°	0.0
90°	0.0

(END OF REPORT)