

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1246196

Luminaire Tested: P3A05R459024DE010 E3DLD1WMH

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1246196
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-647-26)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A05R459024DE010 E3DLD1WMH
Description: 3in Adjustable LED luminaire with, R45 optic, 2400K CCT AND, 90CRI , E3DLD1WMH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 382.9 lumens
Efficiency: N/A
Efficacy: 53.2 lumens/watt
Spacing Criteria (0/90/45): 0.84 / 0.84 / 0.92
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 7.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1246196

CATALOG NUMBER: P3A05R459024DE010 E3DLD1WMH

Luminous Intensity Polar Plot



TEST NUMBER: P1246196

CATALOG NUMBER: P3A05R459024DE010 E3DLD1WMH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	104	110	107	104	102	103	101	99		99	97	96		96
2	106	100	95	91	103	98	94	90	95	91	88		92	89	86		89
3	99	92	86	82	97	91	85	81	88	83	80		85	81	78		83
4	94	85	78	74	92	84	78	73	81	76	72		79	75	71		77
5	88	79	72	67	86	78	71	67	76	70	66		74	69	65		72
6	83	73	66	61	81	72	66	61	71	65	61		69	64	60		68
7	78	68	61	57	77	67	61	56	66	60	56		65	60	56		64
8	74	64	57	52	73	63	57	52	62	56	52		61	56	52		60
9	70	60	53	49	69	59	53	49	58	52	48		57	52	48		56
10	67	56	50	45	66	56	49	45	55	49	45		54	49	45		53

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	81200
5°	79771
10°	75483
15°	68831
20°	60882
25°	52866
30°	45374
35°	37798
40°	28167
45°	17242
50°	7983
55°	6232
60°	6008
65°	5500
70°	5065
75°	4829
80°	4420
85°	3271

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 17242 cd/sqm

TEST NUMBER: P1246196

CATALOG NUMBER: P3A05R459024DE010 E3DLD1WMH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	33.9	8.8
10°-20°	84.4	22.0
20°-30°	100.3	26.2
30°-40°	87.1	22.8
40°-50°	43.7	11.4
50°-60°	15.2	4.0
60°-70°	10.7	2.8
70°-80°	5.9	1.5
80°-90°	1.8	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	218.6	57.1
0°-40°	305.7	79.8
0°-60°	364.6	95.2
0°-90°	382.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	382.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	370	
5°	362	34
15°	303	84
25°	218	100
35°	141	87
45°	56	44
55°	16	15
65°	11	11
75°	6	6
85°	1	2
90°	0	

TEST NUMBER: P1246196

CATALOG NUMBER: P3A05R459024DE010 E3DLD1WMH

CANDELA DISTRIBUTION (FULL):

0°	
0°	370.3
2.5°	368.6
5°	362.4
7.5°	352.7
10°	339.0
12.5°	322.2
15°	303.2
17.5°	282.0
20°	260.9
22.5°	239.2
25°	218.5
27.5°	198.6
30°	179.2
32.5°	160.7
35°	141.2
37.5°	120.5
40°	98.4
42.5°	76.8
45°	55.6
47.5°	36.6
50°	23.4
52.5°	18.1
55°	16.3
57.5°	15.0
60°	13.7
62.5°	12.4
65°	10.6
67.5°	9.3
70°	7.9
72.5°	6.6
75°	5.7
77.5°	4.4
80°	3.5
82.5°	2.6
85°	1.3
87.5°	0.9
90°	0.0

(END OF REPORT)