

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1426888

Luminaire Tested: P3A20RH9030D010 E3HY1WMH

Issue Date: 3/9/2026

Test Information

Test Method: LM-79-2019
Report Number: P1426888
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2601-658-2)
Test Lab: INNOVATION CENTER
Issue Date: 3/9/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A20RH9030D010 E3HY1WMH
Description: 3in Adjustable LED luminaire with, RH optic, 3000K CCT AND, 90CRI , E3HY1WMH TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1032.0 lumens
Efficiency: N/A
Efficacy: 35.8 lumens/watt
Spacing Criteria (0/90/45): 0.61 / 0.61 / 0.55
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 28.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1426888

CATALOG NUMBER: P3A20RH9030D010 E3HY1WMH

Luminous Intensity Polar Plot



TEST NUMBER: P1426888

CATALOG NUMBER: P3A20RH9030D010 E3HY1WMH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	112	110	108	112	110	108	106	106	104	103		102	101	100		99
2	109	105	102	99	107	104	100	98	100	98	96		97	95	93		95
3	105	99	95	92	103	98	94	91	95	92	89		93	90	88		91
4	101	94	89	86	99	93	89	85	91	87	84		89	86	83		87
5	96	89	84	81	95	88	84	80	87	83	79		85	82	79		84
6	93	85	80	76	91	84	79	76	83	78	75		81	78	75		80
7	89	81	76	72	88	80	75	72	79	75	72		78	74	71		77
8	85	77	72	69	84	77	72	68	76	71	68		75	71	68		74
9	82	74	69	65	81	73	69	65	73	68	65		72	68	65		71
10	79	71	66	62	78	70	66	62	70	65	62		69	65	62		68

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	515814
5°	467619
10°	404958
15°	368016
20°	205305
25°	127483
30°	102193
35°	55600
40°	28024
45°	12559
50°	4025
55°	650
60°	0
65°	0
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 12559 cd/sqm

TEST NUMBER: P1426888

CATALOG NUMBER: P3A20RH9030D010 E3HY1WMH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	192.7	18.7
10°-20°	410.9	39.8
20°-30°	252.8	24.5
30°-40°	137.9	13.4
40°-50°	34.6	3.3
50°-60°	3.1	0.3
60°-70°	0.0	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	856.4	83.0
0°-40°	994.3	96.3
0°-60°	1032.0	100.0
0°-90°	1032.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1032.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2352	
5°	2124	193
15°	1621	411
25°	527	253
35°	208	138
45°	40	35
55°	2	3
65°	0	0
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1426888

CATALOG NUMBER: P3A20RH9030D010 E3HY1WMH

CANDELA DISTRIBUTION (FULL):

0°	
0°	2352.3
2.5°	2293.2
5°	2124.4
7.5°	1945.4
10°	1818.7
12.5°	1722.5
15°	1621.1
17.5°	1290.2
20°	879.8
22.5°	589.4
25°	526.9
27.5°	471.1
30°	403.6
32.5°	302.3
35°	207.7
37.5°	141.9
40°	97.9
42.5°	65.9
45°	40.5
47.5°	22.0
50°	11.8
52.5°	5.1
55°	1.7
57.5°	1.7
60°	0.0
62.5°	0.0
65°	0.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)