

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1255697

Luminaire Tested: P3A24R259035D010 E3D1LI

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1255697
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2501-338-9)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3A24R259035D010 E3D1LI
Description: 3in Adjustable LED luminaire with, R25 optic, 3500K CCT AND, 90CRI , E3D1LI TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2758.0 lumens
Efficiency: N/A
Efficacy: 95.8 lumens/watt
Spacing Criteria (0/90/45): 0.44 / 0.44 / 0.4
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 28.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1255697

CATALOG NUMBER: P3A24R259035D010 E3D1LI

Luminous Intensity Polar Plot



TEST NUMBER: P1255697

CATALOG NUMBER: P3A24R259035D010 E3D1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	99	99
1	115	113	111	110	113	111	110	108	107	106	105	104	103	102	100	99	99	97	96	96
2	112	108	106	103	110	107	104	102	104	102	100	101	99	98	98	97	96	94	93	93
3	109	104	101	98	107	103	100	97	100	98	96	98	96	94	96	94	93	92	91	91
4	106	101	97	94	104	100	96	94	98	95	92	96	93	91	94	92	90	89	88	88
5	103	97	93	91	101	96	93	90	95	92	90	93	91	89	92	90	88	87	86	86
6	100	94	90	88	99	94	90	87	92	89	87	91	88	86	90	88	86	85	84	84
7	98	92	88	85	97	91	87	85	90	87	84	89	86	84	88	86	84	83	82	82
8	95	89	85	83	94	89	85	83	88	85	82	87	84	82	86	84	82	81	80	80
9	93	87	83	81	92	86	83	80	86	83	80	85	82	80	84	82	80	79	78	78
10	91	85	81	79	90	84	81	79	84	81	78	83	80	78	83	80	78	77	76	76

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	3020526
5°	2798078
10°	2164912
15°	1034035
20°	340930
25°	143718
30°	55705
35°	24092
40°	8015
45°	3721
50°	1365
55°	765
60°	439
65°	519
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 45°
Luminance: 3721 cd/sqm

TEST NUMBER: P1255697

CATALOG NUMBER: P3A24R259035D010 E3D1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1117.4	40.5
10°-20°	1270.8	46.1
20°-30°	295.3	10.7
30°-40°	62.0	2.2
40°-50°	10.0	0.4
50°-60°	1.7	0.1
60°-70°	0.9	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2683.5	97.3
0°-40°	2745.5	99.5
0°-60°	2757.1	100.0
0°-90°	2758.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2758.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	13775	
5°	12712	###
15°	4555	1271
25°	594	295
35°	90	62
45°	12	10
55°	2	2
65°	1	1
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1255697

CATALOG NUMBER: P3A24R259035D010 E3D1LI

CANDELA DISTRIBUTION (FULL):

0°	
0°	13774.7
1°	13746.7
2°	13603.7
3°	13402.7
4°	13095.7
5°	12711.7
6°	12218.7
7°	11702.7
8°	11123.8
9°	10470.8
10°	9722.8
11°	8855.8
12°	7860.8
13°	6770.9
14°	5630.9
15°	4554.9
16°	3602.9
17°	2806.9
18°	2208.0
19°	1766.0
20°	1461.0
21°	1221.0
22°	1025.0
23°	856.0
24°	716.0
25°	594.0
27.5°	352.0
30°	220.0
32.5°	141.0
35°	90.0
37.5°	54.0
40°	28.0
42.5°	18.0
45°	12.0
47.5°	7.0
50°	4.0
52.5°	2.0
55°	2.0
57.5°	1.0
60°	1.0
62.5°	1.0
65°	1.0
67.5°	1.0
70°	0.0
72.5°	0.0

TEST NUMBER: P1255697

CATALOG NUMBER: P3A24R259035D010 E3D1LI

CANDELA DISTRIBUTION (continued):

	0°
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)